[INCH-POUND]
A-A-2679A
August 10, 1995
SUPERSEDING
A-A-2679
May 1, 1991

COMMERCIAL ITEM DESCRIPTION

SAW, CIRCULAR, PNEUMATIC, PORTABLE

This Commercial Item Description is approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. Scope. This commercial item description covers 12-inch, portable, pneumatic circular saws primarily intended for cutting steel, stone, masonry, ceramics, plastics, and other ferrous and nonferrous materials.
2. Salient Characteristics.

2.1 Design. Circular saws supplied in accordance with this description shall be of the manufacturer's current design, be similar to Figure 1 and shall be in accordance with Table I. The saw shall be of the 12 inch size with a safety lock-off throttle. The saw shall operate properly at pressures between 80-100 psig.




Figure 1. Saw.

Table I

National Stock Number	Specified Torque ft. - lbs. (min.)	Speed at Specified Torque RPM (min.)	Speed at No Load RPM (max.)	Air Consumption scfm/hp (max.)	90° Depth of cut inches (min.)	45° Depth of Cut inches (min.)
5130-00-239-5813	10	1500	2400	38	3-7/8	2-3/4

2.2 Motor. The motor shall be the rotary-vane type.

Beneficial comments, recommendations, additions, deletions, clarifications, etc., and any other data which may improve this document should be sent to: General Services Administration, Federal Supply Service, Tools and Appliances Commodity Center (6FETE-CO), Washington, DC 20406.

FSC 5130

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:25Z
Check the source to verify that this is the current version before use.

2.3 Lubrication: Parts requiring lubrication shall be protected from the entrance of foreign matter and loss of lubricant. The saw shall provide for the delivery of lubricant in a manner that will assure proper operation.

2.4 Materials: The materials used in the construction of all components shall be capable of completing the examination and tests specified herein. All components shall be new and unused; repaired or reconditioned components shall not be acceptable. Housing shall be metal or composite. Cadmium is not an acceptable plating.

2.5 Handle: The saw shall have a closed pistol-grip type handle with an integral throttle valve. The throttle valve shall have a positive safety lock and shall be located within the closed pistol-grip handle to prevent accidental starting of the saw. An auxiliary handle or knob shall be provided and located in such a manner as to make the saw suitable for two-handed operation.

2.6 Bearings: All rotating parts of the saw shall be provided with ball or roller bearings. Ball and roller bearings, which are primarily designed for radial loads, shall not be used to absorb axial thrust. Open-type bearings shall be suitably housed and adequately sealed to prevent leakage of lubricant and entrance of dirt and dust. Sleeve bearings are not acceptable.

2.7 Arbor: The arbor shall be 1.0 inch in diameter. Means shall be provided to preclude the saw blade turning on the arbor in the event the stalled torque of the saw is reached.

2.8 Rotation: The saw blade rotation shall be such that the material being cut will be held against the saw base by the cutting action of the saw blade.

2.9 Saw blade: Unless otherwise specified a 12-inch diameter rip and crosscut saw blade shall be furnished. The blade shall conform to type III, class 1 of Federal Specification GGG-B-440, have 18 style S teeth and arbor hole of a size compatible with the arbor specified.

2.10 Throttle: Saws shall be provided with a non-leaking manual throttle for admitting air supply, gradually regulating the speed of the tool, and automatically shutting off the supply of compressed air when the throttle is released. Saws shall be equipped with a safety lock-off throttle which requires two operations by the same hand as used to turn on the tool. A lock-off device shall automatically and positively lock the throttle in the OFF position when the throttle is released. A lock-off device shall be integral with the tool so it cannot be removed from the tool without modification to the tool and shall operate in such a manner as to prevent the throttle from starting the tool until the lock-off device has been activated.

2.11 Saw-blade guards: The saw shall be provided with guards above and below the base. The guards above and below the base shaft cover the saw blade to the depth of the teeth. The guard below the base, except for the minimum arch of the saw-blade required to enter the work shall be of the automatic, self-closing telescoping type which shall instantly return to covering the saw blade when the saw is withdrawn from the work.

2.12 Base: The base shall support the saw against the material being cut, and shall be securely fastened to the saw housing. The saw shall be provided with means for mounting an adjustable rip-fence on either side of the base. The rip-fence furnished shall provide a minimum rip width of 6 inches.

2.13 Position indicator: The lines, grooves, or pointer shall be located at the leading edge of the base to clearly indicate exactly where the saw blade is going to enter the work when the blade setting is at zero angle and 45 degrees; the lines, grooves, or pointer shall be visible from the user's operating position.

2.14 Angle adjustment: Means shall be provided for adjusting the base from 0 to 45 degrees. A graduated scale shall be provided to clearly indicate the angle setting in increments of not more than 5 degrees from 0 to 45 degrees angle. Angle adjustment and fastening devices shall be accomplished without the use of tools.

2.15 Depth adjustment: The base shall be readily adjustable to control the depth of cut within the minimum vertical and 45 degree depth specified in Table I. Depth adjustment and fastening devices shall be accomplished without the use of tools.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:25Z
Check the source to verify that this is the current version before use.

2.16 Air inlet connection: The air inlet connection shall consist of a 1/2-inch-diameter, well-secured brass or ferrous fitting. The fitting shall be threaded with internal American Standard taper pipe threads and fitted with an air strainer or screen (20 mesh or finer). The screen or air strainer shall be effective in preventing solid particles in the compressed air supply from entering the tool. The strainer or screen shall be of such design that it can be easily removed for cleaning.

2.17 Manual: One copy of a technical manual consisting of the manufacturer's standard commercial instruction and parts list shall be furnished with each tool.

2.18 Carrying Case: Each saw shall be furnished in a metal or plastic carrying case. The case shall be large enough to contain the tool and allow a minimum of 10 cubic inches of space for accessories. The case shall not open when carried by the handle. The case, if metal, shall be made of 0.032-inch-thick (minimum) steel with formed welded corners, a heavy duty snap latch, and a suitable carrying handle of formed metal secured by welding, screws, or rivets. All surfaces of the metal case shall be painted.

2.19 Workmanship: Details of workmanship shall be in accordance with the best commercial standards and practices. Paints, coatings, platings, and finishes shall be smooth, dry, adherent, continuous, and not stained or discolored. Fasteners shall be firmly secured and show no evidence of deformation, cross threading, or hazardous burrs. The adhesives and lubricants adequate for their intended purpose shall be properly and neatly applied. Adhesives shall be adequately cured. There shall be no interference, binding, or galling of parts. External and bearing surfaces shall be free of tool and gouge marks, nicks, or other surface imperfections. The item shall be clean and free of corrosion and debris (e.g., chips, shavings, slivers) or other foreign material. The item shall be free from manufacturing workmanship defects (e.g., loose, missing, binding or misaligned parts, sharp or rough external edges, corners or surfaces) and material workmanship defects (e.g., pits, rips, fins, burrs, tears, nodules, cracks, blisters) which may adversely impact the item's serviceability, durability, safety, or appearance.

3. Regulatory requirements: In accordance with Section 23.403 of the Federal Acquisition Regulations, the Government's policy is to acquire items composed of the highest percentage of recovered materials practicable, consistent with maintaining a satisfactory level of competition without adversely affecting performance requirements or exposing supplier's employees to undue hazards from the recovered materials.

3.1 Metric products: Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within the tolerances specified and all other requirements of this document are met. If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request should be made to the specification preparing activity for change to this document.

4. Quality assurance provisions.

4.1 Responsibility for inspection: Unless otherwise specified in the contract, the Contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services adhere to prescribed requirements.

4.2 Inspection: It shall be determined that the sample units meet all salient characteristics stated in the requirements section of this document. Any sample containing one or more defects shall be rejected, and if the number of rejected units exceeds the acceptance number for that sample, the lot represented by the sample shall be rejected.

4.3 Test conditions: All tests shall be conducted with an air supply of 90 psig (620 kPa) measured as close to the tool as practicable. The test tool shall be connected to the air supply line by means of a 10 foot length of air hose having a hose size of 3/4 inch (inner diameter). The air supply line shall be equipped with a filter, air pressure regulator and lubricator.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:25Z
Check the source to verify that this is the current version before use.

4.4 First article inspection. When specified, the contractor shall furnish one sample of a completely fabricated tool for first article inspection. The sample shall have been manufactured and inspected using the same materials, processes, and methods that will be used in the production of the tools used to fulfill the terms of the contract or purchase order. The sample shall meet the requirements of this Commercial Item Description. Approval of the first article sample shall not relieve the contractor of the responsibility to furnish tools in accordance with the requirements of this Commercial Item Description. First article inspection shall consist of the following evaluation in the sequence listed: Inspection, Air consumption test, Speed test, Torque test, Sound pressure level test, Practical service test, Service test, and Examination after service test.

4.5 Production lot inspection and testing: Production lot testing shall consist of the following evaluations conducted in the sequence listed: Inspection, Air consumption test, Speed test, Torque test, and Practical service test. A sample lot shall consist of all items of same NSN offered for delivery at one time. Sampling procedures shall be in accordance with ANSI/ASQC Z1.4 at an Inspection Level of S-3. The acceptable quality level (AQL) shall be 1.5 defects per 100 units tested. A sample unit shall consist of one completely fabricated tool and accessories.

4.6 Air consumption test: Air consumption shall be measured with either a certified liquid displacement meter or a flowmeter.

4.7 Speed test: Each sample tool shall be tested to determine compliance with the speed requirement specified herein. A stroboscope, tachometer or other suitable device, of sufficient capacity and accuracy, shall be used.

4.8 Torque test: Each sample tool shall be tested to determine compliance with the torque requirement specified herein. The test shall be conducted on a prony brake analyzer or similar system of appropriate capacity calibrated to assure accurate readings.

4.9 Sound pressure level test: The sound pressure level test shall be conducted in accordance with the applicable provisions of the Compressed Air and Gas Institute's "CAGI-PNEUROP Test Code for the Measurement of Sound from Pneumatic Equipment." The sound pressure level shall not exceed 95 decibels on the A weighted scale.

4.10 Practical service test: Each sample tool shall be operated for 5 minutes. The test shall duplicate a typical work application. During the test, the tool shall be checked for throttle operation, rotation, excessive noise or vibration, ease of operation, and general serviceability.

4.11 Service test: A simulated service test shall be conducted for 150 hours. A test sample shall be installed in a fixture in a manner that the tool can be loaded and automatically actuated for 150 hours. Each cycle shall be 10 seconds ON and 30 seconds OFF. The load applied shall be to the specified torque.

4.12 Examination after service test: Tools satisfactorily completing the Service test shall again be subjected to the Sound pressure level test, Air consumption test and shall conform to the applicable requirements of these tests. Upon completion of the Service test, the tool shall be disassembled and the parts examined. Any tool having broken, cracked, or deformed parts shall be rejected.

5. Preservation, packaging, packing, and marking: Tools shall be preserved, packaged, packed, and marked as specified in the contract or purchase order.

5.1 Identification markings: Each item (including all items within a set or kit) shall be marked with the manufacturer's name or identifying symbol, and the state or country of manufacture, unless otherwise specified. All marking shall be engraved, etched, molded, or indented directly on the item's surface in such a manner that it remains clearly legible throughout the life of the item.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:25Z
Check the source to verify that this is the current version before use.

6. Notes:

6.1 The issue of referenced documents in effect on the date of invitation for bids or request for proposal shall be used to determine compliance with the stated requirements. Sources for obtaining referenced documents may be determined by contacting the Contracting Officer.

6.2 Military standards are available from Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19120-5094.

6.3 The "CAGI-PNEUROP Test Code for the Measurement of Sound from Pneumatic Equipment" is available from the Compressed Air and Gas Institute, 1300 Sumner Avenue, Cleveland, OH 44115.

Military Coordinating Activity

Army - GL

Preparing Activity

GSA - FSS

Custodians

Army - GL
Air Force - 99

Review Activities

Air Force - 35, 84

User Activity

Navy - MC

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:25Z
Check the source to verify that this is the currentversion before use.