A-A-52006
March 29, 1988

COMMERCIAL ITEM DESCRIPTION

PLOTTER, PEN, DIGITAL

The General Services Administration has authorized the use of this commercial item description.

This commercial item description covers a multipen digital plotter capable of handling single-sheet or roll media in size A3 to A0, as defined by ANSI/ASME Y14.1, and the plotter transport/storage case.

Salient Characteristics:

Design: The plotter shall be capable of producing A3-A0 size engineering drawings in monochrome single or multiple color. The plotter shall be able to draw at a speed of at least 41 cm/sec., with high resolution (.003 cm.). When raised the pens shall move at a speed of at least 51 cm/sec. Excellent plot quality shall be available at all speeds and in each case shall be repeatable (±.013 cm with the same pen) or (±.02 cm with different pens). The plotter shall be able to receive data at a selectable baud rate of 300, 600, 1200, 2400, 4800 or 9600. A minimum 6 Kbyte memory shall be provided as data buffer. It shall be operable using various media types, such as film, vellum, or paper. The performance of the plotter shall not differ when operating within temperature ranging from 30 °F to 90 °F. The plotter shall not be damaged in a storage temperature that ranges between -25 °F to 120 °F and relative humidity that ranges between 5 percent to 95 percent. The plotter shall be capable of handling single sheet or roll media. It shall have pen carousels or holders that will allow automatic pickup, use, and return of pens to ready location. The carousel or holder shall be capable of holding various types of pens depending on the media being used. The pen carousel or pen holder shall hold a minimum of 8 pens at one time. The plotter shall be capable of using readily available pens to provide a wide range of colors and line weights. The plotter shall be operable in a free standing mode but may be disassembled for transport/storage. It shall interface with all CAD systems including MS DOS based systems. The plotter shall have a 2 cm border limitation on all media. It shall operate on 50 to 60 Hz. It shall also be compatible with the following voltage 100, 120, 140, 200, 220, and 240. The plotter shall have RS-232-C interface capability to allow direct connection to personal computers (ordering data will specify computer system to which plotter will be connected so that connecting cables may be provided as required). Documentation provided with the plotter shall include sufficient information to allow cable selection/manufacturer for connection to a variety of computers. In addition, operating instructions and maintenance instructions should be clear and logical. Information concerning identification of replacement supplies and parts is required. The plotter physical requirements are as follows:

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:04Z
Check the source to verify that this is the current version before use.

Overall Height (free standing) - not to exceed 122 cm
Overall Width - not to exceed 140 cm
Overall Depth - not to exceed 61 cm
Weight - not to exceed 68 Kg

A data plate containing make, model, serial number, manufacturer's address and other data commercially provided shall be affixed in a location that is readily accessible.

Case: The case for the digital plotter shall contain the plotter and will be used primarily for storage and transporting. The design of the case shall be made to accommodate the plotter (in a disassembled state) and operating supplies. (Ordering data will specify quantities and types of supplies.) The exterior of the case shall be made of either ABS plastic, fiberglass or of an aluminum laminate. The wall structure shall be of plywood and shall be either 1/4" , 3/8", or 1/2" AC grade, crossply and multi-layer. Extruded aluminum- edging shall close the case across the edge with corner clamps. The interior cushioning shall be made from either a minimum 2.2 pound density esterfoam, or a high density anti-static or ethafoam treatments. The case shall be designed to allow easy storage and removal of the plotter and supplies. Valene spanning latches along with rubber valence gasket shall be provided. For easier handling, the handles shall be spring-loaded. The case shall be designed to preclude damage to the contents under normal shipping and handling procedures.

Regulatory requirements. The offeror/contractor is encouraged to use recovered material in accordance with Public Law 94-580 to the maximum extent practicable.

Packing and marking. Military packaging shall be specified when shipments are to consignees outside the continental United States and for nonspecific end item users in the continental United States. Commercial packaging may be specified for shipments to specific end item users within the continental United States.

Military packaging. Each plotter shall be preserved and packed to protect against physical damage and deterioration in a logistic environment characterized by the following.

1. Multiple handling during transportation and in-transit storage.

2. Shock, vibration, and static loading forces during worldwide shipment.

3. Uncontrolled warehouse storage for extended periods.

4. Weather exposure during shipment and in-transit transfers.

5. Stacking loads during shipment and storage.

Quantities of plotters, destined to a single addressee may be unitized into one or more unit loads.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:04Z
Check the source to verify that this is the current version before use.

Commercial. Each plotter shall be packaged in accordance with supplier's normal method for retail distribution. Plotter's shipped to a single destination may be unitized to permit handling as a single unit. Shipping containers shall comply with the uniform Freight Classification or National Motor Freight Classification rules.

Marking. Unit, intermediate (when provided) and exterior pack shall be marked with the item nomenclature, stock or part number, quantity per pack, and contract number as a minimum. Additional marking shall be as specified in the contract or order. Exterior pack shall have in addition to the complete consignee's address. Marking shall be applied in a legible manner, in a contrasting color, of an appropriate size, and of waterproof material.

Quality assurance. The digital plotter and its case shall be examined for the following defects. Presence of one or more defects shall be cause for rejection of either the plotter or the case.

1. Plotter unable to produce the specified drawing size.
2. Plotter unable to draw and move at specified speed.
3. Repeatability not as specified.
4. Baud rate not as specified.
5. Data buffer not as specified.
6. Hardware problems such as automatic pickup, use and return of pens to a ready location, and repetitive media jams.
7. Supplied materials, such as pen carousel and media types, not as specified.
8. Plotter and personal computer CAD is not electronically compatible for downloading drawing fields to the plotter buffer.
9. Plotter not compatible with the specified voltage.
10. Documentation not provided as specified.
11. Physical requirements of the plotter not as specified.
12. The exterior and interior material for the case is not as specified.
13. The overall construction of the case is not per plotter dimensions.
14. Latches and handles for the case are not as specified.
15. Packaging and marking are not as specified.

Certification of commercial item. The contractor shall certify that the product offered to the Government, meets the salient characteristics of this description

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:04Z
Check the source to verify that this is the current version before use.

and that the product conforms to the producer's own drawing, specifications, standards and quality assurance practices and is the same product as the manufacturer's current product offered by the contractor in the commercial market place for at least one year preceding the solicitation. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter or may be otherwise provided for under the provisions of the contract.

Small business. A small business that can not meet the certification-of-commercial item requirement of this document, may make an offer under this solicitation, and, if such small business is the apparent successful offeror, the Government may require the small business to submit a sample plotter, pen, digital and case. Any such plotter may be evaluated for the solicitation if time to contract award permits. Such evaluation would be to determine conformance to all requirements of the commercial item description and to determine the plotter's equivalency to other digital plotter's and cases available in the commercial market place in the area of durability, human factors engineering, and safety. It should be noted that samples are not required unless specifically requested by the Contracting Officer. NOTE: The Government may elect not to evaluate a sample from an apparent low bidder for award for this solicitation if a determination of users is made by the Contracting Officer. The sample would then be evaluated prior to future solicitation for comparable items.

Ordering data Computer system interface designation, packaging requirements, package quantities, and labeling and marking must be specified in the contract and/or order

Notes

1. When this commercial item description is used for procurement, the commercial item certification clause must appear in the solicitaiton.

MILITARY INTERESTS:

Custodians

Army - ME
Navy - YD
Air Force - 99

Review activities

DLA - GS
Air force - 82

User activities

Navy - CG, MC

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - FCGC

PREPARING ACTIVITY

Army - ME

Project 6675-0838

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:04Z
Check the source to verify that this is the current version before use.