METRIC

A-A-52006B
30 June 2003
A-A-52006A
31 October 1998

COMMERCIAL ITEM DESCRIPTION

PLOTTER, DIGITAL

The General Services Administration has authorized the use of this Commercial Item Description (CID) for all federal agencies.

1. SCOPE.

1.1 Abstract. This CID covers a multi-color, digital plotter capable of handling single sheet or roll media, with transport/storage case. This digital plotter will be used to create Computer-Assisted Design (CAD) system engineering drawings.

2. SALIENT CHARACTERISTICS.

2.1 Plotter. The plotter shall operate in a free-standing mode, but may be disassembled for transport.

2.1.1 Dimensions. The plotter overall height (free-standing) shall not exceed 122.00 cm (48.00 in). The overall width shall not exceed 140.00 cm (55.00 in), and the overall depth shall not exceed 61.00 cm (24.00 in).

2.1.2 Weight. The plotter weight shall not exceed 68.00 kg (149.9 lbs).

2.2 Media. The plotter shall be capable of handling various media types, such as film, vellum, or paper, in single sheet or roll, sizes A3 to A0, as defined by ASME Y14.1.

2.3 Data reception. The plotter shall receive data at the following selectable baud rates: 300, 600, 1200, 2400, 4800, or 9600. A minimum 6K byte memory data buffer shall be provided.

2.4 Pens and holder. When pens are used, the plotter shall be capable of using a variety of commercially available plotting pens providing a wide range of colors and line weights. Pen holders or carousels shall be provided, allowing automatic pick-up, use, and return of pens to a ready location. The holder or carousel shall hold a minimum of 8 pens at one time.

Beneficial comments, recommendations, additions, deletions, clarifications etc., and any other data which may improve this document should be sent to: ENGINEER RESEARCH AND DEVELOPMENT CENTER, CORPS OF ENGINEERS, U.S. ARMY TOPOGRAPHIC ENGINEERING CENTER, ATTN CEERD-TS, 7701 TELEGRAPH ROAD, ALEXANDRIA, VA 22315-3864.

AMSC N/A FSC 6675

Distribution Statement A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:04Z
Check the source to verify that this is the current version before use.

2.5 Drawing capabilities. The plotter shall produce A3-A0 size engineering drawings, with a 2.00 cm (0.79 in) border limitation on all media, in monochrome single or multiple color at a speed of at least 41.00 cm/sec (16.1 in/sec) with high resolution. When pens are used, the pens shall move at a speed of at least 51.00 cm/sec (20.1 in/sec) in the raised position. Plot quality shall be consistent at all speeds and shall be repeatable.

2.6 Interface. The plotter shall interface with all computer-aided design (CAD) systems including MS DOS based systems. The plotter shall have RS-232-C interface capability, allowing direct connection to personal computers (see 6.2).

2.7 Voltage and cycles. The plotter shall operate on 50 and 60 Hz and be compatible with the following voltages: 100, 120, 140, 200, 220, and 240.

2.8 Operating and storage temperature. Plotter performance shall not be adversely affected when operating within temperatures ranging from 30 to 90 °F. The plotter shall not be damaged when stored in temperatures ranging from -25 to 120 °F, and relative humidity from 5 to 95 percent.

2.9 Identification marking. A data plate containing make, model, serial number, and Commercial and Government Entity Code (CAGE) shall be affixed to the plotter in a readily accessible location.

2.10 Instructions. Clear and logical operating and maintenance instructions shall be provided.

2.11 Case. A case shall be provided to store and transport the disassembled plotter and any operating supplies. The case shall be made of a sturdy, lightweight material and shall be weather-tight. The case interior shall be cushioned. Handles shall be spring-loaded for easy use. The case shall prevent damage to its contents under normal shipping and handling conditions.

2.12 Treatment and painting. The carrying case and plotter shall be treated and painted in accordance with the manufacturer's standard practice. Special color or treatment requirements shall be specified (see 6.2).

2.13 Safety. All moving or sharp parts presenting a hazard to personnel shall be fully enclosed or guarded. All electrical system and wiring shall conform to NFPA No. 70, National Electrical Code. Operators shall not have access to components with voltage exceeding 30 V. Safety markings and labels shall identify any potential hazards and comply with ANSI Z535.4.

3. REGULATORY REQUIREMENTS.

3.1 Recoverable materials. In accordance with Section 23.403 of the Federal Acquisition Regulation, the Government's policy is to acquire items composed of the highest percentage of recoverable materials practicable, consistent with maintaining a satisfactory level of competition without adversely affecting performance requirements or exposing the supplier's employees to undue health hazards from recovered materials.

4. QUALITY ASSURANCE PROVISIONS.

4.1 Market acceptability. The plotter offered shall be the latest model of the standard product of the supplier, which has been used in the field for at least one year by commercial organizations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:04Z
Check the source to verify that this is the current version before use.

4.2 Product conformance. The plotter provided shall meet the salient characteristics of this CID, and conform to the manufacturer's drawings, specifications, standards, and quality assurance practices, and be the same product offered for sale in the commercial market. The government reserves the right to require proof of such conformance.

4.3 Examination. Each plotter shall be examined for compliance with the requirements specified in Section 2. Any modification necessary following failure to meet the specified requirements shall receive particular attention for adequacy and suitability. This element of inspection shall encompass all examinations of performance and dimensional requirements. Failure to comply with any specified requirement, or the presence of one or more defects, shall constitute cause for rejection.

5. PACKAGING.

5.1 Packaging. Preservation, packaging, packing, labeling, and marking shall be as specified in the contract or order (see 6.2).

6. NOTES.

6.1 Intended use. The plotter is intended for use in creating CAD system-engineering drawings.

6.2 Ordering data.

a. Title, number, and date of this document.
b. Type of computer system to which plotter will be connected (see 2.6).
c. Special color or treatment requirements (see 2.12).
d. Level of preservation and packing required (see 5.1).

6.3 Data requirements. The contracting officer shall include, in the contract or order, any data requirements, such as maintenance and operation manuals, instructional materials, and technical publications to be furnished with each plotter.

6.4 Provisioning. The contracting officer shall include, in the contract or order, provisioning requirements, maintenance tools (including any special tools), as necessary; and instructions regarding shipment of the plotter.

6.5 Source of documents.

6.5.1 ASME standards are available from the American Society of Mechanical Engineers, 345 East 47th Street, New York, NY 10017.

6.5.2 Defense Logistics Agency, Defense Automated Printing Service, 700 Robbins Avenue, Bldg. 4D, Philadelphia, PA 19111-5094.

6.6 Subject term (key word) listing:

CAD
Drawing, engineering
Equipment, surveying

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:04Z
Check the source to verify that this is the current version before use.

Custodian:
Army - CE3
Navy – YD
DLA-GS

Preparing Activity:
Army - CE3
(Project 6675-0164)

Civilian Coordinating Activity:
GSA – FCGC

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:04Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7, and send to preparing activity.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE *(YYYYMMDD)*
	A-A-52006B	20030630

3. DOCUMENT TITLE: PLOTTER, DIGITAL

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME *(Last, First, Middle Initial)*	b. ORGANIZATION	
c. ADDRESS *(Include Zip Code)*	d. TELEPHONE *(Include Area Code)* (1) Commercial (2) DSN *(If applicable)*	7. DATE SUBMITTED *(YYYYMMDD)*

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (*Include Area Code*)	
U.S. ARMY TOPOGRAPHIC ENGINEERING CENTER	(1) Commercial (703) 428-6862	(2) DSN 328-6862
c. ADDRESS (*Include Zip Code*) ATTN: CEERD-TS 7701 TELEGRAPH ROAD ALEXANDRIA, VA 22315-3864	**IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT:** Defense Standardization Program Office (DLSC-LM) 8725 John J. Kingman Road, Suite 2533 Fort Belvoir, Virginia 22060-6221 Telephone (703) 767-6888 DSN 427-6888	

DD Form 1426, FEB 1999 (EG) PREVIOUS EDITIONS OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:04Z
Check the source to verify that this is the current version before use.