INCH-POUND
A-A-52015A
10 September 2010

SUPERSEDING
A-A-52015
9 January 1990

COMMERCIAL ITEM DESCRIPTION

TAGLINES, CRANE, SPRING-LOADED, REEL TYPE

The General Services Administration has authorized the use of this commercial item description as a replacement for MIL-T-52198 for all federal agencies.

1. SCOPE. This description covers spring-loaded, independently operating, reel type taglines capable of maintaining constant tension on a clamshell bucket or other types of crane loads to prevent rotation while the load is suspended freely.

2. CLASSIFICATION. Taglines shall be one of the following sizes, as specified (see 7.2):

Size 50 - For use with 1/2 cubic yard (yd^3) capacity bucket
Size 75 - For use with 3/4 yd^3 capacity bucket
Size 150 - For use with 1 yd^3 and 1-1/2 yd^3 capacity buckets
Size 200 - For use with 2 yd^3 capacity bucket
Size 350 - For use with 2 yd^3 up to 3-1/2 yd^3 capacity buckets

3. SALIENT CHARACTERISTICS

3.1 General. Taglines shall be a commercial product and the latest model of the manufacturer's standard product that has been manufactured, marketed, and accepted commercially for a period of one year prior to invitation for bid or request for proposal. The manufacturer's latest product improvements incorporated in their current production taglines are acceptable. When specific requirements are not stated herein, all items listed as standard equipment in the manufacturer's published specifications, brochures, and catalogs which are normally furnished to the commercial customer as standard equipment shall be furnished. In addition, the taglines shall be equipped with optional equipment and accessories as required to comply with the performance

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data that may improve this document should be sent to DAMI_STANDARDIZATION@conus.army.mil or U.S. Army RDECOM, Tank Automotive Research, Development and Engineering Center, ATTN: RDTA-EN/STND/TRANS MS #268, 6501 E. 11 Mile Road, Warren, MI 48397-5000. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.daps.dla.mil.

AMSC N/A FSC 3815

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:04Z
Check the source to verify that this is the current version before use.

requirements specified herein. Optional equipment, for the purpose of this item description, may be defined as equipment not standard or normally furnished with the taglines but which is available to the commercial customer on an optional basis. Any additional equipment or accessories specified to satisfy military requirements shall also be considered optional and processed accordingly. The taglines shall be constructed, assembled, and equipped with all components, whether or not specified herein, necessary to enable the item to function reliably and efficiently in sustained operation. The taglines shall conform to all Federal laws and regulations applicable for this type equipment which are in effect on the date of contract award.

3.2 Design. Taglines shall be of the independently operating, automatic reel type with an adjustable tension mechanism permitting desired tension to be attained by manually reversing the rotation of the tagline reel, or with desired tension preset during fabrication. The taglines shall consist essentially of a reel attached to one or more helical spring-loaded cylinders and a fairlead consisting of two sheaves, a bell cable guide, or a spiral spring-loaded reel and a fairlead consisting of two sheaves and two rollers. The taglines shall be capable of being mounted on either side of the crane boom, inside the crane boom, or on the gantry frame. Each tagline shall be complete and ready for operation with the reel filled with wire rope of proper size and length and with all parts necessary for installation.

3.2.1 Reel. The tagline reel shall be of sufficient size to accommodate all necessary wire rope as specified herein. Adequate means shall be provided to anchor one end of the rope to the reel.

3.2.2 Fairlead. The tagline fairlead shall consist of two sheaves, a bell cable guide, or two sheaves and two guide rollers connected to the tagline mechanism by a steel bracket. Fairlead sheaves shall be heat-treated hardened steel with smooth rope grooves. Groove diameters shall be not less than the diameter of the wire rope and the inside diameter of the bell cable guide shall be not less than the diameter of the wire rope specified herein.

3.2.3 Wire rope. Wire rope furnished with the tagline shall be 6 by 19, filler wire construction, improved plow steel, uncoated, fiber core, right regular lay. The diameter of the wire rope shall be not less than 5/16 inch with a nominal breaking strength of not less than 8,400 pounds. The terminal (outside) end of the wire rope shall be properly seized, fitted with a thimble suitable for the wire rope specified herein, and secured by not less than two cable clamps.

3.3 Performance. Taglines, when properly installed, shall be capable of providing sufficient tension to keep the crane load from turning and fouling the crane hoisting and closing lines. Tension exerted shall be sufficient for efficient performance through all operating cycles with a crone equipped with a boom of a length as specified in table I, positioned at a 60 degree angle, and with a clamshell bucket or similar attachment operating in any position from maximum height to not less than 20 feet below ground level. Taglines shall be equipped with sufficient wire rope to permit conformance to the payout capabilities specified in table I, with not less than two full wraps remaining on the reel.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:04Z
Check the source to verify that this is the current version before use.

TABLE I. Performance requirements.

Tagline Size	Bucket Capacity (yd^3)	Crane Boom Length (feet)	Approx. Maximum Tension Required (pounds)	Maximum Wire Rope Payout Capacity (feet)
50	1/2	30	190	60
75	3/4	60	195	70
150	1 and 1-1/2	80	180	90
200	2	100	275	125
350	2 to 3-1/2	80	350	90

3.4 Material. Taglines shall be fabricated from compatible materials, inherently corrosion resistant or treated to provide protection against the various forms of corrosion and deterioration that may be encountered in any of the applicable operating and storage environments to which the taglines may be exposed.

3.5 Treatment and painting. Unless otherwise specified, the taglines shall be cleaned, treated and painted in accordance with the manufacturer's normal method for the commercial market. When specified (see 7.2), the portions of the tagline normally painted shall be cleaned, treated, and painted in accordance with MIL-T-704, type F or G, as applicable. Unless otherwise specified (see 7.2), the finish coat shall be the manufacturer's standard color provided the finished paint thickness required by MIL-T-704 is met. When specified (see 7.2), chemical agent resistant coating (CARC) conforming to MIL-DTL-53039 or MIL-DTL-64159 shall be required.

3.6 Transportability. The taglines shall be capable of highway, rail, and marine transport.

3.6.1 Lifting and tiedown attachments. When specified (see 7.2), the taglines shall have lifting and tiedown attachments. Instructions for the use of the attachments or procedures shall be included on plates permanently affixed to the taglines.

3.7 Preparation for delivery. Prior to delivery, the taglines shall be serviced as required with lubricants for all moving parts. Means to lubricate these parts as required shall also be provided. Pressure lubrication fittings shall not be used where normal lubricating pressure may damage grease or other parts. The taglines lubrication shall include filling tagline barrels when required by design. The tagline shall be conspicuously tagged to identify the lubricants and their temperature range. When specified (see 7.2), the tagline shall be lubricated with military lubricants and required military lubricants shall be as specified by the procuring activity.

4. REGULATORY REQUIREMENTS. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR). For the purpose of this requirement, recovered materials are those materials which have been collected from solid waste and reprocessed to become a source of raw materials as distinguished from virgin raw materials. The component pieces and parts incorporated in the taglines may be newly fabricated from recovered materials to the maximum extent practicable, provided the taglines produced meet all other requirements of this item

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:04Z
Check the source to verify that this is the current version before use.

description. Used, rebuilt or remanufactured components, pieces, and parts shall not be incorporated in the taglines.

5. PRODUCT CONFORMANCE PROVISIONS

5.1 Certification of commercial item. The contractor shall certify that the product offered to the Government meets the salient characteristics of this description and that the product conforms to the producer's own drawings, specifications, standards, quality assurance practices and the manufacturer's current product offered by the contractor in the commercial marketplace for at least one year preceding the solicitation. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract (see 7.2).

5.2 Quality assurance. Each tagline shall be examined for the following defects. Presence of one or more defects shall be cause for rejection.

1. Design not as specified.
2. Size not as specified.
3. Wire roper reel, and fairleads not as specified.
4. Materials not as specified.
5. Treatment and painting not as specified.
6. Transportability not as specified.
7. Lifting and tiedown attachments not as specified.
8. Packaging and marking not as specified.

6. PACKAGING Preservation, packaging, packing, labeling, and marking for the desired level shall be as specified in the contract (see 6.2).

7. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

7.1 Addresses for obtaining copies of Government specifications and standards.
Copies of MIL-T-704 “Treatment and Painting of Materials”, MIL-DTL-53039 “Coating, Aliphatic Polyurethane, Single Component, Chemical Agent Resistant”, and MIL-DTL-64159 “Coating, Water Dispersible Aliphatic Polyurethane, Chemical Agent Resistant” are available from Document Automation and Production Service, Building 4/D, 700 Robbins Avenue, Philadelphia, PA 19111-5094 or https://assist.daps.dla.mil/quicksearch/. The Federal Acquisition Regulation (FAR) may be obtained at the following website: http://www.acquisition.gov/far/.

7.2 Ordering data. The procuring agency should specify the preferred options permitted herein and include the following information in procurement document:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:04Z
Check the source to verify that this is the current version before use.

a. Title, number, and date of this item description.
b. If required, the specific issue of individual documents referenced (see 7.1)
c. Classification (size) required (see 2).
d. When treatment, painting, and paint color other than the manufacturer's standard is required (see 3.5).
e. When CARC coating is required (see 3.5).
f. When lifting and tiedown attachments are required (see 3.6.1).
g. If military lubricants are required (see 3.7).
g. When military packaging is required and specification of those requirements (see 6.1) or if additional markings are required (see 6.4).
h. Certification that the model offered meets all requirements of this commercial item description (see 5.1).
i. When this commercial item description is used for procurement, the commercial item certification clause must appear in the solicitation.
j. When commercial manuals with installation and operating instructions and parts list are required.
k. When a PIN number is required (see 7.3).

7.3 Part or identification number (PIN). The following part identification numbering procedure is for Government purposes and does not constitute a requirement for the contractor (see 7.2). The PINs to be used for taglines acquired to this commercial item description are created as follows:

A 52015 - XX

- XX: Tagline size (see 2):
  - 50 - For use with 1/2 yd^3 capacity bucket
  - 75 - For use with 3/4 yd^3 capacity bucket
  - 150 - For use with 1 yd^3 and 1-1/2 yd^3 capacity buckets
  - 200 - For use with 2 yd^3 capacity bucket
  - 350 - For use with 2 yd^3 up to 3-1/2 yd^3 capacity buckets
- 52015: CID number
- A: CID designator

7.4 Key words.

Clamshell Bucket
Constant Tension
Load Stability

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:04Z
Check the source to verify that this is the current version before use.

Custodians:
Army - AT
Air Force - 99

Review activities:
Army - CE
DLA - CC

Preparing activity:
Army - AT

(Project 3815-2010-001)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:04Z
Check the source to verify that this is the current version before use.