INCH POUND
A-A-52018A
6 January 1992
SUPERSEDING
A-A-52018
21 November 1990

COMMERCIAL ITEM DESCRIPTION

SANDER, FLOOR: POWER DRIVEN, PORTABLE

The General services Administration has authorized the use of this commercial item description in preference to Military Specification MIL-S-12516.

This commercial item description covers an electric-motor-driven, drum type, portable floor sander.

Salient characteristics:

General: The floor sander shall be a commercial product and the latest model of the manufacturer's standard floor sander that has been manufactured, marketed, and accepted commercially for a minimum period of one (1) year prior to invitation for bid or request for proposal. All accessory equipment listed in the manufacturers' published specifications, catalogs, and brochures which are normally furnished to the commercial customer shall be included with each floor sander.

Classification: The floor sander shall be of the following type and width as specified.

Type	IA - 8 inch drum 110 volt minimum 1 hp (for light duty).
Type	IB - 8 inch drum 220 volt minimum 4 hp (for heavy duty).
Type	II - 12 inch drum 220 volt.
Type	III - 10 inch belt sander.
Type	IV - 16 inch screener minimum 1 hp.
Type	V - 7 inch edger 115 volt minimum 1 hp.

Design and construction: The floor sander shall be a heavy duty type, portable, wheel and/or caster mounted, and shall consist of an electric-motor-driven sanding drum, direct or V-belt drive unit, and a dust collecting system all mounted on a rigid frame. The sanding unit shall be fully enclosed with a removable, hinged, or retractable type drum cover to permit access to the sanding drum for service. The floor sander shall be easily maneuverable and controlled

Beneficial comments, recommendations, additions, deletions, clarifications, etc., and other data which may improve this document should be sent by letter to: Commander, US Army Belvoir Research, Development and Engineering Center, ATTN: STRBE-TSE, Fort Belvoir, VA 22060-5606.

AMSC N/A FSC 3220

DISTRIBUTION STATEMENT A. Approved for public release, distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:04Z
Check the source to verify that this is the current version before use.

by a walk-behind steering handle or column, equipped with insulated hand grips. The sanding drum shall be capable of being raised or lowered to any desired sanding position by a hand control lever mounted on the steering handle. Both the on/off power switch and the hand control lever shall be mounted on the steering column adjacent to the hand grips for operator convenience. The drum height lever shall be labeled as to function (i.e. drum height) and the end points of the lever travel shall be labeled as to functional result of the control movement (i.e. UP, DOWN). Means shall be provided to adjust the sanding drum downpressure to obtain a desired finish on any type wood floors. The floor sander shall be capable of limited disassembly to reduce the unit size and weight for portability.

Performance: The floor sander shall perform continuous floor sanding operations from rough-in through finish sanding on all types of wood floors without overload or overheating while using the full grit range of abrasive paper.

Electric motor: The electric motor shall be a continuous duty, AC, 115/230 volt, 50/60 Hz, heavy duty, electric motor with overload protection.

Dust collecting system: The dust collecting system shall be capable of efficient removal of sanding dust and other residue from sanding operations and depositing such residue in a detachable collection bag for disposal.

Sanding drum: The sanding drum assembly shall be reinforced to prevent distortion, machined, and dynamically balanced to avoid chatter and uneven finished surfaces. The drum shall be gear or V-belt driven and equipped with prelubricated, sealed type, ball or roller type bearings.

Wheels: The floor sander shall be mounted on fixed position or swivel type steel or nonmarking type composition wheels with antifriction bearings. The wheels shall be sufficient in number and located to provide maximum stability and maneuverability for the sander to efficiently perform all intended floor sanding operations.

Safety: All belts, shafts, pulleys, and other rotating parts shall be guarded to prevent accidental contact by operating personnel. The floor sander shall comply with all National Electrical Manufacturing Association (NEMA) and National Fire Protection Association (NFPA) regulations as applicable for this type equipment.

Noise limits. The noise levels produced by the sander shall riot exceed 85 dB(A) when measured with an ASA 47, type I meter and when measured with the equipment operating at maximum load. With the sander resting on a level surface, the microphone shall be located 2 feet behind the handle at its shortest position and 5 feet off the surface. If and only if the 85 dB(A) limit is documented as being clearly beyond the state-of-the-art, selection of another noise limit shall be made by the contracting officer on the basis of system requirements. Said

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:04Z
Check the source to verify that this is the current version before use.

documentation must be based upon testing and analysis which clearly and convincingly proves that achievement of the required limit is beyond the state-of-the-art for the sander. Such testing and the resultant analysis shall be conducted and reported by a professionally qualified acoustical consultant or acoustical laboratory. Documentation shall be furnished to the procuring activity for consideration of whether or nut increase of the required limit is justified. If the contracting officer grants written permission to exceed the 85 dB(A), the sander shall be labeled "HEARING PROTECTION REQUIRED WITHIN (specify) FEET". The distance specified shall be the distance from the operator's position at which the 85 dB(A) limit is met.

Treatment and painting: The floor sander shall be treated and painted in accordance with the manufacturer's normal method for retail distribution.

Materials: The floor sander shall be fabricated from compatible materials, inherently corrosion resistant, or treated to provide protection against corrosion and deterioration that may be encountered in the applicable operating and storage environments in which the floor sander may be exposed.

Certification of commercial item. The contractor shall certify that the floor sander offered to the Government meets the salient characteristics of this description and that the floor sander conforms to the producer's own drawings, specifications, manufacturer's current floor sander offered by the contractor in the commercial marketplace for at least one year preceding the solicitation. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Regulatory requirements: The contractor is encouraged to use recovered materials in accordance with Publication 94-580 to the maximum extent practicable. For the purpose of this requirement, recovered materials are those materials which have been collected from solid waste and reprocessed to become a source of raw materials as distinguished from virgin raw materials. The components, pieces, and parts incorporated in the floor sander may be newly fabricated from recovered materials to the maximum extent practicable, provided the floor sander produced meets all requirements of this description. Used, rebuilt, or remanufactured components, parts, and pieces shall not be incorporated in the floor sander.

Packaging and marking: When specified, military packaging shall be required when shipments are to overseas Department of Defense (DOD) consignees. Commercial may be specified for shipment to the DOD consignees within the continental United States and the non-DoD consignees worldwide. When a supplier's normal packaging will satisfy the requirement for military packaging, it may be used.

Military packaging: The floor sander shall be preserved and packed to protect against physical damage and deterioration in a logistic environment characterized by the following:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:04Z
Check the source to verify that this is the current version before use.

1. Multiple handling during transportation and in-transit storage
2. Shock, vibration, and static loading during worldwide shipment by all transport modes.
3. Uncontrolled warehouse storage for extended periods.
4. Weather exposure during shipment and in-transit storage.
5. Stacking loads during shipment and storage.

Commercial packaging: Each floor sander shall be prepared and packaged as applicable in accordance with the supplier's normal method for retail distribution. Shipping containers, when used, shall comply with the Uniform Freight and/or National Motor Freight Classification rules as applicable.

Marking for shipping and storage: Unit, intermediate, and exterior packs shall be marked with the item nomenclature, stock or part number, quantity per pack, and contract number as a minimum; additional marking shall be as specified in the contract or order. Exterior packs shall have the complete consignee's address. All marking shall be applied in a legible manner, in contrasting color, of an appropriate size, and with waterproof materials.

Quality assurance: Each floor sander shall be examined for the following defects. Presence of one or more defects shall be cause for rejection.

1. Design not as specified.
2. Size not as specified.
3. Accessories not as specified.
4. Fabrication not as specified.
5. Treatment and painting not as specified.
6. Safety equipment not as specified.
7. Materials not as specified.
8. Preparation for shipping, packaging, and marking not as specified.

Notes: The procuring agency should specify the preferred options permitted herein and include the following information in the procurement document:

1. Title, number, and date of this item description.
2. Type and class of sander.
3. When military packaging and marking is required.
4. When commercial packaging is required.

ASA 47 is available from the Acoustical Society of America, 335 East 45th Street, New York, New York 10017

National Electrical Manufacturing Association standards are available from the National Electrical Manufacturers Association, 2101 L. Street NW, Washington, DC 20037.

National Fire Protection Association (NFPA) regulations are available from the National Fire Protection Association, Batterymarch Park, Quincy, MA 02269

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:04Z
Check the source to verify that this is the current version before use.

National Motor Freight Classification Rules are available from the National Motor Freight Traffic Association, ATIN: Traffic Order Section, 2200 Mill Road, Alexandria, VA 22314.

Unifor Freight Classification Rules are available from the Uniform Classification Committee, ATTN: Tariff Publishing officer, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.

MIITARY INTERESTS:

Custodian:
Army - ME

User Activity:
DLA - GS

PREPARING ACIVITY:
Army - ME

Project 3220-0167

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:04Z
Check the source to verify that this is the current version before use.