INCH-POUND

MIL-S-63540/1A
AMENDMENT 3
17 December 1997
SUPERSEDING
AMENDMENT 2
31 OCTOBER 1986

MILITARY SPECIFICATION SHEET

STUD, SELF-LOCKING, FLUSH HEAD,RIBBED CLINCH TYPE

This amendment forms a part of MIL-S-63540/1A, dated 31 MARCH 1986, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 3

In Table II, in column for Thread Size .086-56 UNC, Length .750, add dash number “57” for carbon steel and “57C” for CRES.

PAGE 6

INSTALLATION PROCEDURES:

Delete subparagraph identifications “a, b, b, c” and substitute “a, b, c, d”.

PAGE 7

Delete Table IV: Delete in its entirety and substitute new Table IV, below.

TABLE IV. Installation dimensions (Reference)

T THREAD SIZE CLASS 2A	SHEET THICKNESS MIN	HOLE SIZE IN SHEET +.003 -.000	CENTER OF HOLE TO SHEET EDGE MIN	NUT TIGHTENING TORQUE (IN LBS) MAX 1/	ANVIL COUNTERSINK DIAMETER	ANVIL HOLE DIAMETER
.086-56 UNC	.040	.085	.111	2.3	.110 TO .114	.087 TO .090
.112-40 UNC	.040	.111	.219	5	.136 TO .140	.113 TO .116
.138-32 UNC	.040	.137	.250	9	.162 TO .166	.139 TO .142
.164-32 UNC	.040	.163	.281	17	.188 TO .192	.165 TO .168
.190-24 UNC	.040	.189	.281	24	.216 TO .220	.191 TO .194
.190-32 UNC	.040	.189	.281	27	.216 TO .220	.191 TO .194
.250-20 UNC	.062	.249	.313	58	.295 TO .300	.250 TO .253
.313-18 UNC	.093	.311	.375	120		.313 TO .316

1/ This load is the limiting load when the nut is fastened to the stud at installation.

Custodians:
Army - AR
Navy - MC
Air Force - 99

Preparing Activity:
DLA-IS

(Project 5307-0639)

Review activity:
Army - AT, CR CR4
Air Force - 11, 82
NSA - NS

AMSC N/A

FSC 5307

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:04Z
Check the source to verify that this is the current version before use.