INCH-POUND

PPP-P-600G
December 31, 1992
SUPERSEDING
PPP-P-600F
April 26, 1977

FEDERAL SPECIFICATION

PORCELAIN ENAMEL PRODUCTS AND HOUSEHOLD APPLIANCES, ELECTRICAL AND MECHANICAL - REQUIREMENTS FOR PACKAGING OF

The General Services Administration has authorized the use of this federal specification, for all federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers performance requirements for levels A, B, and C packaging of porcelain enamel products, household appliances (see 6.1).

1.2 Classification. The shipment of appliances or products shall be divided into the following gross weight-test groups:

Weight-test group 1 - 100 pounds and over

Weight-test group 1A - Up to 100 pounds

2. APPLICABLE DOCUMENTS

2.1 Government documents. The following documents, of the issues in effect on the date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be used in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5018 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC PACK

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:50Z
Check the source to verify that this is the current version before use.

Federal Specifications

PPP-B-576	-	Boxes, Wood-Cleated Panelboard
PPP-B-585	-	Boxes, Wood, Wirebound
PPP-B-601	-	Boxes, Wood, Cleated-Plywood
PPP-B-621	-	Boxes, Wood, Nailed and Lock-Corner
PPP-B-636	-	Boxes, Shipping, Fiberboard
PPP-B-640	-	Boxes, Fiberboard, Corrugated, Triple-Wall
PPP-V-205	-	Veneer, Paper Overlaid, Container-Grade

Federal Standards

FED-STD-101	-	Test Procedures for Packaging Materials
FED-STD-123	-	Marking for Shipment (Civil Agencies)

(Activities outside the federal Government may obtain copies of federal specifications, standards, and commercial item descriptions as outlined under General Information in the Index of Federal Specifications, Standards and Commercial Item Descriptions. The Index, which includes cumulative bi-monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402-0001.)

(Single copies of this specification and other federal specifications and commercial item descriptions required by activities outside the federal Government for bidding purposes are available without charge from General Services Administration Business Service Centers, Regional Offices in Boston, MA; New York, NY; Washington, DC; Atlanta, GA; Chicago, IL; Kansas City, MO; Fort Worth, TX; Denver, CO; San Francisco, CA; Los Angeles, CA; and Seattle, WA.)

(Federal Government activities may obtain copies of federal standardization documents and the index of Federal Specifications, Standards and Commercial Item descriptions from established distribution points in their agencies.)

Military Specifications

MIL-C-104	-	Crates, Wood; Lumber and Plywood Sheathed, Nailed and Bolted
MIL-C-11133	-	Crates, Shipping, Wood, Open, Wirebound
MIL-C-52950	-	Crates, Wood, Open and Covered

Military Standards

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	-	Marking for Shipment and Storage
MIL-STD-731	-	Quality of Wood Members for Containers and Pallets

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:50Z
Check the source to verify that this is the currentversion before use.

MIL-STD-1186 - Cushioning, Anchoring, Bracing, Blocking and Waterproofing; with Appropriate Test Methods

(Copies of military specifications and standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Federal Regulation

Regulations governing United States Code Congressional and Administrative News - Resource Conservation and Recovery Act of 1976 (Public Law 94-580)

U.S. Department of Commerce (USDC)

PS 1 - Product Standard for Construction and Industrial Plywood

(Application for copies should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402).

(The code of Federal Regulations (CFR) and the Federal Register (FR) are for sale on a subscription basis from the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402. When indicated, reprints of certain regulations may be obtained from the federal agency responsible for issuance thereof.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

American Plywood Association (APA)

APA PRP-108 - Performance Standards and Policies for Structural-Use Panels

(Application for copies should be addressed to the American Plywood Association, 7011 South 19th Street, P.O. Box 11700, Tacoma, WA 98411-0700.)

American Society for Testing And Materials (ASTM)

D 3951 - Standard Practice for Commercial Packaging
D 4727 - Standard Specification for Corrugated and Solid Fiberboard Sheet Stock (Container Grade) and Cut Shapes

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187).

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:50Z
Check the source to verify that this is the currentversion before use.

Hardwood Plywood Manufacturers Association (HPMA)

American National Standards Institute (ANSI)

ANSI/HMPA HPI-1 1992 Interim Standard for Hardwood Plywood

(Application for copies should be addressed to the Hardwood Plywood Manufacturer's Association, 1825 Michael Faraday Drive, P.O. Box 2789, Reston, VA 22090-2789.)

(Federal Government activities may obtain copies of those non-Government documents which have been indexed in the Department of Index of Specifications and Standards from the DoD Single Stock Point, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094.)

3. REQUIREMENTS

3.1 Materials. Materials shall be as specified herein.

3.1.1 Recovered material. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practicable.

3.2 Disassembly. Except when disassembly details are specified in the contract or order or in the commodity specification, the extent of disassembly shall be determined by the manufacturer. This determination shall be based on the need for protection of fragile or projecting parts and for reduction in cubage. Parts removed shall be adequately identified or tagged. Where disassembly affects the operation of an appliance, warning tags or labels indicating the disassembly shall be attached. Instructions for assembly shall be furnished with the appliance and may be included as a part of the warning tag, or label, or as a separate sheet or folder attached to the appliance. Disassembly shall not alter calibrations or settings which affect desired overall operation of the product or appliance and shall not be such that special skills and special tools, other than those furnished, or both, are required to place the product or appliance in operation.

3.3 Preservation. Preservation and packaging shall be level A, B, or C as specified (see 6.2).

3.3.1 Levels A, B, and C. Preservation and packaging shall be as provided for in the commodity specification or as specified (see 6.2).

3.4 Packing. Packing shall be level A, B, or C, as specified (see 6.2).

3.4.1 General requirements applicable to levels A, B, or C.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:50Z
Check the source to verify that this is the current version before use.

3.4.1.1 Base. For all packs having a weight of contents in excess of 200 pounds, provisions shall be made to permit handling with power equipment such as fork lift trucks. This may be provided by external skids (see 3.4.2), strips on the bottom of the shipping container, or by strips bolted to the base of the appliance and secured to the inside face of the bottom of the shipping container, positioned in such a manner to ensure adequate protection to the container and contents when handled with power equipment. When strips or skids are secured to inside face of the bottom of the shipping container, the container shall be marked to indicate two opposite sides intended for fork lift truck handling.

3.4.1.1.1 Rubbing strip for skids. For bases exceeding 6 feet in length, skids shall be provided with rubbing strips of nominal 2 inch thick lumber of the same width as skids and shall be attached with staggered rows of nails in accordance with the applicable container specification. Openings in the rubbing strips shall be provided for fork lift truck access. The openings shall be 12 inches in length, 28 inches center to center and positioned to straddle the center of balance of the loaded container. Center pieces of the rubbing strips shall be 16 inches in length. Rubbing strips shall extend to within 6 inches of the ends of the skids. A tolerance of $\pm$ 1/2-inch shall be permitted on the above length dimensions.

3.4.1.2 Design. The choice of design and type of shipping container for levels B and C shipments shall be the option of the supplier. Shipments shall be in accordance with ASTM D 3951. The shipping containers for level A packing shall be as specified in 3.4.2.

3.4.2 Level A. The items, preserved as specified in 3.2, shall be cushioned, blocked, braced, anchored, or bolted in a manner to provide sufficient clearance within a shipping container specified herein and to ensure meeting the test requirements specified in 4.4 for vibration, impact or drop test and compression, as applicable, for level A shipments. The pack shall be considered to have satisfactorily passed the test if, upon examination, the product and its containers are free from damage except for superficial scuffs, scratches, superficial splitting of wood members, punctures of container panels, or dents which may occur on the exterior surfaces of the container. If the container is structurally damaged as a result of the tests, a container conforming to one of the other specifications listed hereinafter shall be used and the tests shall be repeated. The items shall be packed in a shipping container constructed, closed, and strapped in accordance with one of the following specifications:

Type I or III

PPP-B-576	- Class 2
PPP-B-585	- Class 3
PPP-B-601	- Overseas type
PPP-B-621	- Class 2

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:50Z
Check the source to verify that this is the current version before use.

PPP-B-636	- Class weather resistant, grade V2s
PPP-B-640	- Class 2
MIL-C-104	- Type and class optional, style A
MIL-C-11133	- Type, class and style optional, grade A, process 1
MIL-C-52950	- Type, as required

Each shipping container shall be provided with waterproofing in accordance with the applicable requirements of MIL-STD-1186. Alternatively, each PPP-B-636 and PPP-B-640 container may be waterproofed by sealing with tape as specified in the applicable container specification. All packing materials which are subject to exposure to the elements shall be of water resistant types. Each shipping container shall be provided with skids in accordance with the applicable specification. When no skids are provided in the applicable specification, the weight of contents shall not exceed the lesser of either the weight limitation of the applicable specification or 200 pounds and the base shall conform to 3.4.1.1 and 3.4.1.1.1.

3.4.3 Level B. The items, preserved as specified in 3.3, shall be packed in a manner that will ensure meeting the test requirements specified in 4.4 for vibration, compression, and impact, or drop test, as applicable, for level B shipments. The pack shall be considered to have satisfactorily passed the test if, upon examination, the product and its container are free from damage, except for superficial scuffs, scratches, or dents which may occur on the exterior surfaces of the container. Unless otherwise specified (see 6.2), packing materials may be those which are normally used for level C packing with the following exceptions:

(a) When specified (see 6.2), fiberboard shall be grade V3c, V3s or V4s of ASTM D 4727.

(b) For PPP-B-576 boxes, when specified (see 6.2), fiberboard shall be class weather resistant of ASTM D 4727.

(c) When specified for triple-wall corrugated boxes (see 6.2), type CF, class weather resistant, variety TW of ASTM D 4727 shall be used.

(d) When specified (see 6.2), panels shall be either exposure 1 of PS-1 and APA PRP-108 or type II, grade 3.3 or 3.4 of HPMA HP-1 1992.

(e) When treatment is specified (see 6.2), panels and cleats shall have the surface treated with a water repellent wood preservative as specified in PPP-B-601.

(f) Paper overlaid veneer shall conform to type I of PPP-V-205.

(g) Wood shall conform to the requirements of MIL-STD-731, quality classification 2, at the time of fabrication of the container.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:50Z
Check the source to verify that this is the current version before use.

3.4.4 Level C. The items, preserved as specified in 3.3 shall be packed in a manner that will ensure meeting the test requirements specified in 4.4 for vibration, compression, and impact or drop test, as applicable, for level C shipments. The pack shall be considered to have satisfactorily passed the tests if, upon examination, the product is free from damage and the container still affords reasonable and proper protection to the contents. Packing materials may be those materials which are normally used by the supplier and shall conform to ASTM D 3951 and 3.1.1 requirements.

3.5 Marking. Marking shall be in accordance with 3.5.1 or 3.5.2 as specified (see 6.2).

3.5.1 Civil agencies. In addition to any special marking required by the contract or purchase order, interior packages and shipping containers shall be marked in accordance with FED-STD-123.

3.5.2 Military requirements. In addition to any special marking required by the contract or purchase order, interior packages and shipping containers shall be marked in accordance with MIL-STD-129.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of section 3. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.2 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.2.1 Component and material examination. In accordance with 4.1, components and materials shall be examined in accordance with all the

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:50Z
Check the source to verify that this is the currentversion before use.

requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.2.2 End item examination.

4.2.2.1 Examination of end item. When shipping containers are required to be in accordance with one of the shipping containers specified in 3.4.2, the examination shall be in accordance with the applicable quality assurance provisions contained in the shipping container specification. In addition, the following minor defect shall be added to the applicable table used for the above examination: "Marking omitted, incomplete, incorrect, illegible, or not in accordance with contract requirements."

4.2.2.2 Examination of the base of the shipping containers. Examination of the base of the shipping containers, when applicable, to determine compliance with the requirements in 3.4.1.1 and 3.4.1.1.1, shall be in accordance with the defects listed below. The lot shall be expressed in units of shipping containers. The sample unit shall be one shipping container. The inspection level shall be S-2 and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 2.5.

Examine	Defect
Base of packs exceeding 200 pounds	Not provided with internal or exterior skids or strips
	Skids or strips not positioned or secured as specified
Special marking	Marking for forklift truck handling (when applicable) missing or illegible
Skids on bases exceeding 6 feet in length	Rubbing strips missing
	Rubbing strips less than 1-1/2 inch thick
	Any dimension not within tolerance specified (see 3.4.1.1.1)

4.2.3 End item testing.

4.2.3.1 Test report. The tests specified herein are intended to determine compliance with the requirements for level A, B, or C packing and shall be required on one model identical to the item being packed for each level of packing specified in the contract or purchase order. Tests may be conducted either by the manufacturer with his own test equipment or by a commercial testing laboratory and witnessed by a Government representative if the Government so requests. Whether the contract or purchase order is awarded to the original manufacturer, or to a supplier other than the original manufacturer, the tests will not be required by the contractor if a test report from a testing laboratory acceptable to the Government is furnished.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:50Z
Check the source to verify that this is the current version before use.

A test report, indicating no damage to the test item and no functional damage to the container and packing, will be accepted as proof of compliance for the level of packing specified in the contract or purchase order and shall be made available to the inspection service. The test results shall be obtained from tests conducted on an item of the identical model specified in the contract or purchase order. Test results, obtained as a result of tests conducted prior to date of contract or purchase order, shall contain a complete description of the packaging and packing materials, and items packed, within 12 months prior to date of a new contract or purchase order. A packed item tested after date of contract or purchase order shall be made available for identification by the Government representative and remain at the supplier's plant until the last shipment on the contract as a guide in determining that packed machines furnished on the contract conform to the item tested.

4.3 Examination after testing. After the specified tests for levels A, B, and C in 3.4.2, 3.4.3, and 3.4.4 have been conducted, a visual examination shall be made of the shipping container and its contents. Any damage to the contents or functional damage to the container or packing shall be cause for rejection. Structural damage to the container which would result in either spilling of the contents or failure of the container in subsequent handling is cause for rejection. Substantial shifting of contents within the container that would create conditions likely to cause damage during shipment, storage, and reshipment, will also be cause for rejection. Minor container damage, such as chipping, abrasion, and superficial splitting of wood members and punctures of container panels, will not be cause for rejection. When the end item is an electrical appliance, it shall be connected to a power source having the electrical characteristics specified in the contract and operated for a period of not less than one hour. When the end item is an automatically operated electrical or mechanical appliance using thermostat(s), timer(s) or similar devices, it shall be connected to the operating source and operated through two complete automatic cycles, including automatic defrost cycle of refrigerators and freezers. Any deviation from the intended operation of the appliance shall be cause for rejection of the pack.

4.4 Tests.

4.4.1 Weight-test group 1. The following tests cover procedures for preshipment testing of packed appliances or products weighing 100 pounds and over. A test cycle in the order herein specified shall consist of all the tests required for a packed item.

4.4.1.1 Vibration test. The vibration test shall be performed on the packed appliance in accordance with method 5019 of FED-STD-101. Packs shall be tested on the skid base. Packs without a skid base shall be tested in the normal shipping position. The platform vibration to be applied for the level of pack specified in the contract or purchase order shall be as follows:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:50Z
Check the source to verify that this is the current version before use.

a. Level A pack - Frequency of vibration of the platform shall be that at which the maximum platform acceleration is 1 ± 0.1 times the acceleration of gravity, as specified in paragraph 6 of method 5019 as determined by instrumentation or by actual measurement of table amplitude and frequency.

b. Levels B and C pack - Platform vibration shall be in accordance with either method specified in paragraph 6 of method 5019. The test shall be conducted for the specified level of pack for the number of hours listed as follows:

Level A pack - 2 hours
Level B pack - 1-1/2 hours
Level C pack - 1 hour

4.4.1.2 Incline - impact test. The packed appliance shall be tested in accordance with method 5023 of FED-STD-101. The bumper of the test apparatus shall be of sufficient size to provide full contact with the surfaces of the test container. Extraneous material shall not be used between the impact surface of the bumper and the test container. The impact velocities at time of impact required for the specified levels of pack shall be as follows:

Level A pack - 7 feet per second
Level B pack - 7 feet per second
Level C pack - 6 feet per second

4.4.1.2.1 Calibration. The incline-impact test apparatus shall be calibrated so that the velocities required in 4.4.1.2 are established in terms of the height of release or the length of travel of the dolly on the impact tester. The calibration shall be made on the empty dolly and may be made by any suitable apparatus such as an electric timing device which indicates velocity in units of 0.01 foot per second. If a timing device is used, the average velocity shall be calculated from the known length of roll and the elapsed time. Velocity at impact shall be taken as twice the average velocity.

4.4.1.2.2 Procedure. The impact test shall be made on all six faces of the test container for all packed products not having a skid base. For packed products having a skid base, which requires that the product will be shipped in an upright position on the skid base, impact will be made on five faces of the container; the four sides, and the bottom of the container. For packed products where the item is securely fastened to the base of the container and the container is clearly marked on all four sides to indicate shipping and handling position, impact shall be made on five faces of the container; the four sides, and the bottom of the container. This shall constitute one complete standard cycle of impact tests. Standard impact tests shall be applied as follows:

Level A - 2 cycles of impacts
Level B - 1 cycle of impacts
Level C - 1 cycle of impacts

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:50Z
Check the source to verify that this is the current version before use.

4.4.1.3 Compression (superimposed-load) tests. The packed appliance shall be tested in accordance with method 5016 of FED-STD-101. The value of S shall be level A - 2, B - 1-1/2, or C - 1.

4.4.2 Weight-test group 1A. The following test covers procedures for preshipment testing of packed products weighing less than 100 pounds. A test cycle in the order herein specified shall consist of all the tests required for a packed item.

4.4.2.1 Vibration test. The vibration test shall be performed in accordance with 4.4.1.1.

4.4.2.2 Drop test (free fall). The packed appliance shall be tested in accordance with method 5007 of FED-STD-101. The free fall drop height shall be as specified in method 5007 for level A and level B. For level C the free fall drop height shall be 60% of the height specified for level A.

4.4.2.2.1 Procedure. The packed product shall be dropped in the following sequence which constitutes a drop test cycle:

a. A corner drop on any top corner.
b. An edge drop on the shortest edge radiating from that corner.
c. An edge drop on the next shortest edge radiating from that corner.
d. An edge drop on the longest edge radiating from that corner.
e. A flatwise drop on one of the smallest faces.
f. A flatwise drop on the opposite smallest face.
g. A flatwise drop on one of the medium faces.
h. A flatwise drop on one of the opposite medium faces.
i. A flatwise drop on one of the largest faces.
j. A flatwise drop on the opposite large face.

4.4.2.3 Compression tests. The compression test shall be in accordance with 4.4.1.3.

5. PREPARATION FOR DELIVERY

This section is not applicable to this specification.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. This specification reflects preshipment performance type testing standards and is intended for application to assembly line mass-produced porcelain enamel products, household appliances, and other appliances, including the accessories and components consisting of but not limited to the following:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:50Z
Check the source to verify that this is the current version before use.

Air Conditioning units	Radios
Bathroom cabinets	Ranges
Bathtubs	Refrigerators and freezers
Clothes dryers	Roasters, cookers, ovens,
Computers	including mircrowaves, hot
Fans, electric	plates, toasters, etc.
Hollow-ware	Room heaters
Irons and ironers	Sinks and washtubs
Kitchen cabinets	Table tops
Lavatories	Television sets
Lighting fixtures (metal)	Washing Machines (incl. dish)
Mixers, beaters, etc.	Water coolers
Washing machines (incl. dish)	Water heaters

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this specification.
b. Both the level of preservation and the level of packing required (see 3.3 and 3.4).
c. Preservation required if not provided for in commodity specification (see 3.3.1).
d. When packing materials other than those normally used for level C are required (see 3.4.3).
e. Whether weather-resistant fiberboard is required for level B shipments (see 3.4.3).
f. When panels should have water repellent treatment for level B (see 3.4.3).
g. Whether marking shall be for civil agencies or military requirements (see 3.5).

6.3 Environmental information. Environmental pollution prevention measures are contained in the material specifications referenced herein. Refer to material specification or preparing activity for recommended disposability methods. Environmental conditions that could be encountered during distribution and storage are described below:

Climate conditions	Conditioning prior to test	Required time
1. Refrigerated packages	Temp. 5°C ± 2°C R. Humidity 85% ± 5%	72 hours min.
2. Temperated climates (typical Europe)	Temp. 20°C ± 2°C R. Humidity 85% ± 5%	72 hours min.
3. Tropical (wet) climate (transport less than 120 miles after received at dock)	Temp. 38°C ± 2°C R. Humidity 85% ± 5%	72 hours min.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:50Z
Check the source to verify that this is the current version before use.

4. Tropical (dry) climate (transport greater than 120 miles after received at dock)	Temp. 38°C ± 2°C	72 hours min.
	R. Humidity 85% ± 5%, Plus	
	Temp 60°C ± 2°C	72 hours min.
	R. Humidity 30% ± 5%	6 hours min.

6.4 Subject term (key word) listing.

Air conditioning units
Bathroom cabinets
Bath tubs
Cloth dryers
Marking
Preservation
Radios
Testing
Televisions
Washing machines

6.5 Changes from previous issue. Asterisks (or vertical lines) are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

MILITARY INTERESTS:

Custodians:

Army - GL
Navy - SA
Air Force - 99

Review Activities:

Army - SM, EL
Navy - YD, SA
Air Force - 69
DLA - GS

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - FSS

PREPARING ACTIVITY:

Army - GL

Project No. PACK-0979

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:50Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	PPP-P-600G	1992 December 31

3. DOCUMENT TITLE: PORCELAIN ENAMEL PRODUCTS AND HOUSEHOLD APPLIANCES, ELECTRICAL AND MECHANICAL - REQUIREMENTS FOR PACKAGING OF

4. NATURE OF CHANGE (*Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.*)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code) (1) Commercial	(2) AUTOVON/DSN
U.S. Army Natick RD&E Center	508-651-4501	256-4501
c. ADDRESS (Include Zip Code) Commander, U.S. Army Natick RD&E Center ATTN: SATNC-WTP Natick, MA 01760-5018	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

DD Form 1426, OCT 89 NATICK OP4, JUL 91 *Previous editions are obsolete*

198-29

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:50Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:50Z
Check the source to verify that this is the current version before use.