FEDERAL SPECIFICATION

CLEANING COMPOUND, LINOLEUM-TOPPED FURNITURE

This specification was approved by the Commissioner, Federal Supply Service, General Service Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers one type and grade of a ready-to-use solvent cleaner for removing deeply imbedded stains in linoleum-topped desks (see 6.1).

2. APPLICABLE DOCUMENTS

2.1 Specifications and standards. The following specifications and standards, of the issues in effect on date of invitation for bids or request for proposal, form a part of the specification to the extent specified herein:

Federal Specifications:

TT–A–511—Amyl Acetate (For Use in Organic Coatings).
TT–B–838—Butyl Acetate; Normal (For Use in Organic Coatings).
TT–B–846—Butyl Alcohol; Normal (Butanol) (For Use in Organic Coatings).
PPP–C–96—Cans, Metal, 28 Gage and Lighter.

Federal Standards:

Fed. Std. No. 123—Marking for Domestic Shipment (Civilian Agencies).
Fed. Test Method Std. No. 141—Paint, Varnish, Lacquer, and Related Materials; Methods of Inspection, Sampling, and Testing.

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C., 20402.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D.C., Atlanta, Chicago, Kansas City, Mo., Dallas, Denver, San Francisco, Los Angeles, and Seattle, Wash.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Standards:

MIL–STD–105—Sampling Procedures and Tables for Inspection by Attributes.
MIL–STD–129—Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated the issue in effect on date of invitation for bids or request for proposal shall apply.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:18Z
Check the source to verify that this is the current version before use.

DEPARTMENT OF HEALTH EDUCATION AND WELFARE

Federal Hazardous Substances Act

(Application for copies should be addressed to the U.S. Department of Health, Education and Welfare, Food and Drug Administration, Washington, D. C. 20203.)

3. REQUIREMENTS

3.1 Materials. The cleaning compound shall be a mixture of normal butyl acetate, amyl acetate, normal butyl alcohol, ethylene glycol, and diethylene glycol.

3.1.1 Normal butyl acetate. The normal butyl acetate shall be of technical grade and shall conform to the requirements of TT-B-838

3.1.2 Amyl acetate. The amyl acetate shall be of technical grade and shall conform to the requirements of type I or II of TT-A-511.

3.1.3 Normal butyl alcohol. The normal butyl alcohol shall be of technical grade and shall conform to the requirements of TT-B-846.

3.1.4 Ethylene glycol. The ethylene glycol shall be of technical grade, a minimum of 99 percent ethylene glycol, a specific gravity at 20°/20°C. 1.115 to 1.116, a boiling range, at 760 mm 193–210°C., and a color (platinum-cobalt scale) not greater than 15.

3.1.5 Diethylene glycol. The diethylene glycol shall be of technical grade, a minimum of 99 percent diethylene glycol, a specific gravity at 20°/20°C. 1.117 to 1.120, a boiling range, at 760 mm 235–255°C., and a color (platinum-cobalt scale) not greater than 25.

3.2 Composition. The cleaning compound shall conform to the requirements of table I when tested as specified in 4.3.2.

TABLE I. Composition

Component	Percent by volume
Normal butyl acetate	40.0 ± 1.0
Amyl acetate	25.0 ± 1.0
Normal butyl alcohol	15.0 ± 1.0
Ethylene glycol	15.0 ± 1.0
Diethylene glycol	5.0 ± 0.5

3.3 Flash point. The flash point of the cleaning compound shall be not less than 100°F. when tested as specified in 4.3.2 and 4.4.1.

3.4 Labeling. Each unit container shall be durably and legibly marked in accordance with the Federal Hazardous Substances Act and shall be marked with the following information:

Instructions for Use:

This cleaning compound should be used only on the linoleum desk tops for the removal of ink, carbon paper stains, and other deeply imbedded stains not removed with a detergent solution. Do not allow this cleaning compound to come in contact with enamel or painted surfaces. Use only in a well ventilated area.

1. Saturate a clean, dry, soft cloth with the cleaning compound.
2. Thoroughly wet the entire surface to be cleaned with the cleaning compound using a circular motion.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:18Z
Check the source to verify that this is the current version before use.

3. Remove the soil while wet using a dry, soft cloth. Do not allow dirty solution to dry on desk surface.
4. Apply the compound two or three times on severely stained or previously waxed surface to obtain a uniform clean surface.

Precautionary label:

WARNING: HARMFUL OR FATAL IF SWALLOWED

Contains Ethylene Glycol and Diethylene Glycol

FLAMMABLE

Do not drink: If swallowed give one or two glasses of milk or water and induce vomiting. Call a medical doctor immediately. Avoid prolonged breathing of vapors or repeated contact with the skin or contact with the eyes.

Keep away from heat and open flame.

Do not store in open or unlabeled containers.

Do not throw in fire or incinerator.

Keep out of reach of children.

3.5 Workmanship. The cleaning compound shall be a clear, water-white, single phase liquid, free from suspended and sedimentary matter when tested as specified in 4.3.2 and 4.4.2.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.1.1 Certificate of compliance. Where certificates of compliance are submitted, the Government reserves the right to check test such items to determine the validity of the certification. The submitting of a certificate of compliance (see 4.3.2) does not relieve the supplier of his obligation in meeting the requirements of all cleaning compound delivered under this specification.

4.2 Inspection. Sampling for inspection shall be performed in accordance with MIL-STD-105, except where otherwise indicated. For purposes of sampling, an inspection lot for examinations and tests shall consist of all the cleaning compound prepared in a single batch.

4.2.1 Component and material inspection. In accordance with 4.1 above, components and materials shall be inspected and tested in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified or qualified in this specification or applicable purchase documents. The supplier shall submit to the contracting officer or his authorized representative a certificate of compliance covering the material requirements contained in 3.1.1 through 3.1.5, inclusive, for every lot of component materials. The certificate shall be accompanied by actual test, inspection or other verifiable quality data.

4.3 Inspection of the end item.

4.3.1 Examination of the end item. The end item shall be examined for the defects in the applicable subparagraphs at the inspection levels and acceptable quality levels (AQLs) set forth in 4.3.1.4. The lot size shall be expressed in unit containers of the specified capacity for the examinations in 4.3.1.1 and 4.3.1.2 and in units of shipping containers for the examinations in 4.3.1.3.

4.3.1.1 Examination of the unit container. The sample unit for this examination shall be one filled unit container.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:18Z
Check the source to verify that this is the current version before use.

Examine	Defect
Construction	Not as specified. Cans dented; evidence of leakage. Not equipped with formed bridge type handle, as applicable. Handle not securely affixed, as applicable.
Closure	Not as specified.
Markings (use and hazard printing)	Missing, incomplete, incorrect, illegible. Does not contain labeling information specified in 3.4.

4.3.1.2 Examination for average net contents. The sample unit for this examination shall be one filled unit container. The lot shall be unacceptable if the average net content per container for all sample units examined is less than specified.

4.3.1.3 Examination of preparation for delivery. An examination shall be made to determine that packaging, packing, and marking comply with the requirements of Section 5 of this specification. The sample unit for this examination shall be one shipping container fully packed, selected just prior to the closing operation. Shipping containers fully prepared for delivery shall be examined for closure defects. This examination does not apply when the unit container is the shipping container.

Examine	Defect
Packaging	Not level specified. Materials and construction not as specified. Evidence of leakage.
Packing	Not level specified. Materials and construction not as specified. Any nonconforming component; component missing, damaged, or otherwise not serviceable. Any bulged, distorted, or broken container.
Markings (interior or exterior, as applicable)	Omitted, illegible, incorrect, incomplete; not in accordance with contract requirements.

4.3.1.4 Inspection levels and acceptable quality levels (AQLs) for examinations. The inspection levels, for determining the sample size, and the acceptable quality levels (AQLs), expressed as defects per 100 units, shall be as follows:

Examination paragraph	Inspection level	AQL
4.3.1.1	S-4	2.5
4.3.1.2	S-2	N/A
4.3.1.3	S-1	2.5

4.3.2 Testing of the cleaning compound. The supplier shall submit to the contracting officer, or his authorized representative, production data certifying the compliance of each prepared batch with composition requirements. In addition the cleaning compound shall be tested for the characteristics specified in 3.3 and 3.5 for each lot. The lot size shall be expressed in gallons of cleaning compound. The sample unit shall be one quart. The sample size shall be as specified below. Test reports shall contain individual values utilized in expressing the final result. The lot shall be unacceptable if one or more sample units fail to meet the test requirement specified.

Lot size (gallons)	Sample size
800 or less	2
801 up to and including 22,000	3
22,001 and over	5

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:18Z
Check the source to verify that this is the current version before use.

4.4 Test procedures.

4.4.1 Flash point. The flash point of the cleaning compound shall be determined in accordance with method 4294 (Cleveland Open Cup) of Fed. Test Method Std. No. 141. Two determinations shall be made on each sample unit and the values averaged for the final result.

4.4.2 Workmanship. Vigorously shake a unit container of the cleaning compound. After shaking, pour 100 milliliters (ml) of the cleaning compound into a 100 ml. graduate cylinder. Visually examine the cleaning compound for color, clarity, homogeneity (single phase) and the presence of suspended and sedimentary matter. Allow to stand for one hour and re-examine. One determination shall be made per sample unit and the result reported as pass or fail.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A, B, or C as specified (see 6.2).

5.1.1 Level A. One quart or one gallon of cleaning compound as specified (see 6.2), shall be filled into appropriate sized oblong metal cans conforming to type V, class 4, exterior coating plan A of PPP-C-96. The one-gallon can shall be provided with a formed bridge type handle securely affixed to the top.

5.1.2 Level B. One quart or one gallon of cleaning compound, as specified (see 6.2), shall be filled into appropriate sized oblong metal cans conforming to type V, class 4 of PPP-C-96. Exterior coating is optional and may be commercial. The one-gallon can shall be provided with a formed bridge type handle securely affixed to the top.

5.1.3 Level C. The cleaning compound shall be packaged to afford adequate protection against damage during shipment from the supply source to the first receiving activity. The supplier may use his standard practice when it meets this requirement.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A. Cleaning compound, packaged as specified in 5.1, shall be packed in accordance with the level A packing requirements in the appendix of PPP-C-96.

5.2.2 Level B. Cleaning compound, packaged as specified in 5.1, shall be packed in accordance with the level B packing requirements in the appendix of PPP-C-96.

5.2.3 Level C. Cleaning compound, packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers shall be in accordance with rules or regulations of carriers applicable to the mode of transportation.

5.3 Marking.

5.3.1 Civil agencies. In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with Fed. Std. No. 123.

5.3.2 Military requirements. In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTE

6.1 Intended use. The cleaning compound covered by this specification is a special purpose cleaner for use on linoleum desk tops only. The cleaning compound should be used only when other cleaning methods do not remove ink and other stains. The cleaning compound is intended to be used by trained custodial cleaning personnel after normal working hours.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

a. Title, number, and date of this specification.

b. Selection of the applicable levels of packaging and packing (see 5.1 and 5.2).

c. Quantity of cleaning compound desired (see 5.1.1 and 5.1.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:18Z
Check the source to verify that this is the current version before use.

MILITARY INTEREST:

Custodians:

Army—GL
Air Force—84

Review activities:

Army—GL, MD
Air Force—84, 85

User activities:

Army—SM
Navy—YD

Preparing activity:

Army—GL

Civil agency interest:

AGR
COM
GSA—FSS
VA

Review and user information is current as of the date of this document. For future coordination of changes to this document, draft circulation should be based on the information in the current DODISS.

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein. Price 5 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:18Z
Check the source to verify that this is the current version before use.

"to detach this form, cut along this line"

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity.

SPECIFICATION

Cleaning Compound, Linoleum-Topped Furniture - P-C-1239

ORGANIZATION	CITY AND STATE

CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*	DATE

DD FORM 1 OCT 64 1426

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:18Z
Check the source to verify that this is the current version before use.