P-C-1632B
February 25, 1977
SUPERSEDING
Fed. Spec. P-C-1632A
July 29, 1974

FEDERAL SPECIFICATION

CLEANING COMPOUND, RUG AND UPHOLSTERY

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers three types of cleaning compounds for use in "location" cleaning of rugs and upholstery (see 6.1).

1.2 Classification. The cleaning compounds shall be of the following types, as specified (see 6.2).

Type I - Granular cleaner
Type II - Liquid cleaner, sanitizing
Type III - Aerosol cleaner

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specification:

PPP-B-636 - Boxes, Shipping, Fiberboard.

Federal Standard:

Fed. Std. No. 123 - Marking for Shipment (Civil Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Specification:

MIL-B-26701 - Bottles, Screw cap, and Carboys, Polyethylene Plastic.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:19Z
Check the source to verify that this is the current version before use.

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Laws and Regulations:

16 CFR 1500 - Federal Hazardous Substances Act.
40 CFR 162 - Regulations for the Enforcement of the Federal Insecticide, Fungicide, and Rodenticide Act.

(The Code of Federal Regulations (CFR) and the Federal Register (FR) are for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402. When indicated, reprints of certain regulations may be obtained from the Federal agency responsible for issuance thereof.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

National Motor Freight Traffic Association, Inc., Agent:

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Associations, Inc., Traffic Department, 1616 P Street, N.W., Washington, DC 20036.)

Uniform Classification Committee, Agent:

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

American Society for Testing and Materials (ASTM) Standards:

D 460 - Sampling and Chemical Analysis of Soaps and Soap Products.
D 502 - Particle Size of Soaps and Other Detergents.
D 820 - Chemical Analysis of Soaps Containing Synthetic Detergents.
D 1078 - Distillation Range of Volatile Organic Liquids, Test For.
D 1331 - Surface and Interfacial Tension of Solution of Surface-Active Agents.
E 70 - pH of Aqueous Solutions with the Glass Electrode.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

3. REQUIREMENTS

3.1 Material.

3.1.1 Type I. The type I rug and upholstery cleaner shall be a fast drying product composed of granular cellulosic material or a uniform mixture of granular cellulosic material mixed with diatomaceous earth, dry cleaning solvents, and detergents. Carbon tetrachloride shall not be used in the formulation.

3.1.2 Type II. The type II rug and upholstery cleaner shall be a fast drying, translucent, uniform, free flowing concentrated liquid product. The concentrated product is intended for dilution (see 6.2) to its application strength and application with a mechanical cleaning apparatus or manually with brushes. The cleaner shall be a solvent and detergent based cleaner which may contain additives to enhance its cleaning performance or convenience. The product shall contain sufficient germicide to make the product a sanitizer and shall be registered with the E.P.A. as a sanitizer (see 3.8). When specified (see 6.2), the cleaner shall be furnished with a plastic hand brush adapter that can be used to apply the cleaner after dilution.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:19Z
Check the source to verify that this is the current version before use.

3.1.3 Type III. The type III rug and upholstery cleaner shall be packaged in an aerosol container. The product is to be similar to type II, except that it shall be supplied in a concentration suitable for direct application from its container, as a foam, to the surface being cleaned. When specified (see 6.2), the unit shall contain a combination foam pad and brush applicator capable of being attached to the container for direct application and scrubbing of the surface to be cleaned.

3.2 Basic requirements. The cleaners shall conform to the requirements indicated in table I when tested as specified in table II.

TABLE I. Basic requirements

Characteristic	Type I		Type II		Type III	
	Min.	Max.	Min.	Max.	Min.	Max.
Nonvolatile matter, percent 1/	55	75	12	----	5	----
pH	----	--	7.0	9.5	7.0	9.0
Surface tension, dynes per cm	----	--	24	37	24	37
Alcohol soluble organic matter, percent	----	--	6.0	11	4.3	5.5
Particle size, mesh, of cellulosic material 2/	60	40	----	----	----	----
Free alkali	----	--	----	0	----	0
Distillation range (°C) 2/	90	190	----	----	----	----

1/ The nonvolatile matter shall be a powder, cake, or film that is non-tacky to the touch at 70° - 80°F (20° - 27°C).
2/ 90 percent of the product shall pass these requirements.

3.3 Stability in hard water, type II. A solution of the cleaner made, according to its recommended use dilution, with 20 grain hard water shall be as clear as the undiluted cleaner immediately after preparation and after standing for 4 hours when tested as specified in 4.4.1.9.

3.4 Foam stability.

3.4.1 Type II. A solution of the cleaner made in accordance with its recommended use dilution using 20 grain hard water shall produce a minimum of 200 ml of foam after standing 1 minute, and still have a minimum of 150 ml of foam after standing 15 minutes when tested as specified in 4.4.1.10.

3.4.2 Type III. When tested as specified in 4.4.1.11, some of the foam shall remain after a period of 45 minutes and 75 percent of the test paper shall be wetted by 45 minutes.

3.5 Color and odor.

3.5.1 Type I. The type I cleaner shall be of the natural color of the cellulosic material used in the formulation. The cleaner shall not impart a rancid odor or any color (except for cellulosic material that may adhere) to a test fabric when tested as specified in 4.4.1.12.

3.5.2 Type II. The type II cleaner shall be translucent and may be lightly tinted. The cleaner shall not impart a rancid odor or any color to the test fabric when tested as specified in 4.4.1.12.

3.5.3 Type III. The type III cleaner shall be a white dense foam. The cleaner shall not impart a rancid odor or any color to the test fabric when tested as specified in 4.4.1.12.

3.6 Heat stability. The product shall show no sign of precipitation or separation when subjected to a temperature of 125°F (51°C) for 7 days (168 hours).

3.7 Cold stability. The product shall not permanently separate or precipitate when subjected to a temperature of 0°F (-17°C) for 48 hours.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:19Z
Check the source to verify that this is the current version before use.

3.8 Registration. The type II product shall be registered with the Environmental Protection Agency as a sanitizer in accordance with 40 CFR 162, Regulations for the Enforcement of the Federal Insecticide, Fungicide, and Rodenticide Act, and shall have the E.P.A. registration number on the package label.

3.9 Labeling. The product labels shall be required to include the following information:

The recommended use dilution for type II.
Instructions for moistening the cellulosic material in type I by inverting the container.
Instructions for application, including recommendations for the amount of carpet to be treated in one step; all types.
Instructions for working in the cleaner; all types.
Instructions for the removal of the cleaner and soil; all types.
The cleaner should be tried out on an inconspicuous area to test for deleterious effects; all types.
Appropriate caution statements for exposure to harmful ingredients; all types in accordance with the Federal Hazardous Substances Act and Regulations (16 CFR 1500).

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Inspection sampling. Sampling for the inspection procedures set forth in this specification shall be performed in accordance with MIL-STD-105. The lots to be inspected shall consist of no more than one classification (see 1.2).

4.3 Examination.

4.3.1 Examination of preparation for delivery.

4.3.1.1 Sampling plan. The sample unit shall be defined as one shipping container fully marked and prepared for delivery. The samples shall be selected in accordance with inspection level S-2 and the AQL shall be 4.0 percent defective.

4.3.1.2 Examination procedure. An examination shall be made to determine the compliance of the packing and marking with the requirements of section 5. The sample units shall be examined for the defects described below and scored accordingly.

Examination of Preparation for Delivery

Examine	Defects
Packing	Not as specified; odd shape or size.
Content	Not as specified; incorrect number of packages within.
Marking	Omitted; incorrect; illegible; improper size, location, sequence, or method of application.
Material	Component missing or damaged.
Workmanship	Bulging or distortion of containers.

4.3.2 Examination of the package and contents.

4.3.2.1 Sampling plan. The sample unit shall be defined as one package including its label. The samples shall be selected in accordance with inspection level S-2 and the AQL shall be 4.0 percent defective.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:19Z
Check the source to verify that this is the current version before use.

4.3.2.2 Examination procedure. The examination shall be made to determine the compliance of the packaging and marking with the requirements of sections 3 and 5 and the contents with the requirements of paragraph 3.1. The sample units shall be examined for the defects described below and scored accordingly.

Examination of the Package and Contents

Examine	Defects
Container	Not as specified.
Marking	Omitted; incorrect; illegible; improper size, location, sequence, or method of application (See 3.8, 3.9, and 5.3).
Material	Component missing or damaged.
Workmanship	Bulging or distortion of containers.
Contents	Type I product: solvent layer above solids layer; cellulosic material not uniform in appearance.
	Type II product: not uniform; separated into layers; visual presence of foreign material; not translucent.

4.4 Testing.

4.4.1 Cleaner testing.

4.4.1.1 Sampling plan. The sample unit shall be defined as one filled container. A 2-pound composite shall be made by mixing equal portions of each of the sample units taken from the lot in accordance with inspection level S-1. For type III, the average of the determinations of three sample units shall be used to determine compliance. The lot shall be unacceptable if the composite sample fails to pass any of the applicable tests described in 4.4.1.

4.4.1.2 Testing procedure. The composite sample shall be tested in accordance with the instructions in table II.

TABLE II. Instructions for testing the rug cleaner

Characteristic	Applicable to type	Spec. Reference		Results reported as	
		Requirement	Test Method	Pass or Fail	Numerically to nearest
Nonvolatile matter, percent	All	Table I	4.4.1.3		0.1 percent
Tackiness	II, III	Table I	4.4.1.3	X	
pH	II, III	Table I	4.4.1.4		0.1
Surface tension, dynes per cm	II, III	Table I	4.4.1.5		0.1
Alcohol soluble organic matter, percent	II, III	Table I	4.4.1.6		0.1 percent
Particle size, cellulosic material	I	Table I	4.4.1.7		1 percent
Free alkali	II, III	Table I	4.4.1.8		1 percent
Stability in hard water	II	3.3	4.4.1.9	X	
Foam stability	II	3.4.1	4.4.1.10	X	
	III	3.4.2	4.4.1.11	X	
Color and odor	I	3.5.1	4.4.1.12	X	
	II	3.5.2	4.4.1.12	X	
	III	3.5.3	4.4.1.12	X	
Heat stability	II	3.6	4.4.1.13	X	
Cold Stability	II	3.7	4.4.1.14	X	
Distillation range	I	Table I	4.4.1.15		degree C

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:19Z
Check the source to verify that this is the current version before use.

4.4.1.3 Nonvolatile matter. Determine the percentage of nonvolatile matter in accordance with ASTM D 820, Moisture and Other Matter **Volatile at 105°C (oven** method). After weighing, the nonvolatile matter shall be cooled in a desiccator and examined by touch for evidence of tackiness.

4.4.1.4 pH. The pH determination of type II shall be made on the undiluted cleaner. For the pH determination of type III, spray the cleaner into a clean, dry wide mouth container and let stand until sufficient liquified cleaner can be obtained for a pH measurement of the undiluted type III cleaner. pH measurements shall be done in accordance with ASTM E 70.

4.4.1.5 Surface tension. For type II, make a distilled water solution of the cleaner in accordance with the use dilution ratio recommended on the product label. For type III, obtain the product as specified in 4.4.1.4, and measure the surface tension without diluting the cleaner. Measurements of surface tension shall be done in accordance with ASTM D 1331.

4.4.1.6 Alcohol soluble organic matter. Weigh to the nearest milligram a 10 g sample of undiluted cleaner. Evaporate to dryness on a steam bath. Proceed as specified for determination of Alcohol Soluble Matter, and for the determination **of Alcohol** Soluble Matter, and for the determination of Chlorides in Alcohol Soluble Matter as specified in ASTM D 820. The percent alcohol soluble organic matter shall be calculated using the following formula:

$$\text{Percent} = \frac{[(\text{Wt. of alcohol soluble matter}) - (\text{Wt. of chlorides})]}{\text{Wt. of liquid cleaner sample}} \times 100$$

4.4.1.7 Particle size. Dry about 400 gm of type I in a porcelain or glass dish, to constant weight in an oven at a temperature of 105 ± 2°C. Determine the particle size of the dried product in accordance with ASTM D 502 using a No. 40 and a No. 60 sieve.

4.4.1.8 Free alkali. The determination of free alkali shall be made on the undiluted type II cleaner, or type III cleaner obtained as specified in 4.4.1.4. The method of free alkali determination shall be as specified in ASTM D 820.

4.4.1.9 Stability in hard water. Make a 20-grain hard water solution of the product in accordance with the use dilution ratio recommended on the product label. The 20-grain hard water shall be prepared by dissolving 0.040 g of calcium chloride dihydrate and 0.136 g of magnesium chloride hexahydrate in 1 liter of distilled water. The hard water solution of the product shall be placed in a stoppered flask, mixed thoroughly by stirring and allowed to stand for 4 hours.

4.4.1.10 Foam stability, type II. Make a 20-grain hard water solution of the product in accordance with the use dilution ratio recommended on the product label. The hard water shall be made in accordance with 4.4.1.9. Place 50 ml of the solution in a 250 ml glass stoppered graduated cylinder. Stopper the cylinder and shake by inversion, rotating the cylinder about its midpoint without translational motion for 1 minute at such a rate that 30 inversions are completed. Place the cylinder in an upright position on a table, remove the stopper, wait 1 minute, and read the net volume of foam (total volume minus the volume of liquid). Measure the foam height again after 30 minutes.

4.4.1.11 Foam stability, type III. The aerosol container shall be held as specified on the product label and sprayed for about 2 seconds to obtain an even spray. Then spray the product onto the center of a 6 ± 1/4 inch circular piece of Whatman No. 1 filter paper. Allow the foam to remain on the filter paper for 45 minutes. After 45 minutes, examine for presence of foam and for the amount of paper wetted by the product.

4.4.1.12 Color and odor. For type I, filter the product with suction to obtain about 20 ml of the liquid part of the product. For type II, dilute the product with distilled water in accordance with the use dilution ratio recommended on the product label. For type III, spray some of the product into a clean, dry wide mouth container and let stand until sufficient liquid can be obtained for the test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:19Z
Check the source to verify that this is the current version before use.

Swatches of unbleached, uncolored wool fabric shall be saturated in the product prepared as stated above. The excess cleaner solution shall be squeezed from the fabric by hand and the swatches shall be dried at room temperature. Examine the swatches for evidence of offensive odor or discoloration.

4.4.1.13 Heat stability. Place 100 ml of the cleaner in a 100 ml beaker and place in a forced air oven at a temperature of 125°F (21°C) for 7 days (168 hours). Allow to cool to room temperature and examine for evidence of separation or precipitation.

4.4.1.14 Cold stability. Place 100 ml of the cleaner in a 100 ml beaker and place in a freezer at 0°F (-17°C) for 48 hours. Remove the beaker and allow to warm to room temperature. Pour the sample into a 100 ml graduate invert ten times and examine for separation or precipitation after an additional 20 minutes.

4.4.1.15 Distillation range. Filter the type I product through a funnel plugged with a cotton. The distillation range of the filtered liquid shall be measured in accordance with ASTM D 1078.

4.4.2 Aerosol testing.

4.4.2.1 Sampling plan. The sample unit shall be defined as one filled aerosol package. The sample shall be selected in accordance with inspection level S-2, except that twice as many containers shall be selected, and the AQL shall be 4.0 percent defective.

4.4.2.2 Testing procedure. The tests described below shall be made to determine compliance with paragraphs 5.1.1.3.1, 5.1.1.3.2, and 5.1.1.3.3.

4.4.2.3 Valve performance. Remove paper label, protective cover, and all other detachable materials except for the actuator. Activate the valve for a few seconds and weigh the container to the nearest 0.05 g. Place the container in a water bath equipped with a stirrer and maintained at 80° ± 1°F (27° ± 0.5°C). The container shall be kept completely submerged for 30 minutes. Remove the dispenser. Activate the valve for 10.0 seconds. Dry the dispenser with a towel and use a blast of compressed air to remove moisture from areas inaccessable to the towel. Reweigh the dispenser and compute the weight loss. The delivery rate shall be calculated as the weight loss in grams, ± 0.1 gram, divided by the test spray time (10.0 seconds) to 0.1 second accuracy. The delivery rate shall be reported as the weight, ± 0.1 g, delivered per second. For valve leakage, a one ounce vial calibrated in millititers and completely filled with water shall be placed over the valve of an unused aerosol container for 48 hours. During this time, the aerosol container and vial shall be placed in water to just above the lower edge of the vial. The water level in the vial shall be recorded at the beginning and end of the test. Any lowering of the water level during the test shall constitute failure.

4.4.2.4 Net weight. Weigh filled container to the nearest gram. Shake the container with a wrist twisting motion for 15 seconds at the approximate rate of one complete cycle per second. Holding the container in the position recommended on the product label, exhaust the container by holding the valve wide open. Rinse the exterior of the container and dry, using a towel and compressed air for drying inaccessable areas including the interior of the actuator. Weigh the exhausted container to the nearest gram. The measured net weight in ounces shall be calculated using the following formula:

$$N.W. = (G - E - 10)/(28.375)$$

where: G = gross weight of filled container (grams).
E = weight of exhausted container (grams).

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A, B, or C, as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Type I. Type I cleaning compound shall be packaged in a 1/2-gallon or 1-gallon capacity container, as specified (see 6.2). The container shall be of a commercial type commonly used by industry for packaging the product. The container shall neither affect nor be affected by the packaged product.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:19Z
Check the source to verify that this is the current version before use.

5.1.1.2 Type II. Type II cleaning compound shall be packaged in a 1-quart, 1/2-gallon or 1-gallon capacity polyethylene bottle, as specified (see 6.2). Each polyethylene bottle shall be fabricated and closed in accordance with the applicable requirements of MIL-B-26701.

5.1.1.3 Type III. Type III cleaning compound shall be packaged in a 24-ounce capacity pressurized can commonly used by industry for packaging the product. The cans shall neither affect nor be affected by the packaged product.

5.1.1.3.1 Valve performance (type III). The filled aerosol container shall meet the following performance requirements when tested as specified in 4.4.2.3.

Delivery rate of 80°F; 3.8 gm Min, 5.5 gm Max.
Leakage in 48 hours; 0 ml Max.

5.1.1.3.2 Net weight (type III). The measured net weight, determined as specified in 4.4.2.4 shall not be less than the net weight stated on the container label.

5.1.2 Level B. Cleaning compound shall be packaged in accordance with the applicable requirements specified in 5.1.1.

5.1.3 Level C. Cleaning compound shall be packaged to afford adequate protection against deterioration and physical damage during shipment from the supply source to the first receiving agency. The package and the quantity per package shall be the same as that normally used by the supplier for retail distribution.

5.2 Packing. Packing shall be level A, B, or C, as specified (see 6.2).

5.2.1 Level A.

5.2.1.1 Type I. Six 1/2-gallon or four 1-gallon capacity containers of type I cleaning compound, packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC-L, grade V2s of PPP-B-636. The inside of each shipping container shall be fitted with a box liner conforming to type CF, class weather-resistant, variety DW, grade V15c of PPP-B-636. Each fiberboard container shall be provided with top and bottom fiberboard pads made of the same material as the box liner and cut 1/4-inch less than the inside length and width of the box liner. Each shipping container packed with glass packages shall be provided with a full height (less the thickness of the top and bottom pads) half-slotted style interlocking partition made of the same material as the box liner. Each shipping container shall be closed in accordance with method III, waterproofed in accordance with method V, and reinforced as specified in the appendix of PPP-B-636.

5.2.1.2 Type II. Twenty-four 1-quart, six 1/2-gallon or four 1-gallon capacity bottles of type II cleaning compound, packaged as specified in 5.1, shall be packed as specified in 5.2.1.1.

5.2.1.3 Type III. Twelve 24-ounce capacity pressurized cans of type III cleaning compound, packaged as specified in 5.1, shall be packed as specified in 5.2.1.1.

5.2.2 Level B.

5.2.2.1 Type I. Six 1/2-gallon or four 1-gallon capacity containers of type I cleaning compound, packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC-L, type CF (variety SW) or SF, class domestic, grade 200 minimum of PPP-B-636. The inside of each shipping container shall be fitted with a box liner conforming to type CF, class domestic, variety DW, grade 200 of PPP-B-636. Each fiberboard container shall be provided with top and bottom fiberboard pads made of the same material as the box liner

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:19Z
Check the source to verify that this is the current version before use.

and cut 1/4-inch less than the inside length and width of the box liner. Each shipping container packed with glass packages shall be provided with a full-height (less the thickness of the top and bottom pads) half-slotted style interlocking partition made of the same material as the box liner. Each shipping container shall be closed in accordance with method II as specified in PPP-B-636.

5.2.2.2 Type II. Twenty-four, 1-quart, six 1/2-gallon or four 1-gallon capacity bottles of type II cleaning compound, packaged as specified in 5.1, shall be packed as specified in 5.2.2.1.

5.2.2.3 Type III. Twelve 24-ounce capacity pressurized cans of type III cleaning compound, packaged as specified in 5.1, shall be packed as specified in 5.2.2.1.

5.2.2.4 Weather resistant grade fiberboard. When specified (see 6.2), the fiberboard shipping container specified in 5.2.2.1, 5.2.2.2, and 5.2.2.3 shall be a grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method III as specified in the appendix of the container specification.

5.2.3 Level C. Cleaning compound, packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination. The quantity per shipping container shall be the same as that normally used by the supplier for retail distribution. Containers shall comply with US Postal Service Manual, Uniform Freight Classification Rules or National Motor Freight Classification, as applicable.

5.3 Marking.

5.3.1 Civil agencies. In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with FED-STD-123.

5.3.2 Military requirements. In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The cleaners covered by this specification are intended for use in the general purpose maintenance cleaning of rugs and upholstery. The product does not require that the rug be removed from the floor and can be used at room temperature.

6.2 Ordering data. Purchasers should select the preferred options permitted herein, and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) When plastic hand brush adapter is required (see 3.1.2).
(c) When plastic hand brush applicator is required (see 3.1.3).
(d) Size and level of packaging and packing required (see 5.1 and 5.2).
(e) When weather resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.4).

6.3 Use dilution procurement, type II. Purchasing of the type II rug and upholstery cleaner under this specification is intended to be on a use dilution basis. To compare prices on a use dilution basis, the actual cost of a gallon of properly diluted cleaner can be calculated by using the following formula:

$$AC = CC \times F$$

where: AC = Actual cost of a gallon of cleaner.
CC = Concentrate cost per gallon of type II.
F = Fraction of a gallon of type II to be added to a gallon of water.

In the procurement document, the use dilution recommendation, or a copy of the product label can be required to accompany the price quotation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:19Z
Check the source to verify that this is the current version before use.

MILITARY CUSTODIANS:

Army - GL
Air Force - 99

Review activities:

Army - MD
Air Force - 03

User activity:

Navy - SH, MS

CIVIL AGENCY COORDINATING ACTIVITIES:

GSA - FSS
CPSC
EPA
VA - DMS

PREPARING ACTIVITY: GSA - FSS

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein. Price each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:19Z
Check the source to verify that this is the current version before use.