P-D-001397A(GSA-FSS)
June 14, 1969
SUPERSEDING
Int. Fed. Spec. P-D-001397(GSA-FSS)
December 11, 1967

INTERIM FEDERAL SPECIFICATION

DETERGENT-BACTERIOSTAT, GENERAL PURPOSE, SUPERCONCENTRATE

This Interim Federal Specification was developed by the General Services Administration, Federal Supply Service, Standardization Division, Washington, D. C. 20406, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

1. SCOPE

1.1 Scope. This specification covers a liquid superconcentrate detergent bacteriostat, which when diluted to a U. S. gallon with water, will provide a cleaner bacteriostat, concentrate intended for general purpose building maintenance.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids, or request for proposal, form a part of the specification to the extent specified herein.

Federal Specifications:

PPP-B-636 - Box, Fiberboard.
PPP-C-186 - Containers, Packaging and Packing for Drugs, Chemicals, and Pharmaceuticals.
PPP-T-495 - Tubes, Mailing and Filing.

Federal Standard:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civilian Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, D. C. 20402.)

(Single copies of this specification and other Federal specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, D.C., Atlanta, Chicago, Kansas City, Mo., Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, Washington.)

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Specification:

MIL-B-121 - Barrier Material, Greaseproofed, Waterproofed, Flexible.

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:18Z
Check the source to verify that this is the current version before use.

Laws and Regulations:

Federal Insecticide, Fungicide, and Rodenticide Act.

(Copies may be obtained from the Superintendent of Documents, U. S. Government Printing Office, Washington, D. C. 20402.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

Standard Methods of Chemical Analysis Vol. III B.

Sixth Edition, Edited by Frank Welcher and Published by Van Nostrand.

(Application for copies should be addressed to the D. Van Nostrand Company, Inc. 120 Alexander Street, Princeton, New Jersey.)

Official Methods of Analysis of the Association of Official Agricultural Chemists.

(Application for copies should be addressed to the Association of Official Analytical Chemists, P. O. Box [illegible], Benjamin Franklin Station, Washington, D. C. 20044.)

American Society for Testing and Materials (ASTM) Standards:

D 882 - Methods of Test for Tensile Properties of Thin Plastic Sheeting.
D 1505 - Methods of Test for Density of Plastics by the Density-Gradient Technique.
D 1709 - Method of Test for Impact Resistance of Polyethylene Film by the Free Falling Dart Method.
E 96 - Method of Test for Water Vapor Transmission of Materials in Sheet Form.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, Pennsylvania 19103.)

Official and Tentative Methods of the American Oil Chemists Society:

Ba 2-63 - Soap Containing Synthetic Detergents, Alcohol Soluble and Insoluble Matter.
Tl 1a-64T - Amine Value, Fatty Amines, Indicator.

(Application for copies should be addressed to the American Oil Chemists Society, 35 E. Wacker Drive, Chicago, Illinois 60601.)

Uniform Freight Classification Rules.

(Application for copies should be addressed to the Uniform Classification Committee, 202 Union Station, Chicago, Illinois 60606.)

National Motor Freight Classification Rules.

(Application for copies should be addressed to the National Classification Board, 1616 P Street, N.W., Washington, D. C. 20036.)

3. REQUIREMENTS

3.1 Material. The product shall be a concentrated liquid consisting of anionic detergents combined with suitable chelating, and sequestering agents and bacteriostat to provide an effective detergent bacteriostat when diluted to working solution strength. It shall be effective as a cleaner bacteriostat used with all types of water hardness.

3.2 The finished formulation shall meet the requirements of Table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:18Z
Check the source to verify that this is the current version before use.

TABLE I. Composition

	Percent		Numerical value
	Minimum	Maximum	
Active anionic detergent	50.0	55.0	
Ethylene glycol monobutyl ether	9.0	11.0	
Alkali value			160 (min.)
Active tetra sodium ethylenediamine tetra acetate	2.0		
Moisture		6.0	
Amyl, aryl, chloro aryl and chlorobenzyl phenol or ortho benzyl parachloro phenol*	7.5		
Total free inorganic salts		2.0	
Fatty acids		Trace	

*Any of the above phenols or combination thereof which will comply with the other requirements of this specification.

3.3 Registration. The product shall be registered under the provisions of the Federal Insecticide, Fungicide, and Rodenticide Act.

3.3.1 Bacteriostatic activity. The finished compound shall show a clear and measurable zone of inhibition when tested by the seeded agar cup plate test as specified in 4.4.11.

3.4 Excluded ingredients. The finished compound shall contain no ethoxylated or propoxylated phenols, polyethoxylated or propoxylated alcohols.

3.5 Solubility. The superconcentrate shall readily disperse in 120° F. hard water to a homogeneous solution, when tested as specified in 4.4.7.

3.5.1 The diluted superconcentrate shall remain as a homogeneous solution when stored for 72 hours at 0° F. when tested as specified in 4.4.7.2.

3.6 Stability. The packaged superconcentrate must maintain its chemical stability for a period of one year after receipt and show no tendency toward precipitation or sedimentation or leakage while in storage or transit under extreme ranges of temperature (-25° to 115° F.).

3.7 Odor. At use dilution concentrations the product shall be mildly perfumed.

3.8 pH value. The pH of a 1 percent solution of the compound in distilled water shall be not less than 9.5 or more than 10.5, when tested as specified in 4.4.8.

3.9 The film material of the plastic pouch used to package the superconcentrate cleaner shall meet the requirements as specified in table II.

TABLE II. Package film material requirements

Property	Requirement	Test method
Film density	0.936 to 0.940 g./cc.	Table IV
Film ultimate tensile strength	2500 p.s.i. (min.)	Table IV
Film elongation	300 percent (min.)	Table IV
Water vapor transmission	1.0 grams/100 sq. in./24 hrs. (max.)	Table IV
Greaseproofness	5-1/2 hrs. min. (hrs. to fail)	Table IV
Burst strength	2 in. diam. dart, 50 in. fall, 220 grams (50 percent failure weight)	Table IV

3.10 Accelerated storage test. The finished product (plastic pouch or bottle with superconcentrate) shall show no leakage, breakdown, or other deterioration when stored in a forced air oven at 79° C. for seven days, when tested as specified in 4.4.13.

3.11 Certificate of compliance. The manufacturer or supplier shall furnish the contracting officer a certificate of compliance showing that the finished compound meets the requirements of table I for the phenol content.

3.12 Pourability. The superconcentrate when packaged in a plastic bottle (see 5.1.1.2), shall be capable of draining 97 percent of its contents in 40 seconds when tested as specified in 4.4.10.

Source: https://assist.dla.mil - Downloaded: 2026-10-26T11:18Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Sampling for chemical tests. Sampling for inspection and acceptance shall be performed in accordance with MIL-STD-105, special inspection level S-1, AQL 2.5 percent defective.

4.2.1 Visual examination.

1. Fill of containers.
2. Leaks.
3. Damage.
4. Marking.

Sampling for visual examination shall be performed in accordance with MIL-STD-105, special inspection level S-3, AQL 2.5 percent defective.

4.3 Inspection of preparation for delivery. An inspection shall be made to determine that the packaging, packing, and marking comply with the requirements of 4.4 and section 5. Defects shall be scored in accordance with table III. For examination of interior packaging, the sample unit shall be one shipping container fully prepared for delivery, selected at random just prior to the closing operations. Defects of closure listed shall be examined on the shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. Sampling shall be in accordance with MIL-STD-105, inspection level S-2, with an acceptable quality level (AQL) of 4.0 defects per hundred units.

TABLE III. Classification of preparation for delivery defects

Examine	Defects
Containers	Not as specified.
Materials	Any component missing or damaged.
Quantity	Number of unit packages to intermediate package and number of intermediate packages to shipping container not as specified.
Markings	Omitted; incorrect; illegible; improper size, location, sequence, or method of application.
Workmanship	Inadequate application of components, such as incomplete closure of containers, or containers distorted.

4.4 Test methods.

4.4.1 Film material. The film material for the plastic pouch used to package the product shall conform to the requirements specified in table II, when tested in accordance with the test methods as specified in table IV.

TABLE IV. Film test methods

Property	Test method
Film density	ASTM D 1505
Film ultimate tensile strength	ASTM D 882
Film elongation	ASTM D 882
Water vapor transmission	ASTM E 96 (Procedure E)
Greaseproofness	MIL-B-121, Barrier Material, Greaseproofed, Waterproofed, Flexible.
Burst strength	ASTM D 1709 (Method B)

4.4.2 Anionic activity.

4.4.2.1 Reagents.

1. Carbon Tetrachloride C.P.
2. SDA-3A Alcohol (neutralized using O-cresol red as indicator).
3. 13.6 percent potassium chloride (Reagent grade).
4. Distilled H_2O.
5. O-Cresol red indicator.

Document provided by: https://assist.dla.mil -- Downloaded: 2026-01-26T17:57Z
Check the source to verify that this is the current version before use.

6. 0.1 N NaOH.

4.2.1.1 Procedure.

1. Into a 250 ml. separatory funnel, put 25 ml. ethyl alcohol and 50 ml. H_2O.
2. Add approximately 3.0 to 5.0 grams sample to separatory funnel from weighing bottle (Determine weight by difference), dissolve sample.
3. Add to separatory funnel, 50 ml. of carbon tetrachloride and 25 ml. of a 13.6 percent p-toluidine hydrochloride solution.
4. Shake funnel approximately 10 minutes. (Caution: From time to time, release pressure.) Then allow layers to separate.
5. Draw off bottom layer (carbon tetrachloride layer) into 500 ml. flask, containing 125 ml. of previously neutralized ethyl alcohol using O-cresol red as indicator. Be absolutely sure not to draw off any of the top layer.
6. Add 25 ml. of carbon tetrachloride to separatory funnel, shake for 2 minutes, allow to separate, and again draw off bottom layer.
7. Repeat step 6 for the third washing.
8. Combine all three extractions and titrate with 0.1 N NaOH to the O-cresol red end point (purple).

Calculation:

$$\text{Percent active} = \frac{V \times N \times \text{eq. W}}{S \times 10}$$

Where:

V = Volume (in. ml.) of NaOH used.
N = Normality of NaOH solution.
S = Weight of sample.

4.4.3 Moisture. Total moisture shall be determined in accordance with test method "Determination of Water at High Levels by Karl Fischer Titration" of Standard Methods of Chemical Analysis Vol. III pages 1841 - 42.

4.4.4 Alkali value. The amine value shall be determined in accordance with A.O.C.S. Method Tf1b-64.

4.4.5 Inorganic salts. Total inorganic salts shall be determined in accordance with A.O.C.S. Method Da2-48.

4.4.6 Tetra sodium ethylenediamine tetra acetate (EDTA) determination.

4.4.6.1 Reagents.

1. Potassium chromate solution.

   Weigh out 2.5 grams of potassium chromate, dissolve in distilled water, and dilute to 500 ml. in a volumetric flask.

2. EDTA standard solution.

   Weigh out 50, 100, 200, and 300 mg. of dried A.R. EDTA into each of four 100 ml. volumetric flasks. Add approximately 75 ml. of distilled water to each flask and dissolve. Add one NaOH pellet for each 100 mg. EDTA and dissolve. Dilute flasks to 100 ml. with distilled water.

3. Arsenious acid, 0.2 N.

   Weigh out 4.93 gm. of arsenious acid. Add 3.5 gm. of NaOH and dissolve in about 150 ml. of distilled water (warm). Neutralize with glacial acetic acid using phenolphthalein indicator, dilute to about 270 ml. and slowly add 200 ml. of glacial acetic acid with thorough mixing. Dilute to 500 ml. in volumetric flask.

4. Methanol - distilled water solvent (1:1).

4.4.6.1.1 Procedure.

Preparation of standard curve:

1. Pipette 2.0 ml. of each of the standard solutions into calibrated spectrophotometer tubes.
2. Add 2.0 ml. of the potassium chromate solution and mix.
3. Add 2.0 ml. of the arsenious acid reducing agent.
4. Place the tubes in a boiling water bath for 5 minutes, then remove and cool.
5. Add 10.0 ml. of distilled H_2O-methanol mixture (1:1) and shake.

Source: https://standards.iteh.ai Downloaded: 2026-01-26 11:11:18 EST
Check the source to verify that this is the current version before use.

6. Read the absorbance of the colored solution on the spectrophotometer at 560 mμ.
7. Prepare a blank for reference by using 2.0 ml. distilled water in place of an EDTA standard and proceed as above.

Sample analysis:

8. Weigh a 10.0 gm. sample into a 100 ml. volumetric flask and dissolve with about 60 ml. of the distilled water-methanol mixture, dilute to 100 ml. with same solvent.
9. Transfer a 10.0 ml. aliquot of the sample solution to a small beaker and acidify it with 1.0 ml. of glacial acetic acid.
10. Filter the acid solution through no. 42 filter paper to remove any precipitate and colloid and collect the filtrate in a 25 ml. volumetric flask.
11. Wash the filter paper well with the methanol distilled water mixture, collecting the washings in the 25 ml. flask.
12. Dilute the solution to the mark using methanol-water. Take a portion (15 ml.) and add 15 ml. of chloroform. Shake well and let stand 1 hour.
13. Pipette a 5.0 ml. aliquot of the supernatant liquid into a spectrophotometer tube.
14. Follow steps 2, 3, and 4 above.
15. Add 7.0 ml. methanol-distilled water.
16. Read the absorbance of the colored solution on the spectrophotometer at 560 mμ employing the reference blank used for the standards.

Calculations: $\frac{R}{W} \times 100 =$ percent EDTA

Where:

R = mg. from standard curve obtained from sample absorbance.
W = weight of sample in 5 ml. aliquot of step 13. (200 mg.)

4.4.7 Solubility. Add one part of sample to nine parts of hot hard water (120° F.) and stir vigorously for one minute. The product should be homogeneous.

4.4.7.1 Synthetic hard water. The synthetic hard water shall be made to the following formula:

0.264 gram/liter $CaCl_2.2H_2O$
0.295 gram/liter $MgSO_4.7H_2O$

The hard water salts should be dissolved in a small portion of distilled water, the solution transferred quantitatively to a liter volumetric flask, and the flask filled to volume.

4.4.7.2 The diluted sample (see 4.4.7), shall be cooled to 65° F. and stored at 65° F. for 72 hours. Observe at end of storage period for compliance with 3.5.1.

4.4.8 pH value. Make a 1.0 percent solution of the compound in freshly boiled and cool (room temperature) distilled water. Determine the pH value of this solution to the nearest 0.1 unit at room temperature (25° C. ± 2° C.), by means of a suitable pH meter which employs the glass electrode.

4.4.9 Ethylene glycol monobutyl ether.

4.4.9.1 Apparatus and reagents.

1. Gas chromatograph: Hewlett Packard Model 5756 programmed temperature gas chromatograph or equivalent with thermal conductivity detector.
2. Column: (two) 6', 1/8" stainless steel, 10 percent diethylene glycol succinate on 60 to 80 mesh nonacid washed chromasorb G.
3. 5 microliter syringe.
4. Normal Hexane, Eastman Practical Grade.
5. Cellosolve Acetate (Ethylene Glycol Monoethyl Ether Acetate), purified grade.
6. Butyl Cellosolve (Ethylene Glycol Mono Butyl Ether), technical grade as supplied by Union Carbide Chemical Co.

4.4.9.2 Procedure.

1. Set gas chromatograph for the following instrumental conditions:
   a. see 4.4.9.1 (2).
   b. limit stops at 60° C. and 130° C.
   c. post injection interval for 3 minutes.
   d. detector at 230° C.
   e. injection port at 230° C.
   f. chart speed 2" per minute unless digital integrator is used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:18Z
Check the source to verify that this is the current version before use.

e. temp. program at 10° C. per min,
h. carrier gas flow rate at 60 cc./min.
i. carrier gas: helium.
j. bridge current 150 ma.

2. Condition the instrument over the intended temp. range until a stable base line is obtained.

3. Make up a reference solution (A) of equal parts by weight of cellosolve acetate and butyl cellosolve in normal hexane (i.e., 10 grams ca, 10 grams bc, 80 grams hexane). Inject 3 microliters of solution (A) into the gas chromatograph and press the inject start button. Make triplicate runs and average the area of similar peaks. Calculate the area ratio for Butyl cellosolve/cellosolve acetate (factor F). Time to completion of a run should be less than 15 minutes. The CA peak appears prior to the BuC peak.

4. Weigh out 10 grams cellosolve acetate. Add 90 grams bacteriostat-detergent. This is solution (B). Add an equal volume of hexane. Shake vigorously for 30 seconds. Allow two layers to separate. Remove top clear layer of hexane extract and inject 3 microliters in the gas chromatograph. Make triplicate runs and average similar peak areas. Calculate the peak area ratio Butyl cellosolve/cellosolve acetate. If the particular formulation of bacteriostat-detergent does not give a clear upper layer, decrease the hexane/sample volume ratio to obtain a clear layer.

5. Calculation:

$$\frac{\text{Area under the Butyl Cellosolve curve}}{\text{Area under the Cellosolve Acetate curve}} \times F \times 10 = \text{Weight percent of Butyl Cellosolve in sample}$$

4.4.10 Pourability (plastic bottle). The bottled end item (see 5.1.1.2), shall be stored at 70° ± 2° F. for five days. The bottle shall then be inverted for 40 seconds. No less than 97 percent of the superconcentrate shall have been discharged.

4.4.11 Bacteriostatic activity. Place 0.1 ml. of the diluted product as specified under 3.2 (1 oz. superconcentrate to 2-1/2 gallons of distilled water) in cup of seeded nutrient agar prepared by dispensing 25 ml. sterile nutrient agar (Official Methods of Analysis A.O.A.C. 10th edition 1965, p. 80 5.001 (a) (3) previously melted in tube and cooled to 42° to 45° C., inoculated with 0.15 ml., 24 to 32 hr. nutrient broth culture of Staphylococcus aureus, ATCC 6538, maintained as specified under 5.001 (b) p. 80 Official Methods of Analysis A.O.A.C. 10th Edition, 1965, mixed and poured into 110 mm. sterile petri dish containing one sterile polished stainless steel cylinder (penicillin cup) 8 mm. o.d., 6 mm. i.d. - 10 mm. in length, type 304 stainless steel, SS 18-8 (obtainable from S & L Metal Products Corp., 58-29 57 Drive, Maspeth, New York) and allowed to solidify at room temperature. The steel cylinder shall have been placed in the center of the plate and the melted seeded agar evenly distributed. When the seeded agar has solidified, the cylinder shall have been aseptically removed and 1 (one) drop of sterile melted agar added to the cup to provide a bottom layer of agar when solidified.

After the 0.1 ml. of test solution is added to the cup, the petri dish shall be incubated for 48 hrs. at 37° C. Examine the plates after 24 hrs. and 48 hrs. of incubation for a clear zone around the periphery of the cup containing the test solution. A clear and measurable zone of inhibition after the 48 hrs. incubation period is necessary to show that the product is bacteriostatic. The above test shall be run in triplicate.

4.4.12 Fatty acids. Ten grams of the detergent bacteriostat concentrate shall be dissolved in 100 ml. of a 10 percent ethanol-water solution. Five (5) ml. of 6 N H_2SO_4 is added and mixed until homogeneous. The mixture is transferred to a 500 ml. volumetric flask and is diluted to mark with additional 10 percent ethanol-water solution. The flask shall be allowed to stand for two hours and examined for oil separation at surface of liquid layer. The presence of an oil or fatty acid on the surface shall be considered as failing the fatty acid requirements of table I. Note: The above procedure is qualitative only and a trace of fatty acid should not be detected by the above method.

4.4.13 Accelerated storage test. The finished product shall be stored in a forced draft oven at 75° C. for seven days to determine compliance with 3.10.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level B or C, as specified (see 6.2).

5.1.1 Level B. Twelve ounces of bacteriostat detergent shall be packaged in one of the containers specified in 5.1.1.1, or 5.1.1.2. Unless otherwise specified (see 6.2), choice of containers shall be that of the supplier.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:18Z
Check the source to verify that this is the current version before use.

5.1.1.1 Plastic pouch enclosed in fiberboard. The plastic used in fabricating the pouch shall meet the physical requirements of 3.9. The pouch shall be the pillow type with top and bottom seams. Closure of the filled pouch shall be as recommended by the supplier of the material used, except that pressure-sensitive adhesive tabs shall not be used. The plastic shall be not less than 3 mil. thick and so constructed and sealed as to insure no leakage during transit or storage. The product shall not affect the package nor the package affect the product. The pouch shall be packaged in a fiberboard container conforming to PPP-B-636, style OPF, except that the inner flaps shall meet, covering the entire length of the container, with the outer flaps meeting at the centers and covering the width of the container. To facilitate closure the outer flaps shall have side tabs. The inner flaps shall have a die-cut opening of sufficient width and length to receive the tabs (see fig. 1). The package shall be suitable for mailing.

5.1.1.2 Plastic bottle. The bottle shall conform to PPP-C-186, group A, class 2, style 1 or 2, grade 1 or 2, closure A, seal A. The plastic used in making the bottle shall be one which will not affect the package nor the package affect the product. Each bottle shall be packaged in a tube conforming to PPP-T-095, type I, class 1 or 2, style C or D, or in a fiberboard box conforming to PPP-B-636, class domestic, style optional. The package shall be suitable for mailing.

5.1.1.3 Intermediate packaging. Ten unit packages shall be intermediate packaged in a snug-fitting fiberboard box conforming to PPP-B-636, class domestic.

5.1.2 Level C. The product, in the quantity specified, shall be packaged to afford protection against deterioration and damage during shipment from the supply source to the first receiving activity for immediate use or controlled humidity storage.

5.2 Packing. Packing shall be level A, B, or C, as specified (see 6.2).

5.2.1 Level A. Eight intermediate packages (see 5.1.1.3), shall be packed in a snug-fitting fiberboard box conforming to PPP-B-636, class weather-resistant.

5.2.2 Level B. Eight intermediate packages (see 5.1.1.3), shall be packed in a snug-fitting fiberboard box conforming to PPP-B-636, class domestic.

5.2.3 Level C. The product, packaged as specified in 5.1, shall be packed to insure carrier acceptance and safe delivery at destination at the lowest transportation rates in containers complying with the Uniform Freight Classification Rules or National Motor Freight Classification Rules, as applicable.

5.3 Marking. In addition to any special markings required by the contract or order and the special markings required by paragraph 5.3.1, each shipping container shall be marked in accordance with Fed. Std. No. 123 or MIL-STD-129, as applicable.

5.3.1 Special markings. Each unit package shall be marked with the following instructions. (Alternatively, when material is packaged in plastic pouch, the special markings may be printed on an inserted label). When bottles are used, the special markings shall be lithographed.

HOW TO MIX STOCK CONCENTRATE

1. Fill wide mouth gallon jar 7/8 full with hot water.
2. Pour entire contents of the package into the jar of hot water.
3. Stir (or close and shake) the jar until contents are uniformly mixed. STOCK CONCENTRATE is now ready for further dilution for use.

RECOMMENDED DILUTIONS

1. HEAVY DUTY CLEANING OR WAX REMOVAL: 10 parts of water to 1 part of STOCK CONCENTRATE mix.
2. CLEANING WALLS, FLOORS, WOODWORK: 20 parts of water to 1 part of STOCK CONCENTRATE mix.
3. LIGHT OR GENERAL CLEANING: 40 parts of water to 1 part of STOCK CONCENTRATE mix.

6. NOTES

6.1 Intended use. The detergent bacteriostat covered by this specification is intended as a general purpose cleaner bacteriostat for building maintenance.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Quantity of detergent bacteriostat required.
(c) Level of packaging and packing (see 5.1 and 5.2).
(d) Whether a particular type of unit package is required (see 5.1.1).
(e) Quantity to unit package (see 5.1.2).
(f) Special markings required (see 5.3.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:18Z
Check the source to verify that this is the current version before use.