P-D-1295A
February 4, 1977
SUPERSEDING
Int. Fed. Spec. P-D-001295(GSA-FSS)
May 2, 1968

FEDERAL SPECIFICATION

DEODORANT, GENERAL PURPOSE (CONCENTRATED)

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE

1.1 Scope. This specification covers a concentrated liquid general purpose deodorant for use in space sprays or scrub water (see 6.1).

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specifications:

PPP-B-636 - Boxes, Shipping, Fiberboard.
PPP-F-320 - Fiberboard, Corrugated and Solid, Sheet Stock (Container Grade), and Cut Shapes.

Federal Standard:

Fed. Std. No. 123 - Marking for Shipment (Civil Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:18Z
Check the source to verify that this is the current version before use.

Laws and Regulation:

16 CFR 1500 - Federal Hazardous Substances Act Regulations.

(The Code of Federal Regulations (CFR) and the Federal Register (FR) are for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402. When indicated, reprints of certain regulations may be obtained from the Federal agency responsible for issuance thereof).

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

National Motor Freight Traffic Association, Inc., Agent:

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Associations, Inc., Tariff Order Section, 1616 P Street, N.W., Washington, DC 20036.)

Uniform Classification Committee, Agent:

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza., Chicago, IL 60606.)

3. REQUIREMENTS

3.1 Finished product. The finished product shall be a concentrated liquid deodorant consisting of odor masking, destroying or neutralizing compounds and other ingredients as required to insure that the finished product meets all the requirements of section 3.

3.2 Excluded materials. The finished product shall not contain formaldehyde or odor blocks which desensitize the olfactory system.

3.3 Odor. When the deodorant is used as directed on the label (see 3.5), any residual odor shall be mild and pleasant. The residual odor shall not be heavy or cloying.

3.4 Performance. When tested as specified in 4.3.1, the deodorant shall effectively eliminate objectional odors.

3.5 Directions for use. The unit packages (see 5.1) of the deodorant shall be labeled with directions for dilution and use in scrub water and space sprays.

3.6 Solubility in water. When tested as specified in 4.3.2, the deodorant shall be completely soluble in distilled water, or form a uniform, stable emulsion.

3.7 Detrimental action on surfaces. The manufacturer shall provide a warranty that when used as directed, the deodorant shall not have any detrimental effect upon metal or paint surfaces, when compared to water used in the same manner.

3.8 Laws and regulations. The finished product shall comply with the Federal Hazardous Substances Act and rules and regulations published thereunder.

3.9 Workmanship. The finished product shall be a clear, homogeneous liquid or uniform, stable emulsion. The finished product shall have no traces of dirt, sediment, or suspended particulate matter.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:18Z
Check the source to verify that this is the current version before use.

4.2 Quality conformance inspection.

4.2.1 Inspection of the end item. Components and materials shall be inspected and tested in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended or qualified in this specification or applicable purchase documents.

4.2.2 Examination of preparation for delivery. Packaging, packing and marking shall be examined to determine compliance with the requirements of section 5. Defects shall be scored in accordance with table I. Sampling and acceptance shall be in accordance with MIL-STD-105, inspection level S-2, acceptable quality level (AQL) of 4.0 percent defective. The sample unit shall be one shipping container fully prepared for delivery.

TABLE I. Examination of preparation for delivery

Examine	Defect
Containers	Not as specified.
Contents	Not as specified.
Markings	Omitted; Incorrect; Illegible; Improper size, location, sequence or method of application.
Materials	Component missing or damaged.
Workmanship	Bulging or distortion of containers; cushioning inadequate, improper or missing.

4.2.2.1 Examination of closure,waterproofing and banding of containers. When shipping containers are required to comply with PPP-B-636, examination for defects in closure, waterproofing and banding shall be in accordance with the appendix to that specification.

4.2.3 Examination of the end item. The end item shall be examined for defects in accordance with table II. Sampling and acceptance shall be in accordance with MIL-STD-105, inspection level S-2, AQL of 4.0 percent defective. The sample unit shall be one unit package (see 5.1).

TABLE II. Examination of the end item

Examine	Defect
Unit package	Not as specified.
Net contents	Less than specified.
Workmanship	Contents contain dirt, sediment or suspended particulate matter.

4.2.4 Testing of the end item. The end item shall be tested as specified in table III. Testing shall be performed on a composite sample obtained as follows. For 1-ounce containers: from the lot, randomly select 10 containers, combine the contents of the containers and mix thoroughly. For 1-gallon containers: from the lot, randomly select 5 containers, take a 50 ml portion from each container so selected and mix them thoroughly together. Place the composite sample in a clean, dry, glass container; seal and label with the date and batch number. Perform each test in duplicate. Failure of the composite sample to pass any of the tests shall be cause for rejection of the lot.

TABLE III. Instructions for testing the end item

Property	Requirement paragraph	Test method paragraph
Performance	3.4	4.3.1
Solubility	3.6	4.3.2

4.3 Test methods.

4.3.1 Performance. The performance test consists of two parts - contact performance, and spray performance. A panel of six persons, consisting of both men and women, shall make the odor evaluations in 4.3.1.3 and 4.3.1.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:18Z
Check the source to verify that this is the current version before use.

4.3.1.1 Reagents.

4.3.1.1.1 Malodor number 1. Malodor No. 1 (to simulate bathroom odor) shall consist of 0.5 gram scatole (3-methylindole) per liter isopropanol solution. To make malodor No. 1, dissolve 0.50 gram of skatole in 25 ml of 99% isopropanol in a 100 ml volumetric flash and fill to mark with isopropanol. Mix well. Transfer to a 1000 ml volumetric flask, fill to the mark with distilled water and mix well. Store in a stoppered or capped glass container.

4.3.1.1.2 Malodor number 2. Malodor No. 2 (to simulate hospital odor) shall consist of 1 ml of malodor No. 2 concentrate diluted to a final volume of 1000 ml with distilled water and mixed well. Make malodor No. 2 concentrate by thoroughly mixing the ingredients in table IV in the specified proportions. Store both the malodor No. 2 and the malodor No. 2 concentrate in stoppered or capped glass containers.

Precautions: Malodor No. 2 concentrate contains ingredients which are toxic if swallowed or if the concentrated vapors are breathed for a long time. Handle with care. Prepare in a well ventilated room or exhaust hood. Wash the skin thoroughly if the concentrate comes in contact with the skin.

TABLE IV. Malodor No. 2 concentrate

Ingredient	Percent
Creosol, pure	0.42
Tetrachloroethane (Reagent grade)	36.21
Quinoline (Technical), B.P. 84° to 121°C	8.36
Guaiacol (Practical)	8.36
Eugenol, USP	4.18
Methyl salicylate	4.18
Isopropanol (99%)	38.29

4.3.1.2 Spray gun. The spray gun used in 4.3.1.4 shall be a Paasche A-AUDF-2 automatic spray gun (Paasche Airbrush Company, 1909 W. Diversey Parkway, Chicago, IL 60614).

4.3.1.3 Contact performance. Dilute 1.5 ml of the composite sample of the deodorant to 50 ml final volume with distilled water. Place 4 ml of this diluted deodorant in an evaporating dish and add 10 ml of malodor No. 1 and stir well (dish "a"). Place 10 ml of malodor No. 1 in another dish of the same size (dish "b"). The panel shall compare the odor from each dish in an odor-free room. The panel shall smell dish "a", wait 1 minute and then smell dish "b". After 5 minutes the panel shall smell dish "b", wait 1 minute and then smell dish "a". The odor of dish "a", shall be significantly less than that from dish "b". Transfer contents of each dish to separate 100 ml glass stoppered cylinders rinsing the dishes with water and adding the water to the cylinders. Fill the cylinders to the 100 ml mark with water. Mix well. Pour contents of cylinders into separate 150 ml beakers. The panel shall compare the odor from the beakers by the same procedure used above for the dishes. Odor from dilution of dish "a" shall be significantly less than odor from dilution of dish "b". Repeat the procedure using malodor No. 2.

4.3.1.4 Spray performance. Pour 200 ml of malodor No. 1 into each of three shallow pans and allow to evaporate at 25° ± 1°C for 15 minutes in a closed, airtight room (approximately 9' x 8' x 5.5'). Remove the pans from the room after 15 minutes. Have the panel observe the intensity of the malodor in the room. Dilute 7.8 ml of the deodorant composite sample to 500 ml with distilled water, and load into a Paasche automatic spray unit (see 4.3.1.2). Spray the room with the diluted deodorant for 2 minutes with the air control valve adjusted to 40; the fluid adjusting nut set to 80, and air line pressure of 50 p.s.i. Have the panel examine the room again. The malodor shall be completely masked by the deodorant. Repeat the above procedure with malodor No. 2.

NOTE: Protective inhalation masks should be worn during the spraying.

4.3.2 Solubility. Dilute 6.3 ml of the composite sample of deodorant to 100 ml volume with distilled water at 25° ± 1°C. Maintaining temperature at 25°C, stir vigorously for 5 minutes. Allow to stand at 25°C for 15 minutes. The deodorant shall either be completely soluble in the water, or form a homogeneous emulsion with no traces of separation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:18Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. The general purpose deodorant covered by this specification is intended to be used to mask unpleasant odor in lavatories, hospitals, sick rooms, kennels, morgues, and similar applications. It is intended to be diluted and used as a space spray or in scrub water. It may be used in a wick bottle, however water will remain in the bottle after the active ingredients have evaporated.

6.2 Ordering data. Purchasers should select the preferred options permitted herein, and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Quantity required.
(c) Selection of applicable level of packaging and packing required (see 5.1 and 5.2).
(d) Marking document required (see 5.3).

MILITARY INTEREST:

Using activity:

DSA-GS

CIVIL AGENCY COORDINATING ACTIVITY:

GSA-FSS

Preparing activity:

GSA-FSS

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See Section 2 of this specification to obtain extra copies and other documents referenced herein. Price ents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:18Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A, B, or C, as specified (see 6.2).

5.1.1 Levels A and B.

5.1.1.1 Unit packaging.

5.1.1.1.1 One-ounce quantities. One fluid ounce of deodorant shall be packaged in a bottle of the type normally used for the item.

5.1.1.1.2 One-gallon quantities. One-gallon of deodorant shall be packaged in a high density polyethylene bottle with a plastic screw type cap.

5.1.1.2 Intermediate packaging.

5.1.1.2.1 One-ounce quantities. Four (4) bottles of deodorant, as specified in 5.1.1.1.1, shall be intermediately packaged in a paperboard box of the type normally used for the product. Dividers or cushioning shall be provided to separate the bottles.

5.1.1.2.2 One-gallon quantities. One-gallon bottles do not require intermediate packaging.

5.1.2 Level C. The deodorant, in quantities as specified, shall be packaged to afford adequate protection against deterioration and damage during shipment from the supplier to the first receiving agency.

5.2 Packing. Packing shall be level A, B, or C, as specified (see 6.2).

5.2.1 Level A.

5.2.1.1 One-ounce quantities. Thirty-six (36) intermediate packages (144 bottles) of deodorant shall be packaged in a box conforming to PPP-B-636, class weather-resistant. The box shall be closed, waterproofed and banded in accordance with the appendix to PPP-B-636.

5.2.1.2 One-gallon quantities. Four filled bottles shall be packed in a box conforming to PPP-B-636, class weather-resistant. The box shall be fitted with dividers or partitions the full height of the box to separate the bottles. The fiberboard for the partitions shall conform to PPP-F-320, type CF, class domestic, variety SW, grade 200. A minimum of 3/8 inch clearance shall be provided between the top of the bottles and the surfaces of the inner flaps of the box. The box shall be closed, waterproofed and banded in accordance with the appendix to PPP-B-636.

5.2.2 Level B.

5.2.2.1 One-ounce quantities. Thirty-six (36) intermediate packages (144 bottles) of deodorant shall be packed in a fiberboard box conforming to PPP-B-636, class domestic, style RSC. The box shall be closed in accordance with the appendix to PPP-B-636.

5.2.2.2 One-gallon quantities. Four (4) bottles of deodorant shall be packed in a box conforming to PPP-B-636, class domestic. The box shall be fitted with dividers or partitions as specified in 5.2.1.1. The box shall be closed in accordance with the appendix to PPP-B-636.

5.2.3 Level C. Deodorant, in quantities as specified, shall be packed in containers to assure carrier acceptance and safe arrival at destination. Containers shall comply with Uniform Freight Classification or National Motor Freight Classification, as applicable.

5.3 Marking.

5.3.1 Unit packages. Unit packages shall be marked with normal commercial markings to include name or tradename of contents, name or trademark of manufacturer, net contents, and directions for use as specified in 3.5.

5.3.2 Intermediate packages and shipping containers. The intermediate packages and shipping containers shall be marked in accordance with Fed. Std. No. 123 or MIL-STD-129, as specified (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:18Z
Check the source to verify that this is the current version before use.