P-D-800C
January 30, 1976
SUPERSEDING
Fed. Spec. P-D-800B
August 24, 1961

FEDERAL SPECIFICATION

DUST MOP TREATING COMPOUND

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers dust mop treating compound for use in treating dust mops and dust cloths prior to use (see 6.1).

1.2 Classification. This specification covers material of one grade and two types as specified:

Type I - Regular (ready to use liquid).
Type II - Concentrate (dilute 1 part concentrate with 6 parts water).

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

Federal Specifications:

T-M-561 - Mophead, Wet, Cotton.
PPP-C-96 - Cans, Metal, 28 Gage and Lighter.
PPP-P-704 - Pails, Metal: Shipping, Steel (1 Through 12 Gallon).

Federal Standard:

Fed. Std. No. 123 - Marking for Shipment (Civil Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks, and the Index of Federal Specifications and Standards, from established distribution points in their agencies.)

FSC 7930

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:18Z
Check the source to verify that this is the current version before use.

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

American Society for Testing and Materials (ASTM) Standard:

D-93 - Flash Point by Pensky-Martens Closed Tester, Test for.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

National Motor Freight Traffic Association, Inc., Agent:

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Associations, Inc., Tariff Order Section, 1616 P Street, NW., Washington, DC 20036.)

Uniform Classification Committee, Agent:

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

3. REQUIREMENTS

3.1 Material. Type I, undiluted, and Type II, both undiluted and when mixed in the ratio of 1 part compound to 6 parts water, shall be a stable, free-flowing liquid emulsion consisting of mineral oils, emulsifying agents, and water.

3.2 Stability. The compounds shall be stable, without separation or creaming, and without loss of effectiveness for a period of 1 year. In addition, the compounds shall show no separation or creaming when tested as specified in 4.4.1.

3.3 Flash point. The flash point of these compounds shall be not less than 176.7°C (350°F) when tested as specified in 4.4.2.

3.4 Excluded ingredient. The compounds shall contain no alcohol.

3.5 Spontaneous combustion. When tested as specified in 4.4.3, the compounds shall show no evidence of spontaneous heating, oxidation, or ignition.

3.6 Impregnation. The compounds shall uniformly impregnate the cloth or mop. When tested as specified in 4.4.4, the compounds shall be present to the extent of 17.5 percent minimum, or 35 percent maximum, of the dry weight of the cotton mop. After 48 hours standing at 50°C (122°F), the impregnated mop shall be within 1 percent of its original impregnated weight.

3.7 Dirt pick-up efficiency. The impregnated mop shall pick up not less than 22 percent standard soil, based on the initial weight of the impregnated mop, when tested as specified in 4.4.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:18Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Inspection. Sampling for inspection shall be performed in accordance with MIL-STD-105, except when otherwise indicated hereinafter. For purposes of sampling, an inspection lot for examinations and tests shall consist of material all from the same manufactured batch.

4.3 Examination of preparation for delivery. An examination shall be made to determine compliance with the packing and marking requirements of section 5. Defects shall be scored as specified in table I. Sampling shall be in accordance with MIL-STD-105. The sample unit shall be one container fully prepared for delivery. The lot shall be the number of containers offered for inspection at one time. The inspection level shall be S-2 with an AQL of 4.0 expressed in terms of percent defective.

TABLE I. Examination of preparation for delivery

Examine	Defect
Container	Not as specified.
Content	Not as specified.
Marking	Omitted; incorrect; illegible; improper size, location, sequence, or method of application.
Material	Component missing or damaged.
Workmanship	Bulging or distortion of containers.

4.4 Test procedures.

4.4.1 Stability. Place approximately 500 ml of the compounds in a suitable polyethylene bottle and subject to three freeze-thaw cycles. Decant into a glass beaker and examine for compliance with 3.2. In addition, place approximately 500 ml of the compounds in a glass stoppered flask and maintain at 50°C (122°F) for 48 hours. Allow to come to room temperature and examine for compliance with 3.2.

4.4.2 Flash point. The flash point of the compounds shall be determined by the Pensky-Martens method, as described in ASTM D-93.

4.4.3 Spontaneous combustion.

4.4.3.1 Preparation of sample. At the band of a mop conforming to T-M-561, cut off the yarn strings and wash thoroughly with agitation in a warm solution of 5 percent potassium oleate soap and a trace of ammonia (1 ml of 28 percent aqueous ammonia per liter) for 20 minutes. Rinse the strings thoroughly, wring out the excess liquid, and allow to air dry.

Weigh 16 to 17 g. of the dry strings for each test, immerse them in the compound being tested for 10 minutes, and hang them to drain and dry for 18 hours.

Form the strings (which may be slightly damp) into a compact bundle and place them in a snugly fitting glass beaker.

4.4.3.2 Procedure. Place the beaker with the strings in an oven maintained at 97° ± 2°C and insert one thermocouple in the center of the strings to measure the temperature at the center, and a second thermocouple in oven, within 5 cm of the beaker. Both thermocouples should be attached to a continuously recording chart so that the temperature of oven and sample can be simultaneously recorded. Conduct the test for 72 hours.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:18Z
Check the source to verify that this is the current version before use.

4.4.3.3 Evaluation. Examine the sample and the 72-hour temperature recording. Evidence of charring or scorching in the sample shall be cause for rejection. A temperature rise in the center of the sample to above 100°C shall also be cause for rejection.

4.4.4 Impregnation. Weigh 20 to 30 g. of thoroughly dry mop strings, prepared as specified in 4.4.3.1, to the nearest 0.01 g. Immerse with stirring in 300 ml Type I mop treating compound, or in 300 ml of 1 part Type II mop treating compound diluted with 6 parts water, for 10 minutes. Remove strings and shake to remove surplus liquid and age for 24 hours at 25° ± 2°C and 50 ± 5 percent relative humidity. Weigh and calculate percent compound retained on mop strings, then place the section of impregnated mop strings in an oven maintained at 50° ± 2°C and 65 ± 5 percent relative humidity for 48 hours. Remove, allow to come to room temperature, and reweigh. The amount of impregnating compound should be the same within ± 1 percent after the 48-hour period.

4.4.5 Dirt pick-up efficiency. Prepare a synthetic soil according to the following formulation:

Ingredient	Percentages
Walnut sawdust: made with a rotary sanding machine using No. 2 paper on the open grain flat surface of walnut wood	20
Free carbon:	
Lampblack	15
Charcoal, cocoanut, 6-14 mesh	15
Silica:	
18-120 mesh	10
140 mesh	10
240 mesh	10
Pumice powder, N.F.	10
Fuller's Earth, powder, technical	10
	100

Make up five samples of impregnated mop strings as specified in 4.4.4, except that they need not undergo the final 48 hours at 50°C. Fluff the mop strings by shaking, and weigh them to the nearest 0.01 g. The impregnated mop strings should weigh 20-30 g. and be 6-7 cm long. Fasten them securely to lid of a 454 ml (1 pint) Mason jar, or equal, so that about 3 cm of mop strings are hanging loose on either side of the fastening, and place 20 g. of the synthetic soil in the Mason jar. Place the lid on the jar, and place jar and lid on a shaking machine and shake at 450-500 oscillations per minute for 10 minutes.

At the end of 10 minutes, unscrew the lid, and holding the mop strings over a tared dish, unfasten them and weigh them.

The average weight of the five samples shall be taken, and the average weight of retained soil shall be not less than 22 percent of the weight of the impregnated mop strings.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level B or C, as specified (see 6.2).

5.1.1 Level B.

5.1.1.1 One-gallon quantity. One gallon of dust mop treating compound shall be packaged in a can conforming to PPP-C-96, type V, class 4 or 5, with plan A exterior coating. The can shall be furnished with a bridge type handle.

5.1.1.2 Five-gallon quantity. Five gallons of dust mop treating compound shall be packaged in a pail conforming to PPP-P-704, type I, class 8, equipped with a spout or nozzle closure and outer seal.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:18Z
Check the source to verify that this is the current version before use.

5.1.2 Level C. The dust mop treating compound shall be packaged to afford adequate protection from the supply source to the first receiving agency.

5.2 Packing. Packing shall be level A, B, or C, as specified (see 6.2).

5.2.1 Levels A and B.

5.2.1.1 One-gallon quantities. Six (6) one-gallon cans shall be packed in accordance with the appendix to PPP-C-96 for level A or B packing, as applicable.

5.2.1.2 Five-gallon quantities. The five-gallon pail does not require packing.

5.2.2 Level C. The dust mop treating compound, in quantities as specified (see 6.2), shall be packed in containers to assure carrier acceptance and safe arrival at destination. Containers shall comply with the Uniform or National Motor Freight Classification, as applicable.

5.3 Marking. In addition to any special markings required in the procurement documents, marking of the unit and shipping containers shall be in accordance with Fed. Std. No. 123 for civil agencies or MIL-STD-129 for military agencies, as applicable (see 6.2).

6. NOTES

6.1 Intended use. Dust mop treating compound is intended to facilitate dusting by increasing the dust-loading capacity of dust mops and dust cloths.

6.2 Ordering data. Purchasers should select the preferred options permitted herein, and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Type required (see 1.2).
(c) Quantities required.
(d) Packing and packaging required (see 5.1 and 5.2).
(e) Marking document required (see 5.3).

MILITARY INTEREST:

The Defense Department has waived coordination on all revisions or amendments of this specification until further notice.

CIVIL AGENCY COORDINATING ACTIVITY:

GSA-FSS

Preparing Activity:

GSA-FSS

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See Section 2 of this specification to obtain extra copies and other documents referenced herein. Price 30 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:18Z
Check the source to verify that this is the current version before use.