P-H-1722
October 17, 1974

FEDERAL SPECIFICATION

HANDCLEANER PAD

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE

1.1 Scope. This specification covers one type of handcleaning pads made of an absorbent material and saturated with cleansing solution (see 6.1).

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specifications:

GG-B-60 - Ball Point Pen, Single Cartridge.
GG-M-114 - Marker, Tube Type, Felt Tip (Capillary-Action).
TT-I-556 - Ink, Stamp Pad.
PPP-B-566- Boxes, Folding, Paperboard.
PPP-B-636- Boxes, Shipping, Fiberboard.

Federal Standard:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civil Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.

Laws and Regulations:

16 CFR 1500 - Federal Hazardous Substances Act.

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:19Z
Check the source to verify that this is the current version before use.

(The Code of Federal Regulations (CFR) and the Federal Register (FR) are for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402. When indicated, reprints of certain regulations may be obtained from the Federal agency responsible for issuance thereof.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

American Society for Testing and Materials (ASTM) Standards:

D 1122 - Specific Gravity of Engine Antifreezes by the Hydrometer.
E 70 - pH of Aqueous Solutions with the Glass Electrode.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA. 19101.)

National Motor Freight Traffic Association, Inc., Agent:

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Associations, Inc., Tariff Order Section, 1616 P Street, N.W., Washington, DC 20036.)

Uniform Classification Committee, Agent:

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

3. REQUIREMENTS

3.1 Materials.

3.1.1 Pads. Pads shall be made of cotton or synthetic fiber material. The weight of the material shall be not less than 80 grams per square yard. Pads shall be absorbent, white, of uniform composition, even edged, soft to the touch, clean and shall not fray or separate during use (see 4.2.2.2 and 4.2.2.4).

3.1.2 Cleansing solution.

3.1.2.1 General composition. The cleaning solution shall consist of water, denatured alcohol, synthetic detergent(s), humectant(s), mild perfume, and perservatives. Additional components are permitted.

3.1.2.2 The cleansing solution shall not stain white paper nor shall it leave a gritty or sticky film on the hands after use (see 4.2.2.4).

3.1.2.3 Physical and chemical properties. The cleansing solution shall conform to the requirements of table I (see 4.2.2.4).

TABLE I. Physical and chemical requirements

Property	Minimum	Maximum
Specific gravity at 15.5°C	0.958	0.978
pH of 1:5 by volume dilution at 25°C	7.0	9.0

3.1.2.4 Nonvolatile matter. Nonvolatile matter shall consist primarily of nonvolatile surfactants, humectants and nonvolatile substances present in denatured alcohol (see 4.2.2.1).

3.1.2.5 Dermal irritation. The cleansing solution shall have a primary irritation score of 0 (zero) when tested as specified in 16 CFR 1500.41 except that the animals shall not be wrapped with the impervious material (see 4.2.2.1).

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:19Z
Check the source to verify that this is the current version before use.

3.2 Pad dimensions. The pads shall be circular, with a diameter of not less than 2-7/8 inches, or rectangular with length of not less than 2-7/8 inches and width of not less than 2-7/8 inches (see 4.2.2.2).

3.3 Unit container. Fifty pads shall be saturated with cleansing solution and packaged in a plastic container with a tight-fitting lid. A plastic bag or liner is required (see 4.2.2.2).

3.3.1 Weight of cleansing solution per unit container. For each square inch of pad in the unit container, at least 0.283 gram of cleansing solution shall be added. The total weight of cleansing solution to be added is determined by multiplying the number of pads per container by the surface area (to 3 significant figures) of one side of each pad by 0.283 gram (see 4.2.2.4).

3.4 Shelf life. The pads shall remain saturated with cleansing solution and the cleansing solution shall not lose its cleansing ability during storage for a period of twelve months under general warehouse conditions at temperatures below 110 degrees Fahrenheit. The product shall not spoil with mildew or other discoloration (see 4.2.2.1 and 4.2.2.2).

3.5 Performance. The pads shall perform as specified in 4.3.3 in the removal of ink soils.

3.6 Certificate of compliance. The manufacturer shall certify that his product complies with requirements 3.1.2.4, 3.1.2.5, and 3.4.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.1.1 Certificates of compliance. Where certificates of compliance are submitted, the Government reserves the right to check such items to determine the validity of certification.

4.2 Quality conformance inspection.

4.2.1 Sampling for inspection. Sampling for inspection shall be performed in accordance with MIL-STD-105 except where otherwise indicated (see 6.3 and 6.4).

4.2.2 Inspection of the end item. In accordance with 4.1 above, components and materials shall be inspected and tested in accordance with all requirements of the referenced specifications, drawings, and standards unless excluded, amended or qualified in this specification or applicable contract or purchase documents. Where failure is reported, report description of failure or numerical point of failure, as appropriate.

4.2.2.1 Review of certificate of compliance. Conformance of the lot with the requirements of 3.1.2.4, 3.1.2.5, and 3.4 shall be verified by review of a certificate of compliance furnished by the manufacturer.

4.2.2.2 Examination of the end item. Unit packages and pads shall be examined for the defects listed in table II. The sample unit shall be one unit container. The lot size shall be the number of unit containers in the lot. Inspection level shall be S-4 with an acceptable quality level (AQL) of 4.0 defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:19Z
Check the source to verify that this is the currentversion before use.

TABLE II. Examination of the end item

Examine	Defect
Pad:	
Appearance	Not white. Mildewed and spoiled. Not soft.
Workmanship	Uneven or ragged edges. Dirty, torn, holes.
Dimensions	Not as specified.
Unit package:	
Appearance	Not clean.
Workmanship	Lid not tight fitting. Wet or sticky, indicating leakage of cleansing solution. Cracked or broken. No liner.
Labeling	Missing, incomplete, incorrect or illegible.
Pad count	Less than specified.

4.2.2.3 Examination of preparation for delivery. An examination shall be made to determine compliance with the packaging, packing, and marking requirements of section 5. Defects shall be scored as in table III. The sample unit shall be one shipping container fully prepared for delivery. The lot size shall be the number of shipping containers offered for delivery at one time. The inspection level shall be S-2 with an AQL of 4.0 defects per hundred units.

TABLE III. Examination of preparation for delivery

Examine	Defect
Containers	Not as specified.
Contents	Not as specified.
Markings	Omitted; incorrect; illegible; improper size, location, sequence or method of application.
Materials	Component missing or damaged.
Workmanship	Bulging or distortion of container. Cushioning inadequate, improper or missing.

4.2.2.3.1 Examination of closure, waterproofing, and banding of containers. When shipping containers are required to comply with PPP-B-636, examination for defects in closure, waterproofing, and banding shall be in accordance with the appendix of that specification.

4.2.2.4 Testing of the end item. The end item shall be tested as specified in table IV. The sample unit for testing shall be 7 unit containers. The lot size shall be the number of sample units in the lot. The inspection level shall be S-1. The lot shall be unacceptable if one or more sample units fail to meet any test requirement specified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:19Z
Check the source to verify that this is the current version before use.

TABLE IV. Instructions for testing

Characteristic	Specification reference: Requirement	Specification reference: Test Method	Results reported: as Pass/Fail	Results reported: Numerically to nearest
Specific gravity at 15.5°C	3.1.2.3	4.3.1.6		0.002 unit
pH of 1:5 dilution at 25°C	3.1.2.3	4.3.1.5		0.1 pH unit
Performance	3.5	4.3.3	X	
Nonstaining of paper	3.1.2.2	4.3.2	X	
Sticky or gritty film	3.1.2.2	4.3.3.3	X	
Fraying and separation	3.1.1	4.3.3.3	X	
Weight of pad material	3.1.1	4.3.1.1, 4.3.1.4		1 g per sq. yd.
Weight of cleansing solution per container	3.1.1	4.3.1.1, 4.3.1.3		0.5 g

4.3 Test procedures. Use 6 containers from the sample unit in step 4.3.1 and one container in steps 4.3.2 and 4.3.3.

4.3.1 Extraction of cleansing solution, weight of cleansing solution per container and weight of pad material.

4.3.1.1 Weight of filled unit containers. Label each of the six unit containers and weigh each to the nearest 0.5 gram.

4.3.1.2 Extraction of cleansing solution. Remove pads from unit container and hold over a funnel inserted in a 500 ml graduated cylinder (with glass stopper). Squeeze pads to collect cleansing solution, remove funnel and stopper the graduated cylinder to prevent loss of volatile material. Repeat the procedure until at least 400 ml of cleansing solution have been collected.

4.3.1.3 Weight of cleansing solution per unit container. Allow the components of each unit container to dry to constant weight and weigh to the nearest 0.5 g. Report the average loss in weight as the average weight of cleansing solution per unit container. To satisfy the requirement of 3.3.1, the average weight of cleansing solution per container must be equal to or greater than:

$$N \times D \times D \times 0.216 \text{ grams for circular pads}$$

OR

$$N \times L \times W \times 0.275 \text{ grams for rectangular pads}$$

Where:

N = number of pads per unit container.
D = diameter of pad, to 3 significant figures, in inches.
L = length of pad, to 3 significant figures, in inches.
W = width of pad, to 3 significant figures, in inches.

4.3.1.4 Weight of pad material. Weigh 100 dry pads to the nearest 0.1 g. Divide the total weight by 100 times the average area of one side of a pad in square yards. Report the average weight of the pad material in grams per square yard.

4.3.1.5 pH of 1:5 dilution. Dilute 10 ml of cleansing solution 1:5 with cool, freshly boiled, distilled water. Measure the pH of the solution by ASTM Method E 70. Repeat the procedure and report the average of the two determinations.

4.3.1.6 Specific gravity. Transfer 380 ml of the extracted cleansing solution into a glass stoppered Earlenmeyer flask and determine the specific gravity of the cleansing solution by ASTM method D 1122. Begin the procedure at step 4.3 since the cleansing solution is homogeneous. Report the average of two readings.

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:19Z
Check the source to verify that this is the current version before use.

4.3.2 Staining of paper. Clean hands before test. Remove a pad from its container and squeeze three or four drops onto a clean sheet of white bond paper. Allow the cleansing solution to evaporate. The paper shall not be stained or discolored.

4.3.3 Performance. The performance of the pads in cleaning each of the standard test soils from the hands shall be tested as specified in 4.3.3.3.

4.3.3.1 Standard test soils. The standard test soils shall consist of:

Test soil A:	Ball point pen ink:	GG-B-60, black ink.
Test soil B:	Felt tip marker ink:	GG-M-114, black ink.
Test soil C:	Stamp pad ink:	TT-I-556, class 1, black.

4.3.3.2 Application of test soils.

4.3.3.2.1 Test soil A. Rub pen on a piece of paper to start ink flowing. Make four lines, each one inch long, on the palm of the hand.

4.3.3.2.2 Test soil B. Rub marker on the palm of the hand until a circular area of the palm, one inch in diameter, has been covered with ink.

4.3.3.2.3 Test soil C. Place some ink on a piece of paper. Touch a finger to the ink and rub the finger over the palm of the hand until a circular area of the palm, one inch in diameter, has been covered with ink.

4.3.3.3 Performance testing. Take one pad and rub the soiled area of the hand briskly for one minute, turning the pad over during use. Observe if the pad separates or unravels during use. The pad should remove all the ink soil from the ridges of the hand and most of the soil from the creases of the skin. Take a second pad and rub the soiled hand for one minute. Soil should be removed from the hand. A few traces of soil is allowed to remain in the creases of the skin. Allow the hand to dry thoroughly. The hand should not feel sticky or gritty. Press the hand firmly, palm down, on a sheet of white paper. Lift the hand slowly. The paper should not adhere even slightly to the hand. No traces of ink stain should be left on the paper. Rub the hand with a white towel. No ink stain should be left on the towel.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level B or C, as specified (see 6.2).

5.1.1 Level B. Twelve (12) unit containers (see 3.3) shall be packaged in a box conforming to PPP-B-566 or in a box normally used by industry. The box shall be closed to prevent accidental opening.

5.1.2 Level C. The unit containers (see 3.3) shall be packaged to afford adequate protection against damage during shipment from the supply source to the first receiving agency.

5.2 Packing. Packing shall be level B or C, as specified (see 6.2).

5.2.1 Level B. Six (6) packages (as specified in 5.1.1) of unit containers shall be packed in a box conforming to PPP-B-636, class domestic. The box shall be closed in accordance with Method II of the appendix to PPP-B-636.

5.2.2 Level C. Containers of pads in quantities as specified (see 6.2) shall be packed in containers to assure carrier acceptance and safe arrival at destination. Containers shall comply with the Uniform Freight or the National Motor Freight Classification, as applicable.

5.3 Marking.

5.3.1 Unit containers. In addition to any special marking required by the contract or order, unit containers shall be marked with normal commercial marking to include number of pads, name or trade name of contents, and name or trademark of manufacturer. Marking shall be clear, legible, durable and non-fading. In the absence of normal commercial marking, unit containers shall be marked in accordance with Fed. Std. No. 123 for Civil agencies or MIL-STD-129 for Military agencies, as specified (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:19Z
Check the source to verify that this is the current version before use.

5.3.2 Interior and shipping containers. In addition to any special marking required by the contract or order, interior containers and shipping containers shall be marked in accordance with Fed. Std. No. 123 for Civil agencies and MIL-STD-129 for Military activities, as specified (see 6.2).

6. NOTES

6.1 Intended use. Handcleaning pads covered by this specification are intended for use in removing ink type soils from the hands without the need for soap and water.

6.2 Ordering data. Purchasers should select the preferred options permitted herein, and include the following information in the procurement documents:

(a) Title, number, and date of this specification.
(b) Quantity required (see 5.2.1).
(c) Levels of packaging and packing required (see 5.1 and 5.2).
(d) Marking document required (see 5.3).

6.3 Lot. A lot shall consist of all pads which have been made from the same pad material lot, saturated with cleansing solution from the same batch and presented for delivery at the same time.

6.4 Batch. A batch is defined as that quantity of material which has been manufactured under the same processing conditions using the same raw material lots.

MILITARY INTERESTS:

Custodians:

Army - GL (MCA)
Navy - SA
Air Force - 84

Review Activities:

Army - EL, MD
Navy - SH, MC, CG

CIVIL AGENCY COORDINATING ACTIVITIES:

GSA - FSS

PREPARING ACTIVITY:

GSA - FSS

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See Section 2 of this specification to obtain extra copies and other documents referenced herein. Price 30 cents each.

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:19Z
Check the source to verify that this is the current version before use.