[Metric]
A-A-2894
April 04, 1996

COMMERCIAL ITEM DESCRIPTION
ARCH & CLIP BOARD FILES, COMPOSITION HARDBOARD BACK

The General Services Administration has authorized the use of this commercial item description by all federal agencies and will replace Federal Specification LLL-A-650 which is canceled.

1. Scope: This Commercial Item Description covers arch and clip board files for holding papers and serves as a writing board.

2. Classification:

Type: I. Arch Board File (With / Without Paper Perforator or Indexes & Cover).
II. Clip Board File.

3. Salient Characteristics:

3.1 Materials used shall be of any suitable material capable of meeting the performance requirements of this commercial item description.

3.2 Composition hardboard used in the manufacture of arch and clip board files shall be tempered or Standard and in accordance with normal commercial practice.

3.3 The board for the arch and clip board files shall be made of composition hardboard. The board shall be not less than 0.29 cm (0.114 inch), and not more than 0.39 cm (0.153 inch) thick. Surface smoothness shall be as defect free from visible variations in the surface plane as commercially practicable.

3.4 Type I arch board file shall be securely fastened and centered ± .317 cm (.125 inch) to the top part along the upper edge of the board. When specified, a paper perforator shall be firmly attached to the bottom part along the lower edge of the board. An alphabetical index with a cover and metal compressor shall be furnished, unless otherwise specified.

3.5 The arch paper holder shall have a base with two metal arches. Each arch shall have a fixed and movable portion spaced on 6.98 cm (2.748 inch) centered. The fixed portion of the arch shall have a usable filing height of 6.35 cm ± .248 cm (2.5 inch ± .250 inch).

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to General Services Administration, Federal Supply Service, Engineering Branch, 26 Federal Plaza, New York, NY 10278.

FSC 7520

Source: https://assist.dla.mil -- Downloaded: 2026/10-26T08:27Z
Check the source to verify that this is the current version before use.

compliance with the [illegible] answer to retain at test temperature and

3.6 The base of the arch paper holder shall be made of any material suitable for the intended purpose. A concealed spring locking device within the base, or a single-action lever type locking device, shall firmly hold the movable portion of each arch when in either an open or closed position. The bottom of the base shall have, as a integral part, an extension with a .950 cm ± .317 cm (.374 inch ± .124 inch) diameter eye or cutout, extending sufficiently beyond the upper edge of the board to permit the board to be suspended from a flat vertical surface.

3.7 The movable portion of each arch shall be J-shaped and made in compliance with paragraph 3.1. The fixed portion of each arch shall be made of steel, and shall be either solid or hollow construction. The fixed portion of the arch shall be so designed to provide a suitable stop for the movable J-shaped wire arch when in closed position. The arches shall open and close easily and be in alignment when closed.

3.8 When specified, the arch board file shall be equipped with a metal perforator having an overall height no greater than 3.17 cm (1.24 inch) above the face of the board. The perforator mechanism shall punch two .635 cm ± .079 cm holes (.249 inch holes ± .003 inch), 6.98 cm (2.74 inch) center to center. The punches shall not stick to the dies, and perforations shall be free from torn or ragged edges and entirely punched out.

3.9 Index Cards and Cover. Type I boards shall be furnished with index cards and or cover when specified in the ordering data.

3.9.1 The index cards shall consist of at least 20 manila cards of graduated length, lettered, and arranged to form an alphabetical index along the right-hand margin of the file. The index cards shall be perforated so as to pass readily over any portion of the arch board.

3.9.2 The cover shall be made of .508 mm (.020 inch) minimum thickness pressboard capable of meeting the performance requirements of this (CID). Unless otherwise specified, the cover shall not be wider than the width of the board, and not more than 1.27 cm (.499 inch). The cover for size 228.6 mm x 368.3 mm (9 inches x 14.5 inches) board shall not be less than 279.4 mm (11 inches) long, and for size 228.6 mm x 431.8 mm (9 inches x 17 inches) board, not less than 330.2 mm (13 inches) long.

3.10 Type II Clip Board. The board for the clip boards shall have a metal spring clip securely attached and centered ± 3.175 mm (.125 inch) along the upper part of the board.

3.11 Metal Spring Clip. The clamp of the clip shall not be less than 139.7 mm (5.5 inches) wide, and shall be open a minimum of 25.4 mm (1 inch). The clip shall be capable of holding securely any number of sheets of paper from one sheet to full capacity (one inch).

3.11.1 The spring, base and clamp shall be firmly held in place by a rivet or an appropriate pin. The clamp shall be fabricated with a concavity having an eye or cutout 9.5 mm ± 3.175 mm (.374 inch ± .125 inch) diameter. The clamp shall not flex when pressure is exerted to open the clip. The base of the clip shall have, as an integral part, an extension with a centered eye or cutout having a 9.5 mm ± 3.175 mm (.374 inch ± .125 inch) diameter. This extension shall extend sufficiently beyond the upper edge of the board to permit board to be suspended from a flat vertical surface. The exposed surfaces of the clip shall be smooth, and all corners and edges shall be rounded and smooth.

3.12 Board Dimensions. The dimensions for Type I Arch Board Files, and Type II Clip Board Files shall be as specified in Table I. A plus/minus tolerance of 3.175 mm (.125 inch) will be permitted in the overall length and width of the boards.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:27Z
Check the source to verify that this is the current version before use.

TABLE 1.
BOARD DIMENSIONS

Type I -Sizes	Type II - Sizes
228.6 mm x 431.8 mm (9 x 17 inches)	228.6 mm x 317.5 mm (9 x 12.5 inches) 228.6 mm x 393.7 mm (9 x 15.5 inches) 228.6 mm x 431.8 mm (9 x 17 inches)

3.13 Finish. All metal components shall be non corrosive with a shiny metallic finish, except for the pivot nail in type II files which may be made from hardened aluminum. The contractor shall provide certification of conformance upon request by the government.

3.14 The manufacturer's name or trademark shall be exhibited on the arch or clip board. Placement of these permanent markings shall be at the option of the manufacturer, provided they are prominently displayed.

3.15 Workmanship. Rivets, if used, shall be set in accordance with normal commercial practice, including but not limited to exhibiting a well formed, firm, flush seating. The arch and clip boards shall be free from defects or imperfections of manufacture which may affect their durability, appearance, serviceability or which may present a hazard to the user.

4. Regulatory Requirements:

4.1 The offerer/contractor is encouraged to use recovered materials to the maximum extent practicable in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

5. Quality Assurance Requirements:

5.1 General Quality Statement. The product provided shall conform to the producer's own drawings, specifications, standards, and quality assurance practices and be the same product offered for sale in the commercial market. The government reserves the right to require proof of such conformance prior to first delivery and therefore as may be otherwise provided for under the provisions of the contract.

5.2 Examinations & Testing.

5.2.1 Suppliers are encouraged to use quality control (QC) techniques that exhibit control over their processes (e.g. (Statistical Process Control) SPC Techniques) as defined in American National Standards Institute (ANSI) Z1.1, Z1.2 and Z1.3 / American Society for Quality Control (ASQC) B.1, B.2 and B.3 that systematically reduce excess variations. If used, objective evidence shall be available that demonstrates overall measurement adequacy techniques and controls. These techniques shall ensure quality levels equal to, or greater than, those cited in applicable technical document or, herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:27Z
Check the source to verify that this is the current version before use.

5.2.2 End item inspection / testing may be used by the offerer or the Government representative, as a means to determine the effectiveness of the in process quality controls. While in process controls shall not be substituted for end item performance testing they may be used for visual and dimensional sampling.

5.2.3 For those characteristics for which there are no such controls, or for end item performance test, lot by lot sampling for inspection / test shall be required. The sample unit for this item shall be one board. Sampling shall be in accordance with the American National Standards Institute (ANSI) / American Society for Quality Control (ASQC) Z1.4, Sampling Procedures and Tables for Inspection by Attributes.

5.2.4 An inspection lot shall consist of all like items submitted for inspection at one time. The inspection level for visual and dimensional shall testing shall be S-2 with an AQL of 4.0 percent defective. The supplier must provide objective evidence (tests and inspection records) that the presented material meets the requirements of the sampling plan as indicated above.

6. Packaging:

6.1 Preservation, packing, and marking shall be specified in the contract or order.

7. Notes:

7.1 Source of Documents. Issues of the following documents, in effect on the date of invitation for bids or request for proposal form a part of this document to the extent specified herein.

7.1.1 Federal Acquisition Regulation (FAR) may be obtained from the Superintendent of Documents, Government Printing Office, Washington, DC 20402.

7.1.2 Application for copies of (ANSI) Z1.1, Z1.2, Z1.3 and (ASQC) B.1, B.2 and B.3 may be obtained from the American Society for Quality Control. PO Box 3005, 611 E. Wisconsin Avenue, Milwaukee, WI 53201-4606.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:27Z
Check the source to verify that this is the current version before use.

7.2 National Stock Number Listing (NSN). The following is a list of Nsn's assigned which correspond to this CID. The list may not be indicative of all possible nsn's associated with the CID.

Arch Board File

7520-00-191-1075
7520-00-240-5498

Clip Board File

7520-00-240-5503
7520-00-254-4610
7520-00-281-5918

MILITARY INTERESTS:

NONE: DoD has no registered interest in revisions and amendments to this Commercial Item Description until further notice.

Preparing Activity:

GSA-FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:27Z
Check the source to verify that this is the current version before use.