INCH-POUND

A-A-52079A
June 30, 1993
SUPERSEDING
A-A-52079
September 10, 1990

COMMERCIAL ITEM DESCRIPTION

MANTLE, ILLUMINATING (GASOLINE LANTERN)

The General Services Administration has authorized the use of this commercial item description in preference to MIL-M-43576.

1. CLASSIFICATION

1.1 Classification. This commercial item description covers one type of mantle for fuel burning lanterns.

2. SALIENT CHARACTERISTICS

2.1 Design. The mantle shall be a commercial, knitted, soft-type. When the mantle is laid flat its dimensions shall approximate 2.87 inches long by 2.25 inches wide with a tolerance of ± 0.25 inches.

2.2 Mantle. The mantle shall be made from a chemically treated seamless knitted rayon tubing. The closed end of the mantle shall be formed by gathering or pleating the tube and sewing with chemically treated cotton thread. The resulting bag shall be turned so that the end is on the inside. The top section of the mantle shall be treated with a chemical solution or material selection to provide hardness and increase the strength and abrasion resistance of this section of the mantle after ignition. Approximately half of this treated band shall be turned in, to form a double thickness. A draw-string shall be threaded around and through the top or head hardened section of the mantle for fastening the mantle to the mantle holder of the lantern.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be used in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5017, by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 6260

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:05Z
Check the source to verify that this is the current version before use.

2.2.1 Seamless knitted tubing. The seamless knitted tubing shall be knit from 150 denier, 42 filament, bright rayon yarn (or equal) using a duplex weave.

2.2.2 Instructions. Mantle installation instructions shall be included with each unit pack.

3. QUALITY ASSURANCE

3.1 Certification. The contractor shall certify, and maintain substantiating evidence, that the product offered meets the salient characteristics and requirements of this Commercial Item Description, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices, and is the same as the product provided as a bid sample. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

3.2 Bid samples. Ten mantles shall be submitted for bid sample testing.

3.2.1 Bid sample performance test. Two mantles shall be installed and prepared in a commercial lantern according to mantle manufacturers instructions prior to lantern operation. The lantern shall then be lit per the manufacturers instructions. The lantern shall be operated for 30 minutes, turned off, and allowed to cool for 30 minutes. This operation shall be repeated five times. The other mantles shall be installed and ignited (in pairs of two) in the same manner except they will be ignited only one time. All mantles shall be examined for broken threads and holes. The first set of mantles will be tested for light output. The light output shall be a minimum of 150 candle power.

3.3 Metric product. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within specified tolerances using conversion tables contained in the latest revision of Federal Standard No. 376, and all other requirements of this Commercial Item Description are met. If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request should be made to the contracting officer to determine if the product is acceptable. The contracting officer has the option of accepting or rejecting the product.

3.4 Regulatory requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practicable.

4. PACKAGING

4.1 Packaging. Each mantle shall be unit packed in a paper envelope or plastic bag and the envelope or bag shall be sealed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:05Z
Check the source to verify that this is the current version before use.

4.2 Packing. Six mantles, packaged as specified in 4.1, shall then be packed in an intermediate paperboard box. One thousand seven hundred twenty-eight mantles, or 288 intermediate paperboard boxes shall then be packed in a snug-fitting fiberboard shipping container conforming to style RSC, type CF, class domestic, grade 275 of PPP-B-636. Inside dimensions of each shipping container shall approximate 26 inches in length, 13 inches in width, and 9-3/4 inches in depth.

4.3 Palletization. When specified (see 5.2), shipping containers shall be palletized in accordance with load type Ia of MIL-STD-147. Each prepared load shall be bonded with straps in accordance with bonding means C and D or film bonding means F or G. The pallet pattern shall be number 3 in accordance with the appendix of MIL-STD-147.

4.4 Marking. In addition to any special marking required by the contract or purchase order, unit packs, intermediate packs, shipping containers and palletized unit loads shall be marked in accordance with MIL-STD-129.

5. NOTES

5.1 Intended use. The mantle is intended for use with a single or double mantle fuel burning lantern.

5.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this document.
b. When palletization is required (see 4.3).

5.3 Sources of documents.

5.3.1 Source of government documents. Copies of military and federal documents are available from:

Standardization Documents Order Desk
Building 4D
700 Robbins Avenue
Philadelphia, PA 19111-5094

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:05Z
Check the source to verify that this is the current version before use.

MILITARY INTERESTS:

Custodians

Army - GL
Air Force - 99

Review Activities

Air Force - 82
DLA - GS

User Activities

Army - ME
Navy - CG, MC

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - FSS

PREPARING ACTIVITY:

Army - GL

Project 6260-1063

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:05Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	A-A-52079A	1993 June 30

3. DOCUMENT TITLE

MANTLE, ILLUMINATING (GASOLINE LANTERN)

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code) (1) Commercial	(2) AUTOVON/DSN
U.S. Army Natick RD&E Center	508-651-4531	256-4531
c. ADDRESS (Include Zip Code) Commander, U.S. Army Natick RD&E Center ATTN: SATNC-UXT Natick, MA 01760-5017	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

DD Form 1426, OCT 89 NATICK OPI ITIT 01 Previous editions are obsolete 198/29

Source: https://assist.dla.mil -- Downloaded: 20240520T09:05Z
Check the source to verify that this is the current version before use.