INCH-POUND

MIL-DTL-17/202A
09 May 2019
SUPERSEDING
MIL-C-17/202
w/AMENDMENT 2
16 October 2008

DETAIL SPECIFICATION SHEET

CABLES, RADIO FREQUENCY, FLEXIBLE, TWINAXIAL, DOUBLE SHIELD, DATA BUS, 77 OHMS

This specification is approved for use by all Departments and Agencies of the department of Defense.

The requirements for acquiring the cable described herein shall consist of this specification sheet and MIL-DTL-17.




FIGURE 1. Configuration for Part or Identifying Number (PIN) M17/202-00001.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T16:31Z
Check the source to verify that this is the current version before use.

TABLE I. Description.

Componenets	Construction
Inner conductors 1/	M17/202-00001
	AWG. 24 19 strands AWG 36 silver-coated, high strength copper alloy 2/
Dielectrics	Radiation cross-linked modified ETFE, one light blue, one white. Permitivity: 2.7 nominal. O.D.: .048 ±.002 inch each. 3/
Fillers	Radiation crosslinked modified ETFE
Braids	Inner braid: AWG 38 tin-coated copper. O.D. .114 ±.006 inch. Outer braid: AWG 38 tin-coated copper (optimized coverage). O.D. .131 ±.006 inch. 4/
Jacket	Radiation cross-linked Modified ETFE, white. O.D.: .147 ±.007 inch.

1/ Lay length shall be 1.00 ±.25 inch.
2/ High strength copper alloy in accordance with SAE-AS22759/35.
3/ Radiation crosslinked modified ETFE copolymer in accordance with SAE-AS22759/35.
4/ Minimum coverage of 90% in accordance with NEMA-WC27500.

ENGINEERING INFORMATION:

Continuous working voltage: 600 V rms, maximum, at sea level.

Operating frequency: 10 MHz, maximum.

Velocity of propagation: 61 percent, nominal.

Operating temperature range: -65°C to +150°C.

Inner conductor properties:

DC resistance (maximum, at 20°C): 28.4 ohms/100 feet.

Elongation: 6% minimum.

Tensile strength: 22.4 pounds minimum.

Jacket properties:

Elongation: 50% minimum.

Tensile strength: 5k lbf/inch^2, minimum.

Engineering note: Cables shall be suitable for use in MIL-STD-1553 data bus systems for use as main bus or stub cable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T16:31Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions, configuration and description: See figure 1 and table I.

Environmental and mechanical:

Visual and mechanical examination:

Diameter: Applicable.

Out-of-roundness: Applicable.

Eccentricity: 10 percent, maximum.

Adhesion of conductors: Dielectrics shall be free stripping, using conventional stripping tools, without breaking of conductor strands and without bunching of the dielectric.

Electrical and mechanical:

Continuity: Applicable.

Spark test: 1,000 V rms, minimum.

Voltage withstanding: 1,000 V rms, +10%, -0%.

Insulation resistance: 5,000 megohms minimum per 1,000 feet.

Corona extinction voltage: Not applicable.

Characteristic impedance: 77 ±5 ohms at 1 MHz.

Surface transfer impedance: In accordance with SAE AS85485;
10 milliohms/meter maximum at 1 MHz.

RF transmission loss (attenuation): 1.4 dB/100 feet maximum at 1 MHz.

Standing wave ratio (return loss): Not applicable.

Capacitance: 30.0 pF per foot, maximum at 1 MHz.

Capacitance stability: Not applicable.

Capacitance unbalance: 5% maximum.

Transmission unbalance: Not applicable.

Inductance: Applicable

Mechanically induced noise: Not applicable.
Time delay: Not applicable.
Aging stability: Not applicable.
Stress crack resistance: Not applicable.
Outer conductor integrity: Not applicable.

Cold bend: -65ºC (6 inch mandrel). Jacket shall pass spark test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T16:31Z
Check the source to verify that this is the current version before use.

Dimensional stability: Not applicable.
Contamination: Not applicable.
Bendability: Not applicable.

Flammability: Cable shall be tested in accordance with the flammability procedure of SAE-AS22759/35 and shall meet the requirements specified in MIL-DTL 17.

Flame propagation: Not applicable.
Acid gas generation: Not applicable.
Halogen: Not applicable.

Fluid immersion: Cable shall be tested in accordance with SAE-AS22759/35 (using a 6 inch diameter mandrel) There shall be no cracking of the jackets or evidence of breakdown. The increase in diameter shall be 5% maximum.

Smoke index: Not applicable.
Toxicity index: Not applicable.
Durometer hardness: Not applicable.
Weathering: Not applicable.
Abrasion resistance: Not applicable.
Tear strength: Not applicable.
Heat distortion: Not applicable.

Impulse dielectric: Shall be in accordance with SAE-AS22759/35; 8.0 kilovolts (peak), 100 percent test.

Physicals: Applicable

Air oven accelerated aging: Shall be in accordance with SAE-AS22759/35.
(.5 inch mandrel, .375 pound load)

Hot-oil immersion accelerated aging: Not applicable.

Tensile strength and elongation: Applicable

Air oven : Applicable

Hot-oil immersion : Applicable

Inductance: Applicable

Weight: 26.2 pounds/1,000 feet maximum.

Marking: Applicable.

Workmanship: Applicable.

PIN: M17/202-00001.

Supersession: This specification shall supersede Air Force drawing 8421527 when a QPL source becomes available.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T16:31Z
Check the source to verify that this is the current version before use.

TABLE II. Qualification and Group A, B, and C Table.

Group	Qualification inspection	Requirement paragraph	Test paragraph	Qual- # of Specimens	Conf - # of Specimens	Conformance inspection
I	In-process inspection:		4.5	Entire sample		
	Continuity	3.7.1	4.8.2	Entire sample		
	Spark test	3.7.2	4.8.3	Entire sample		
	Voltage withstanding	3.7.3	4.8.4	Entire sample		
	Insulation resistance	3.7.4	4.8.5	Entire sample		
	Visual and mechanical inspection	3.6	4.8.1	Entire sample	Per Table VIII	A
	Diameter measurements.	3.6.1	4.8.1.1	Entire sample	Per Table VIII	A
	Out-of-roundness	3.6.2	4.8.1.2	Entire sample	Per Table VIII	A
	Eccentricity of inner conductor	3.6.3	4.8.1.3	2	Per Table VIII	A
	Adhesion of conductors	See this Specification	See this Specification	4	Per Table VIII	A
	Marking	3.8	4.8.1	Entire sample	Per Table VIII	A
	Workmanship	3.10	4.8.1	Entire sample	Per Table VIII	A
II	Corona extinction voltage	N/A				
	Characteristic impedance	3.7.6	4.8.7	1	Per Table VIII	A
	Surface transfer impedance	See this Specification sheet	See this Specification sheet	1		
	RF transmission loss (attenuation)	3.7.7	4.8.8	2	Per Table VIII	A
	Standing wave ratio (return loss)	N/A				
	Capacitance	3.7.9	4.8.10	1	Per Table VIII	B
	Capacitance stability	N/A				
	Capacitance unbalance	3.7.11	4.8.12	1	Per Table VIII	B
	Transmission unbalance	N/A				
	Inductance	3.7.36	4.8.38	1	Per Table VIII	B
	Mechanically induced noise voltage	N/A				
	Time delay	N/A				
	Aging stability	N/A				
	Stress crack resistance	N/A				

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T16:31Z
Check the source to verify that this is the current version before use.

TABLE II. Qualification and Group A, B, and C Table - Continued.

Group	Qualification inspection	Requirement paragraph	Test paragraph	Qual- # of Specimens	Conf - # of Specimens	Conformance inspection
II	Outer conductor integrity	N/A				
	Cold bend	3.7.18	4.8.19	3	Per Table VIII	B
	Dimensional stability	N/A				
	Contamination	N/A				
	Bendability	N/A				
	Flammability	See this Specification sheet	See this Specification sheet	1	Per Table VIII	C
	Flame propagation	N/A				
	Acid gas generation	N/A				
	Halogen content	N/A				
	Immersion tests	See this Specification sheet	See this Specification sheet	1		
	Smoke index	N/A				
	Toxicity Index	N/A				
	Durometer hardness	N/A				
	Weathering	N/A				
	Abrasion resistance	N/A				
	Tear strength	N/A				
	Heat distortion	N/A				
	Impulse dielectric	See this Specification sheet	See this Specification sheet	1		
	Physicals (aged)	See this Specification sheet	See this Specification sheet	1	Per Table VIII	C
	Tensile strength and elongation	3.7.35	4.8.37	1	Per Table VIII	C
	Weight	3.9	4.8.24	1	Per Table VIII	B

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T16:31Z
Check the source to verify that this is the current version before use.

Changes from previous issue. The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous issue.

Referenced documents. In addition to MIL-DTL-17, this document references the following:

MIL-STD-1553 NEMA-WC27500 SAE-AS22759/35 SAE AS85485

CONCLUDING MATERIAL

Custodians:
Army – CR
Navy – EC
Air Force – 85
DLA – CC

Review activities:
Army – AT, CR4, MI
Navy – AS, MC, OS, SH
Air Force – 19

Preparing activity:
DLA – CC

(Project 6145-2018-061)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T16:31Z
Check the source to verify that this is the current version before use.