MILITARY SPECIFICATION SHEET

CABLES, RADIO FREQUENCY, FLEXIBLE, COAXIAL, 185 OHMS,
M17/208-00001

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-C-17.




FIGURE 1. Configuration.

TABLE I. Description.

Components	Construction details
Inner conductor	Solid, copper-covered, steel wire. Diameter: .007 inch ±.0010.
Dielectric core	Type A-3: Air-spaced polyethylene. A braid of 24 polyethylene filament threads, .020 inch approximate diameter each, with 2 picks/inch approximate, under an extruded tube. Overall diameter: .285 inch ±.010. Alternate Type A-3: Air-spaced polyethylene: A braid of 8 polyethylene filament threads, .035 inch approximate diameter each, with 2 picks/inch approximate, under an extruded tube. Overall diameter: .285 inch ±.010.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T16:32Z
Check the source to verify that this is the current version before use.

TABLE I. Description - Continued.

Outer conductor	Single braid of AWG#34, bare, copper wire. Diameter: .340 inch maximum. Coverage: 91.1%, nominal Carriers: 24 Ends: 8 Picks/inch: 7.0 ±10%
Barrier tape	A .001 inch thick polyester tape faced with a .002 inch thick layer of aluminum. The tape will be applied with a 50% lap, minimum. Aluminum face toward the outer conductor. Diameter: .350 inch, maximum.
Jacket	Cross-linked polyolefin. Diameter: .405 inch ±.010.

ENGINEERING INFORMATION:

Continuous working voltage: 1,000 V rms, maximum.

Operating frequency: 1 GHz, maximum.

Velocity of propagation: 88 percent, nominal.

Power ratings: See figure 2.

Operating temperature range: -40° to +80°C, maximum.

Inner conductor properties:

DC resistance (maximum at +20°C): 54.4 ohms per 100 feet.

Elongation: 2 percent, minimum.

Tensile strength: 110 klbf/inch/inch, minimum.

Engineering notes: This cable is useful in low capacitance, medium low temperature applications. (See connector series 'N', 'C', and 'SC' per MIL-C-39012). Use this cable in new designs in-lieu-of MIL-C-17/47 cables.

The US Government preferred system of measurement is the metric SI system. However, since this item was originally designed using inch-pound units of measurement, in the event of conflict between the metric and inch-pound, the inch-pound units shall take precedence.

REQUIREMENTS:

Dimensions, configuration, and descriptions: See figure 1 and table I.

Environmental and mechanical:

Visual and mechanical examination: Applicable.

Out-of-roundness: Not applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T16:32Z
Check the source to verify that this is the current version before use.

Eccentricity: 10 percent, maximum.

Adhesion of conductors: Not applicable.

Aging stability: +98° ±2°C.

Cold bend: -40° ±2°C.

Stress crack resistance: Not applicable.

Dimensional stability: Not applicable.

Contamination: Not applicable.

Flame propagation: Applicable.

Acid gas generation: 2.0 percent, maximum.

Halogen content: 0.2 percent, maximum.

Immersion test:

  Tensile strength, percent of unaged minimum: 50.

  Elongation, percent of unaged minimum: 50.

Smoke index: 25 maximum.

Toxicity index: 5 maximum.

Durometer hardness: (Type A) 80 minimum.

Weathering: Applicable.

Abrasion resistance: 75 cycles, minimum (jacket only).

Tear strength: 35 pounds per inch minimum.

Heat distortion: 30 percent maximum distortion.

Physical tests on unaged jacket:

  Tensile strength: 1,300 psi. minimum.

  Elongation: 160 percent minimum.

Physical tests on aged jacket:

  Air oven:

    Tensile strength, percent minimum: 60.

    Elongation, percent minimum: 60.

Hot oil immersion:

  Tensile strength, percent minimum: 50.

  Elongation, percent minimum: 50.

Tensile strength and elongation: 1,300 psi, 160 percent minimum.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T16:32Z
Check the source to verify that this is the current version before use.

Weight: 8.9 pounds per 100 feet maximum.

Electrical:

Spark test: 5,000 V rms, minimum.

Voltage withstanding: 5,000 V rms, minimum.

Insulation resistance: Not applicable.

Corona extinction voltage: Not applicable.

Characteristic impedance: 185 ohms ±10.

Attenuation: 8.5 dB per 100 feet, maximum at .4 GHz.

Structural return loss: Not applicable.

Capacitance: 7.2 pF per foot, maximum.

Capacitance stability: ±5 percent.

Capacitance unbalance: Not applicable.

Transmission unbalance: Not applicable.

Mechanically induced noise: Not applicable.

Time delay: Not applicable.

Part or Identifying Number (PIN): M17/208-00001.

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 85

Review activities:
Army - AR, AT, ME, MI
Navy - AS, MC, OS, SH
Air Force - 11, 19, 80, 99
DLA - ES, IS

Preparing activity:
Navy - EC

Agent:
DLA - ES

(Project 6145-2040-02)

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T16:32Z
Check the source to verify that this is the current version before use.




FIGURE 2. Power rating at 25°C sea level.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T16:32Z
Check the source to verify that this is the current version before use.