JJ-N-180F
AMENDMENT-1
May 22, 1973

FEDERAL SPECIFICATION

NET, LAUNDRY (NYLON)

This amendment, which forms a part of Federal Specification JJ-N-180F, dated June 27, 1972, was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

PAGE 4

3.2, end of paragraph. Add "When thread breaks, run-offs or skip stitching occur during sewing, the stitching shall be repaired by restarting the stitching a minimum of 2-inches back of the defective stitching 1/. Thread breaks, run-offs or two or more consecutive skipped stitches noted during inspection of the item (in-process or end item) shall be repaired by overstitching both ends of the defective stitching. The stitching shall start a minimum of 2-inches in back of the defective area, continue over the defective area, and continue a minimum of 2-inches beyond the defective area on to the existing stitching. Loose or excessively tight stitching shall be repaired by removing the defective stitching, without damaging the materials, and restitching in the required manner 1/.

1/ When making the above repairs, the ends of the stitching are not required to be backstitched."

3.2.1, end of paragraph. Add "The first end of stitches of the second row shall be overstitched at least 2-inches."

PAGE 5

3.2.2, end of paragraph. Add "The ends of the stitches not caught in other seams or stitches shall be folded back 1/2 to 5/8 inch and bartacked parallel to the row of stitches. The bartacks shall be 1/2 ± 1/8 inch long.

or

The ends of stitching chain shall be stitched back into the seam by means of the appropriate mechanical device."

PAGE 7

Table II, Construction. Under the "Top" defect, add "When the first end of the stitches of the second row is not overstitched - Major defect. When the first end of stitches of the second row is overstitched less than 2-inches - Minor defect."

FSC 3510

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:56Z
Check the source to verify that this is the current version before use.

Table II, under the "Bottom and sides" defect. Add "When the ends of the stitches not caught in other seams or stitches are not folded back nor bartacked or ends of stitching chain not stitched back into the seam - Major defect." "Bartack not of the specified dimensions - Minor defect."

Table II, under new defect "Stitching". Add "Thread breaks, run-off or skip stitching not repaired - Major defect." "Thread breaks, run-offs or two or more skipped stitches repaired by overstitching less than 2-inches - Minor defect." "Loose or excessively tight stitching not repaired as specified - Minor defect."

Custodians:

Army - GL
Navy - YD
Air Force - 84

Review activity:

Navy - MC

Preparing activity:

Army - GL

Civil Agency Interest:

GSA-FSS
HEW
VA

Project No. 3510-0239

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:56Z
Check the source to verify that this is the current version before use.