INCH-POUND


MIL-C-85049/24A
30 November 1990
SUPERSEDING
MIL-C-85049/24
16 January 1980
MS3188B
10 May 1982

MILITARY SPECIFICATION SHEET


CONNECTOR ACCESSORIES, ELECTRICAL, BACKSHELL, NONENVIRONMENTAL, 90°, SHIELD TERMINATION, CATEGORY 3A (FOR MIL-C-5015 CRIMP, MIL-C-26482 SERIES 2, MIL-C-81703 SERIES 3, AND MIL-C-83723 SERIES III CONNECTORS)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-C-85049.



STYLE 1



STYLE 2

AMSC N/A FSC 5935

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:11Z
Check the source to verify that this is the current version before use.

TABLE I. Dimensions.

Dash No.	Fits Shell of Connector				Clamp Size	A (see note 6) Wire Bundle Accommodation Range		Style	B ±.125	C Ref	D Dia Max
	MIL-C-81703 Ser 3	MIL-C-26482 Ser 2	MIL-C-5015 Crimp	MIL-C-83723 Ser III		Min	Max				
1	3	X	X	X	4	.125	.250	1	1.800	1.027	.669
2					6	.250	.437	2	1.320	1.027	.669
3	X	8	8S	8	4	.125	.250	1	1.200	1.027	.617
4	X	10	10S, 10SL	10	4	.125	.312	1	1.920	1.027	.734
5	X				6	.250	.375	1	1.320	1.027	.734
6	7	12	12,12S	12	4	.125	.312	1	1.940	1.027	.858
7					6	.250	.437	1	1.940	1.027	.858
8					10	.350	.500	1	1.335	1.027	.858
9	12	14	14,14S	14	6	.250	.437	1	2.010	1.027	.984
10					10	.350	.575	1	1.655	1.027	.984

Dash No.	E ±.125	V Thread Class 2A	F Max	G Dia Max	H Max
1	.636	.625-24 UNEF	1.18	-	1.57
2	1.386	.750-20 UNEF	2.02	.858	2.41
3	.541	.625-24 UNEF	1.09	-	1.48
4	.636	.625-24 UNEF	1.18	-	1.57
5	.636	.750-20 UNEF	1.27	-	1.66
6	.641	.625-24 UNEF	1.18	-	1.57
7	.641	.750-20 UNEF	1.28	-	1.67
8	.641	1.000-20 UNEF	1.37	-	1.76
9	.741	.750-20 UNEF	1.38	-	1.77
10	.741	1.000-20 UNEF	1.47	-	1.86

Source: https://assist.dla.mil -- Downloaded: 202610-23T10:11Z
Check the source to verify that this is the current version before use.

TABLE I. Dimensions (continued).

Dash No.	Fits Shell of Connector				Clamp Size	A (see note 6) Wire Bundle Accommodation Range		Style	B ±.125	C Ref	D Dia Max
	MIL-C-81703 Ser 3	MIL-C-26482 Ser 2	MIL-C-5015 Crimp	MIL-C-83723 Ser III		Min	Max				
11	19	16	16,16S	16	6	.250	.437	1	2.100	1.027	1.112
12					12	.500	.700	1	1.745	1.059	1.112
13	27	18	18	18	10	.350	.625	1	2.270	1.027	1.218
14					16	.625	.779	1	1.920	1.156	1.218
15	37	20	20	20	10	.350	.625	1	2.270	1.027	1.345
16					16	.625	.904	1	1.920	1.156	1.345
17		22	22	22	12	.500	.750	1	2.380	1.059	1.468
18					20	.875	1.029	1	2.025	1.375	1.468
19		24	24	24	12	.500	.750	1	2.380	1.059	1.593
20					20	.875	1.144	1	2.025	1.375	1.593

Dash No.	E ±.125	V Thread Class 2A	F Max	G Dia Max	H Max
11	.926	.750-20 UNEF	1.59	-	1.98
12	.926	1.1875-18 UNEF	1.77	-	2.15
13	1.016	1.000-20 UNEF	1.80	-	2.19
14	1.016	1.4375-18 UNEF	1.97	-	2.36
15	1.016	1.000-20 UNEF	1.80	-	2.19
16	1.016	1.4375-18 UNEF	1.97	-	2.36
17	1.166	1.1875-18 UNEF	2.11	-	2.50
18	1.166	1.750-10 UNS	2.29	-	2.68
19	1.166	1.1875-18 UNEF	2.11	-	2.50
20	1.166	1.750-18 UNS	2.29	-	2.68

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:11Z
Check the source to verify that this is the current version before use.

TABLE I. Dimensions (continued).

Dash No.	Fits Shell of Connector				Clamp Size	A (see note 6) Wire Bundle Accommodation Range		Style	B ±.125	C Ref	D Dia Max
	MIL-C-81703 Ser 3	MIL-C-26482 Ser 2	MIL-C-5015 Crimp	MIL-C-83723 Ser III		Min	Max				
21			28		16	.625	.937	1	2.550	1.156	1.969
22					24	1.000	1.375	1	2.195	1.500	1.969
23			32		16	.625	.937	1	2.800	1.156	2.219
24					20	.875	1.250	1	2.800	1.375	2.219
25					28	1.250	1.625	1	2.445	1.781	2.219
26			36		16	.625	.937	1	2.770	1.156	2.469
27					24	1.000	1.375	1	2.770	1.500	2.469
28					32	1.437	1.840	1	2.415	1.830	2.469
29			40		16	.625	.937	1	2.770	1.156	2.719
30					24	1.000	1.375	1	2.770	1.500	2.719

Dash No.	E ±.125	V Thread Class 2A	F Max	G Dia Max	H Max
21	1.266	1.4375-18 UNEF	2.33	-	2.88
22	1.266	2.000-18 UNS	2.51	-	3.06
23	1.616	1.4375-18 UNEF	2.81	-	3.36
24	1.616	1.750-18 UNS	2.81	-	3.36
25	1.616	2.250-16 UN	3.07	-	3.62
26	1.816	1.4375-18 UNEF	3.13	-	3.68
27	1.816	2.000-18 UNS	3.13	-	3.68
28	1.816	2.500-18 UN	3.39	-	3.94
29	2.566	1.4375-18 UNEF	3.88	-	4.43
30	2.566	2.000-18 UNS	3.88	-	4.43

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:11Z
Check the source to verify that this is the current version before use.

TABLE I. Dimensions (continued).

Dash No.	Fits Shell of Connector: MIL-C-81703 Ser 3	MIL-C-26482 Ser 2	MIL-C-5015 Crimp	MIL-C-83723 Ser III	Clamp Size	A (see note 6) Wire Bundle Accommodation Range Min	A (see note 6) Wire Bundle Accommodation Range Max	Style	B ±.125	C Ref	D Dia Max
31			40		32	1.437	1.875	1	2.415	1.830	2.719
32					16	.625	.937	1	2.770	1.156	2.969
33			44		24	1.000	1.375	1	2.770	1.500	2.969
34					32	1.437	1.875	1	2.415	1.830	2.969
35					16	.625	.937	1	2.770	1.156	3.219
36			48		24	1.000	1.375	1	2.770	1.500	3.219
37					32	1.437	1.875	1	2.415	1.830	3.219
38	61				12	.500	.750	1	2.380	1.059	1.653
39					20	.875	1.184	1	2.025	1.375	1.653
40	19	16	16,16S	16	10	.350	.625	1	2.100	1.027	1.112

Dash No.	E ±.125	V Thread Class 2A	F Max	G Dia Max	H Max
31	2.566	2.500-16 UN	4.14	-	4.69
32	2.566	1.437-18 UNEF	3.88	-	4.43
33	2.566	2.000-18 UNS	3.88	-	4.43
34	2.566	2.500-16 UN	4.14	-	4.69
35	2.566	1.4375-18 UNEF	3.88	-	4.43
36	2.566	2.000-18 UNS	3.88	-	4.43
37	2.566	2.500-16 UN	4.14	-	4.69
38	1.166	1.1875-18 UNEF	2.11	-	2.50
39	1.166	1.750-18 UNS	2.29	-	2.68
40	.926	1.000-20 UNEF	1.66	-	2.05

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:11Z
Check the source to verify that this is the current version before use.

TABLE I. Dimensions (continued).

Dash No.	Fits Shell of Connector				Clamp Size	A (see note 6) Wire Bundle Accommodation Range		Style	B ±.125	C Ref	D Dia Max
	MIL-C-81703 Ser 3	MIL-C-26482 Ser 2	MIL-C-5015 Crimp	MIL-C-83723 Ser III		Min	Max				
41	27	18	18	18	4	.125	.312	1	2.270	1.027	1.218
42					6	.250	.437	1	2.270	1.027	1.218
43	37	20	20	20	6	.250	.437	1	2.270	1.027	1.345
44		22	22	22	4	.125	.312	1	2.380	1.027	1.468
45					6	.250	.437	1	2.380	1.027	1.468
46		24	24	24	10	.350	.625	1	2.380	1.027	1.593
47			36		12	.500	.750	1	2.770	1.059	2.469
48			40		12	.500	.750	1	2.770	1.059	2.719
49		10	10S, 10SL	10	6	.250	.437	2	1.940	1.027	.734
50	12	14	14,14S	14	12	.500	.750	2	2.270	1.059	.984

Dash No.	E ±.125	V Thread Class 2A	F Max	G Dia Max	H Max
41	1.016	.625-24 UNEF	1.80	-	2.19
42	1.016	.750-20 UNEF	1.80	-	2.19
43	1.016	.750-20 UNEF	1.80	-	2.19
44	1.166	.625-24 UNEF	2.11	-	2.50
45	1.166	.750-20 UNEF	2.11	-	2.50
46	1.166	1.000-20 UNEF	2.11	-	2.50
47	1.816	1.1875-18 UNEF	3.13	-	3.68
48	1.816	1.1875-18 UNEF	3.88	-	4.43
49	1.381	.750-20 UNEF	2.03	.858	2.42
50	1.766	1.1875-18 UNEF	2.61	1.218	3.00

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:11Z
Check the source to verify that this is the current version before use.

TABLE I. Dimensions (continued).

Dash No.	Fits Shell of Connector				Clamp Size	A (see note 6) Wire Bundle Accommodation Range		Style	B ±.125	C Ref	D Dia Max
	MIL-C-81703 Ser 3	MIL-C-26482 Ser 2	MIL-C-5015 Crimp	MIL-C-83723 Ser III		Min	Max				
51	19	16	16,16S	16	16	.625	.937	2	2.380	1.156	1.112
52	27	18	18	18	12	.500	.750	1	2.270	1.059	1.218
53	61				16	.625	.937	1	2.025	1.156	1.863
54	37	20	20	20	12	.500	.750	1	2.270	1.059	1.345
55					20	.875	1.250	2	2.550	1.375	1.345
56		22	22	22	10	.350	.625	1	2.380	1.027	1.468
57					16	.625	.937	1	2.380	1.156	1.468
58					20	.875	1.250	2	2.550	1.375	1.468
59		24	24	24	16	.625	.937	1	2.380	1.156	1.593
60			28		12	.500	.750	1	2.550	1.059	1.969

Dash No.	E ±.125	V Thread Class 2A	F Max	G Dia Max	H Max
51	1.916	1.4375-18 UNEF	2.87	1.468	3.26
52	1.016	1.1875-18 UNEF	1.86	-	2.25
53	1.166	1.4375-18 UNEF	2.14	-	2.53
54	1.016	1.1875-18 UNEF	1.86	-	2.25
55	2.016	1.750-18 UNS	3.14	1.969	3.53
56	1.166	1.000-20 UNEF	2.11	-	2.50
57	1.166	1.4375-18 UNEF	2.12	-	2.51
58	2.016	1.750-18 UNS	3.14	1.969	3.53
59	1.166	1.4375-18 UNEF	2.14	--	2.53
60	1.266	1.1875-18 UNEF	2.33	--	2.88

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:11Z
Check the source to verify that this is the current version before use.

TABLE I. Dimensions (continued).

Dash No.	Fits Shell of Connector: MIL-C-81703 Ser 3	MIL-C-26482 Ser 2	MIL-C-5015 Crimp	MIL-C-83723 Ser III	Clamp Size	A (see note 6) Wire Bundle Accommodation Range Min	A (see note 6) Wire Bundle Accommodation Range Max	Style	B ±.125	C Ref	D Dia Max
61			28		20	.875	1.250	1	2.550	1.375	1.969
62			32		24	1.000	1.375	1	2.800	1.500	2.219
63			36		20	.875	1.250	1	2.770	1.375	2.469
64					28	1.250	1.625	1	2.770	1.781	2.469
65			40		20	.875	1.250	1	2.770	1.375	2.719
66					28	1.250	1.625	1	2.770	1.781	2.719
67			44		20	.875	1.250	1	2.770	1.375	2.969
68					28	1.250	1.625	1	2.770	1.781	2.969
69			48		20	.875	1.250	1	2.770	1.375	3.219
70					28	1.250	1.625	1	2.770	1.781	3.219

Dash No.	E ±.125	V Thread Class 2A	F Max	G Dia Max	H Max
61	1.266	1.750-18 UNS	2.39	-	2.94
62	1.616	2.000-18 UNS	2.86	-	3.41
63	1.816	1.750-18 UNS	3.13	-	3.68
64	1.816	2.250-16 UN	3.27	-	3.82
65	2.566	1.750-18 UNS	3.88	-	4.43
66	2.566	2.250-16 UN	4.02	-	4.57
67	2.566	1.750-18 UNS	3.88	-	4.43
68	2.566	2.250-16 UN	4.02	-	4.57
69	2.566	1.750-18 UNS	3.88	-	4.43
70	2.566	2.250-16 UN	4.02	-	4.57

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:11Z
Check the source to verify that this is the current version before use.

TABLE I. Dimensions (continued).

Dash No.	Fits Shell of Connector				Clamp Size	A (see note 6) Wire Bundle Accommodation Range		Style	B ±.125	C Ref	D Dia Max
	MIL-C-81703 Ser 3	MIL-C-26482 Ser 2	MIL-C-5015 Crimp	MIL-C-83723 Ser III		Min	Max				
71	7	12	12,12S	12	10	.350	.625	2	2.100	1.027	.858
72	27	18	18	18	16	.625	.937	2	2.380	1.156	1.218
73		24	24	24	20	.875	1.250	2	2.550	1.375	1.593
74	12	14	14,14S	14	4	.125	.312	1	2.010	1.027	.984
75	19	16	16,16S	16	4	.125	.312	1	2.100	1.027	1.112

Dash No.	E ±.125	V Thread Class 2A	F Max	G Dia Max	H Max
71	1.686	1.000-20 UNEF	2.42	1.112	2.81
72	1.925	1.4375-18 UNEF	2.88	1.468	3.27
73	2.026	1.750-18 UNS	3.15	1.969	3.54
74	.741	.625-24 UNEF	1.31	-	1.70
75	.926	.625-24 UNEF	1.59	-	1.98

Source: https://assist.dla.mil -- Downloaded: 202610-23T10:11Z
Check the source to verify that this is the current version before use.

INCH	mm	INCH	mm	INCH	mm	INCH	mm
0.005	0.13	1.1875	30.16	1.770	44.96	2.510	63.75
0.010	0.25	1.200	30.48	1.781	45.24	2.550	64.77
0.020	0.51	1.218	30.94	1.800	45.72	2.566	65.18
0.125	3.18	1.250	31.75	1.816	46.13	2.610	66.29
0.250	6.35	1.266	32.16	1.840	46.74	2.680	68.07
0.312	7.92	1.270	32.26	1.860	47.24	2.719	69.06
0.350	8.89	1.280	32.51	1.916	48.67	2.770	70.36
0.375	9.53	1.310	33.27	1.920	48.77	2.800	71.12
0.437	11.10	1.320	33.53	1.925	48.89	2.810	71.37
0.500	12.70	1.335	33.91	1.940	49.28	2.860	72.64
0.541	13.74	1.345	34.16	1.969	50.01	2.870	72.90
0.575	14.60	1.370	34.80	1.970	50.04	2.880	73.15
0.617	15.67	1.375	34.93	1.980	50.29	2.940	74.67
0.625	15.88	1.380	35.05	2.000	50.80	2.969	75.41
0.636	16.15	1.381	35.08	2.010	51.05	3.000	76.20
0.641	16.28	1.386	35.20	2.016	51.21	3.060	77.72
0.669	16.99	1.437	36.50	2.025	51.43	3.070	77.98
0.734	18.64	1.4375	36.51	2.026	51.46	3.130	79.50
0.741	18.82	1.468	37.29	2.030	51.56	3.140	79.76
0.750	19.05	1.470	37.34	2.050	52.07	3.150	80.01
0.858	21.79	1.480	37.59	2.100	53.34	3.219	81.76
0.875	22.22	1.500	38.10	2.110	53.59	3.250	82.55
0.904	22.96	1.570	39.88	2.120	53.85	3.260	82.80
0.926	23.52	1.590	40.39	2.140	54.36	3.270	83.06
0.937	23.80	1.593	40.46	2.150	54.61	3.390	86.11
0.984	24.99	1.616	41.05	2.190	55.62	3.410	86.61
1.000	25.40	1.625	41.28	2.195	55.75	3.530	89.66
1.016	25.81	1.640	41.66	2.219	56.36	3.540	89.91
1.027	26.09	1.653	41.99	2.250	57.15	3.620	91.94
1.029	26.14	1.655	42.04	2.270	57.66	3.680	93.47
1.059	26.90	1.660	42.16	2.290	58.17	3.820	97.03
1.090	27.69	1.686	42.82	2.360	59.94	3.880	98.55
1.112	28.24	1.690	42.92	2.410	61.21	3.940	100.08
1.144	29.06	1.700	43.18	2.415	61.34	4.020	102.11
1.156	29.36	1.745	44.32	2.420	61.47	4.140	105.16
1.166	29.62	1.750	44.45	2.445	62.10	4.430	112.52
1.180	29.97	1.760	44.70	2.469	62.71	4.570	116.07
1.184	30.07	1.766	44.86	2.500	63.50	4.690	119.12

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:11Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

1. Design and construction:

   a. Dimensions and configuration: See figure 1 and table I.

   b. Interface dimensions shall conform to MIL-C-85049 figure 4.

   c. Figure 1 consists of a coupling nut and follower. The coupling nut shall be captivated to and free to rotate on the follower.

2. Material and finish:

   a. Accessory components shall be as shown in table I.

   b. Clamp assembly screws - Corrosion resistant steel in accordance with MIL-C-85049, passivated per QQ-P-35.

3. Qualification: See MIL-C-85049, category 3A. Information pertaining to qualification of products may be obtained from the Commanding Officer, Naval Avionics Center, Attention: Code B/444, 6000 East 21st Street, Indianapolis, IN 46219-2189.


4. Applications:

   a. These accessories are for shield termination applications.

   b. Style 2 applies when the cable diameter exceeds the "E" diameter of the interface dimensions defined in MIL-C-85049 figure 4.

   c. For assembly instructions see figure 2 of MIL-C-85049/25.

5. Part Number: See example below:



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:11Z
Check the source to verify that this is the current version before use.

6. Supersession data:

MS3188C * * M85049/24 - * *

Dash Number

Finish

Old	New
A	W
C	W

TABLE II. Material and finish.

Component	Material	Finish
Body	Aluminum alloy in accordance with MIL-C-85049	1/ N, 2/ W
Body	Corrosion resistant steel in accordance with MIL-C-85049	B, S

1/ Not for Navy use. Restricted to Air Force Space applications only.
2/ W finish is not for use in space application.

NOTES:

1. Dimensions are in inches.
2. Metric equivalents shall be based upon 1.00 inch = 25.4 mm and shall be in accordance with ASTM E380, paragraph 4.5, Method A and ASTM E29, rounding-off method.
3. Unless otherwise specified, tolerances shall be: .XX = ±.01: .XXX = ±.005: angular, X° = ±1°; X°XX' = ±0°30'.
4. Dimensions apply after plating.
5. Loosely assembled is defined as the MIL-C-85049/42 clamp tightened to the MIL-C-85049/24 connector accessory body a minimum of two full thread lengths.
6. "Wire bundle accommodation range" dimension is defined as the envelope area for the wire bundle. This dimension is not meant to define the clamp hardware limits.
7. O-ring is not supplied with style 2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:11Z
Check the source to verify that this is the current version before use.

Revision letters are not used to denote changes due to the extensiveness of the changes.

Custodians:
Army - CR
Navy - AS
Air Force - 85

Review activities:
Army - AR, MI
Navy - EC
Air Force - 11, 99
DLA - ES

Preparing activity:
Navy - AS
(Project No. 5935-3729-10)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:11Z
Check the source to verify that this is the current version before use.