INCH-POUND

MIL-DTL-83723/84F
w/AMENDMENT 1
6 February 2018
SUPERSEDING
MIL-DTL-83723/84F
1 October 2009

DETAIL SPECIFICATION SHEET

CONNECTORS, ELECTRICAL, CIRCULAR, ENVIRONMENT RESISTING, RECEPTACLE, JAM NUT MOUNT, THREADED COUPLING, CRIMP SOCKET CONTACT, SERIES III, CLASSES A, G, K, M, N, R, S, T, W AND Z

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-83723.




FIGURE 1. Classes A, G, K, M, R, T, W and Z.

AMSC N/A

FSC 5935

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:22Z
Check the source to verify that this is the current version before use.




FIGURE 1. Classes A, G, K, M, R, T, W and Z - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:22Z
Check the source to verify that this is the current version before use.

Inches	mm	Inches	mm	Inches	mm	Inches	mm	Inches	mm
.005	0.08	.198	4.27	.705	17.19	1.090	27.69	1.380	35.05
.008	0.20	.204	5.18	.715	18.16	1.096	27.84	1.382	35.10
.010	0.25	.281	7.14	.721	18.31	1.104	28.04	1.385	35.18
.015	0.38	.290	7.37	.726	18.44	1.105	28.07	1.391	35.33
.018	0.46	.329	8.36	.730	18.54	1.107	28.12	1.437	36.50
.019	0.48	.340	8.64	.754	19.15	1.108	28.14	1.464	37.19
.020	0.51	.351	8.92	.760	19.30	1.110	28.19	1.470	37.34
.022	0.56	.388	9.86	.761	19.33	1.112	28.24	1.479	37.57
.025	0.64	.394	10.01	.769	19.53	1.127	28.63	1.482	37.64
.032	0.81	.413	10.49	.772	19.61	1.132	28.75	1.483	37.67
.035	0.89	.418	10.62	.774	19.66	1.135	28.83	1.485	37.72
.042	1.07	.424	10.77	.781	19.84	1.161	29.49	1.510	38.35
.046	1.17	.433	11.00	.796	20.22	1.171	29.74	1.516	38.51
.048	1.22	.443	11.25	.806	20.47	1.187	30.15	1.562	39.67
.054	1.37	.461	11.71	.860	21.84	1.192	30.28	1.589	40.36
.061	1.55	.479	12.17	.875	22.22	1.214	30.84	1.595	40.51
.062	1.57	.481	12.22	.881	22.37	1.220	30.99	1.604	40.74
.063	1.60	.482	12.24	.896	22.76	1.229	31.22	1.607	40.82
.065	1.65	.490	12.45	.901	22.89	1.233	31.32	1.609	40.87
.069	1.75	.515	13.08	.902	22.91	1.235	31.37	1.610	40.89
.071	1.80	.518	13.16	.908	23.06	1.237	31.38	1.635	41.53
.076	1.93	.530	13.46	.917	23.29	1.240	31.42	1.641	41.68
.078	1.98	.535	13.59	.936	23.77	1.252	31.80	1.732	43.99
.084	2.13	.558	14.17	.947	24.05	1.257	31.93	1.735	44.07
.089	2.26	.562	14.27	.949	24.10	1.260	32.00	1.766	44.86
.090	2.29	.580	14.70	.965	24.51	1.291	32.79	1.795	45.59
.092	2.34	.590	14.99	.971	24.66	1.295	32.89	1.920	48.77
.093	2.36	.596	15.14	.980	24.89	1.296	32.92	1.923	48.84
.097	2.46	.605	15.37	.984	24.99	1.312	33.32	1.954	49.63
.098	2.49	.622	15.80	.985	25.02	1.320	33.53	2.045	51.94
.100	2.54	.627	15.93	.987	25.07	1.339	34.01	2.047	51.99
.101	2.57	.635	16.13	.991	25.17	1.340	34.04	2.048	52.02
.106	2.69	.636	16.15	1.002	25.45	1.345	34.16	2.078	52.78
.112	2.84	.646	16.41	1.007	25.58	1.349	34.26	2.079	52.81
.125	3.18	.648	16.46	1.010	25.65	1.354	34.39	2.152	54.66
.130	3.30	.670	17.02	1.046	26.57	1.357	34.47	2.182	55.42
.137	3.48	.685	17.40	1.047	26.59	1.358	34.49		
.138	3.51	.696	17.68	1.062	26.97	1.360	34.54		
.144	3.66	.700	17.78	1.073	27.25	1.362	34.59		
.160	4.06	.701	17.81	1.078	27.38	1.377	34.98		

FIGURE 1. Classes A, G, K, M, R, T, W and Z - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:22Z
Check the source to verify that this is the current version before use.

NOTES:

1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Unless otherwise specified, tolerances are ± .005 (0.13 mm) for three place decimals and ± .01 (0.25 mm) for two place decimals and ±1° for all angles.
4. Coupling indicator line shall be color coded red.
5. Rear accessory interchangeability dimensions shall be in accordance with MIL-DTL-83723.
6. Shell size 8 will not mate with MIL-DTL-26500 connectors.
7. Phantomed configuration optional.
8. See table I for contact cavities requiring this dimension.
9. The centerline of indicated projection must be located on vertical centerline ± 2°.

FIGURE 1. Classes A, G, K, M, R, T, W and Z - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:22Z
Check the source to verify that this is the current version before use.




FIGURE 2. Classes N and S.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:22Z
Check the source to verify that this is the current version before use.




FIGURE 2. Classes N and S - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:22Z
Check the source to verify that this is the current version before use.

Inches	mm	Inches	mm	Inches	mm	Inches	mm	Inches	mm
.005	0.08	.198	4.27	.705	17.19	1.090	27.69	1.380	35.05
.008	0.20	.204	5.18	.715	18.16	1.096	27.84	1.382	35.10
.010	0.25	.281	7.14	.721	18.31	1.104	28.04	1.385	35.18
.015	0.38	.290	7.37	.726	18.44	1.105	28.07	1.391	35.33
.018	0.46	.329	8.36	.730	18.54	1.107	28.12	1.437	36.50
.019	0.48	.340	8.64	.754	19.15	1.108	28.14	1.464	37.19
.020	0.51	.351	8.92	.760	19.30	1.110	28.19	1.470	37.34
.022	0.56	.388	9.86	.761	19.33	1.112	28.24	1.479	37.57
.025	0.64	.394	10.01	.769	19.53	1.127	28.63	1.482	37.64
.032	0.81	.413	10.49	.772	19.61	1.132	28.75	1.483	37.67
.035	0.89	.418	10.62	.774	19.66	1.135	28.83	1.485	37.72
.042	1.07	.424	10.77	.781	19.84	1.161	29.49	1.510	38.35
.046	1.17	.433	11.00	.796	20.22	1.171	29.74	1.516	38.51
.048	1.22	.443	11.25	.806	20.47	1.187	30.15	1.562	39.67
.054	1.37	.461	11.71	.860	21.84	1.192	30.28	1.589	40.36
.061	1.55	.479	12.17	.875	22.22	1.214	30.84	1.595	40.51
.062	1.57	.481	12.22	.881	22.37	1.220	30.99	1.604	40.74
.063	1.60	.482	12.24	.896	22.76	1.229	31.22	1.607	40.82
.065	1.65	.490	12.45	.901	22.89	1.233	31.32	1.609	40.87
.069	1.75	.515	13.08	.902	22.91	1.235	31.37	1.610	40.89
.071	1.80	.518	13.16	.908	23.06	1.237	31.38	1.635	41.53
.076	1.93	.530	13.46	.917	23.29	1.240	31.42	1.641	41.68
.078	1.98	.535	13.59	.936	23.77	1.252	31.80	1.732	43.99
.084	2.13	.558	14.17	.947	24.05	1.257	31.93	1.735	44.07
.089	2.26	.562	14.27	.949	24.10	1.260	32.00	1.766	44.86
.090	2.29	.580	14.70	.965	24.51	1.291	32.79	1.795	45.59
.092	2.34	.590	14.99	.971	24.66	1.295	32.89	1.920	48.77
.093	2.36	.596	15.14	.980	24.89	1.296	32.92	1.923	48.84
.097	2.46	.605	15.37	.984	24.99	1.312	33.32	1.954	49.63
.098	2.49	.622	15.80	.985	25.02	1.320	33.53	2.045	51.94
.100	2.54	.627	15.93	.987	25.07	1.339	34.01	2.047	51.99
.101	2.57	.635	16.13	.991	25.17	1.340	34.04	2.048	52.02
.106	2.69	.636	16.15	1.002	25.45	1.345	34.16	2.078	52.78
.112	2.84	.646	16.41	1.007	25.58	1.349	34.26	2.079	52.81
.125	3.18	.648	16.46	1.010	25.65	1.354	34.39	2.152	54.66
.130	3.30	.670	17.02	1.046	26.57	1.357	34.47	2.182	55.42
.137	3.48	.685	17.40	1.047	26.59	1.358	34.49		
.138	3.51	.696	17.68	1.062	26.97	1.360	34.54		
.144	3.66	.700	17.78	1.073	27.25	1.362	34.59		
.160	4.06	.701	17.81	1.078	27.38	1.377	34.98		

FIGURE 2. Classes N and S - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:22Z
Check the source to verify that this is the current version before use.

NOTES:

1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Unless otherwise specified, tolerances are ± .005 (0.13 mm) for three place decimals and ± .01 (0.25 mm) for two place decimals and ±1° for all angles.
4. Coupling indicator line shall be color coded red.
5. Rear accessory interchangeability dimensions shall be in accordance with MIL-DTL-83723.
6. Shell size 8 will not mate with MIL-DTL-26500 connectors.
7. Phantomed configuration optional.
8. See table I for contact cavities requiring this dimension.
9. The centerline of indicated projection must be located on vertical centerline ± 2°.

FIGURE 2. Classes N and S - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:22Z
Check the source to verify that this is the current version before use.

Shell size	A thread	B	D	F
8	.562-24 UNEF-2A	.394	.290	.562
10	.688-24 UNEF-2A	.515	.388	.696
12	.875-20 UNEF-2A	.685	.558	.875
14	.938-20 UNEF-2A	.754	.627	.936
16	1.062-18 UNEF-2A	.881	.772	1.062
18	1.188-18 UNEF-2A	.987	.860	1.187
20	1.312-18 UNEF-2A	1.112	.985	1.312
22	1.438-18 UNEF-2A	1.237	1.110	1.437
24	1.562-18 UNEF-2A	1.362	1.235	1.562

Shell size	C	G	M thread
8	.418 .413	.137 .097	.625-25 UN-2A
10	.535 .530		.750-20 UNEF-2A
12	.705 .700		.938-20 UNEF-2A
14	.774 .769		1.000-20 UNEF-2A
16	.901 .896		1.125-18 UNEF-2A
18	1.007 1.002		1.250-18 UNEF-2A
20	1.132 1.127		1.375-18 UNEF-2A
22	1.257 1.252	.148 .128	1.500-18 UNEF-2A
24	1.382 1.377	.168 .128	1.625-18 UNEF-2A

FIGURE 3. Dimensions and configurations.


Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:22Z
Check the source to verify that this is the current version before use.

Shell size	N	P	R	T
8	.670	.980 .949	1.078 1.047	.076 .071
10	.796	1.104 1.073	1.192 1.161	.089 .084
12	.984	1.291 1.260	1.380 1.349	
14	1.046	1.391 1.360	1.561 1.485	
16	1.171	1.516 1.485	1.641 1.610	
18	1.296	1.641 1.610	1.766 1.735	
20	1.482	1.766 1.735	1.954 1.923	
22	1.609	1.954 1.923	2.078 2.047	
24	1.732	2.079 2.084	2.182 2.152	

Shell size	S +.005 / -.000	W	CC min	DD
8	.490	12	.443	.991
10	.636	15	.443	1.107
12	.806	21	.482	1.295
14	.875	24	.596	1.357
16	1.002	30	.622	1.482
18	1.108	33	.646	1.607
20	1.233	36	.648	1.795
22	1.358	39	.701	1.920
24	1.483	42	.726	2.045

FIGURE 3. Dimensions and configurations - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:22Z
Check the source to verify that this is the current version before use.



Shell size	EE	FF	JJ
8	.605	.635	.596 .590
10	.730	.760	.721 .715
12	.917	.947	.908 .902
14	.980	1.010	.971 .965
16	1.105	1.135	1.096 1.090
18	1.229	1.260	1.220 1.214
20	1.354	1.385	1.345 1.339
22	1.479	1.510	1.470 1.464
24	1.604	1.635	1.595 1.589

FIGURE 3. Dimensions and configurations - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:22Z
Check the source to verify that this is the current version before use.

NOTES:

1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Unless otherwise specified, tolerances are ± .005 (0.13 mm) for three place decimals and ± .01 (0.25 mm) for two place decimals and ±1° for all angles.
4. Coupling indicator line shall be color coded red.
5. Rear accessory interchangeability dimensions shall be in accordance with MIL-DTL-83723.
6. Shell size 8 will not mate with MIL-DTL-26500 connectors.
7. Phantomed configuration optional.
8. See table I for contact cavities requiring this dimension.
9. The centerline of indicated projection must be located on vertical centerline ± 2°.

FIGURE 3. Dimensions and configurations - Continued.

REQUIREMENTS:

Dimensions and configurations: See figures 1 and 3 for classes A, G, K, M, R, T, W and Z. See figures 2 and 3 for classes N and S.

This connector mates with MIL-DTL-83723/87, MIL-DTL-83723/92, MIL-DTL-83723/96 and MIL-DTL-83723/98.


Insert arrangements and polarizing positions: See MIL-STD-1554 and table I.

TABLE I. Insert arrangements requiring reduced diameter for lead-in chamfers on outer row of contact cavities as indicated.

Shell size	Insert arrangements	Contact cavities
8	03, 98	1, 2, 3
10	06	1, 2, 3, 4, 5, 6

O-ring: See MIL-DTL-83723.

Part or Identifying Number (PIN) example:



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:22Z
Check the source to verify that this is the current version before use.

Amendment notations. The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Referenced documents. In addition to MIL-DTL-83723, this document references the following:

MIL-STD-1554
MIL-DTL-26500
MIL-DTL-83723/87
MIL-DTL-83723/92
MIL-DTL-83723/96
MIL-DTL-83723/98
MS3186

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - AS
Air Force - 85
DLA - CC

Review activities:
Army - AR, MI
Navy - EC
Air Force - 19, 99

Preparing activity:
DLA - CC

(Project 5935-2018-018)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:22Z
Check the source to verify that this is the current version before use.