MILITARY SPECIFICATION

FUZE, GRENADE: M219E1 (SIMULATED DEFECTIVE) (INERT)

LOADING, ASSEMBLING, AND PACKING

1. SCOPE

1.1 This specification covers the loading, assembling, and packing for one type of fuze designated as Fuze, Grenade: M219E1 (Simulated Defective) (Inert).

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-2550	-	Ammunition and Special Weapons, General Specification for
MIL-I-45607	-	Inspection Equipment, Supply and Maintenance of

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105)

FSC: 1330

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:40Z
Check the source to verify that this is the current version before use.

MIL-STD-109	-	Quality Assurance Terms and Definitions
MIL-STD-1168	-	Lot Numbering of Ammunition
MIL-STD-1169	-	Packaging, Packing and Marking for Shipment of Inert Ammunition Components
MIL-STD-1235	-	Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes

DRAWINGS

U.S. ARMY

D9258715	-	Fuze, Grenade: M219E1 (Simulated Defective)

PUBLICATIONS

U.S. ARMY

ET-9258715	-	Equipment Tabulation

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer.)

2.2 Other publications.-The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on the date of invitation for bids or request for proposal shall apply.

CODE OF FEDERAL REGULATIONS

Title 49	-	Transportation, Parts 0-190

(The Code of Federal Regulations is available from the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402. Orders should specify, "49 CFR 0-190 [latest revision].")

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:40Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Material.-Materials shall be in accordance with the applicable drawings and specifications.

3.2 Parts.-The parts shall comply with all requirements specified on Drawing 9258715, all associated drawings and with all requirements specified in applicable specifications.

3.3 Radiographic Examination of Fuze, Grenade: M219E1 (Simulated Defective) (Inert).-Assembly aids such as pins or other devices, adhesive, or foreign matter of any type shall not be detectable in a radiograph of the Fuze, Grenade: M219E1 (Simulated Defective) when each fuze is tested as specified in 4.2.3.1.

3.4 Transportation Vibration.-The Fuze, Grenade: M219E1 (Simulated Defective) (Inert) shall show no change of its appropriate condition (safe, partially armed, or armed) when tested as specified in 4.2.3.2. Fuzes subjected to this test will be radiographed prior to testing and after testing to insure compliance with this requirement. Fuzes tested in this manner and found acceptable shall be returned to the lot.

3.5 Workmanship.-All parts and assemblies shall be fabricated, loaded and assembled in a thorough, workmanlike manner. They shall be free of burrs, sharp edges, cracks, dirt, grease, rust, and other foreign matter. The cleaning method used shall not be injurious to any part, nor shall the parts be contaminated by the cleaning agents. Exterior surface coatings shall be continuous except for a few light scratches not exposing base material. All required marking and stamping shall be neat and sharply defined.

3.6 Submission of results of contractor-conducted examinations and tests.-The contractor shall forward copies of the results of any of his examinations or tests to the designated address as required by the contract.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.-Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein,

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:40Z
Check the source to verify that this is the current version before use.

unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Reference shall be made to MIL-STD-109 to define terms used herein. The provisions of MIL-A-2550 shall apply.

4.1.1 Submission of product.-At the time the completed lot of items deliverable under the contract is submitted to the Government for acceptance, the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

a. A statement that the lot complies with all the quality assurance provisions specified in this specification.
b. Drawing and specification number and date, together with identification and date of change thereto.
c. A statement that all material purchased by the contractor meets requirements, when such material is controlled by Government or commercial specifications referenced in any of the contractual documents, and that certificates of conformance are on file and available for review.
d. Number of items in the lot.
e. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.2 Inspection provisions

4.2.1 Lot formation.-The term "inspection lot" as used in this specification is defined as an essentially homogeneous collection of units of product from which a representative sample is drawn and inspected to determine conformance with applicable requirements. The sample selected shall represent only that quantity of units from which the sample was drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the inspection lot has been produced

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:40Z
Check the source to verify that this is the current version before use.

by one manufacturer, in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision and complies with the provisions for submission of product as specified in MIL-STD-105. Changes to process, specification, or drawing not affecting safety, performance, interchangeability, or storage, as determined by the Government, shall not be deemed to alter the homogeneity of an inspection lot. All material submitted for inspection in accordance with this specification shall comply with the homogeneity criteria specified herein regardless of the type of sampling procedure which is being applied to determine conformance with requirements. Lot numbering, as required, shall be in accordance with MIL-STD-1168.

4.2.2 Examination.-The examinations listed in the following subparagraphs shall be performed on inspection lots (See 4.3.1) of the components or assemblies designated in the applicable paragraph headings. Inspection for critical defects (and major defects, when so specified) shall be 100 percent. Sampling plans for major and minor defects shall be in accordance with MIL-STD-105 except that continuous sampling plans in accordance with MIL-STD-1235 may be used if approved by the Government. Instead of applying the AQL's designated herein to the groups of major and minor defects listed, the contractor may elect to apply AQL's to individual defects using an AQL of 0.40 percent for each major defect and an AQL of 0.65 percent for each minor defect. When this method is elected, it shall be applied to all of the major and minor defects listed in the applicable subparagraph of this section, except where 100 percent inspection is specified, and be documented as part of the contractor's inspection system. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.2.4.

4.2.2.1 Housing Assembly, Fully Armed (9258705)

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 0.40 Percent		
101.	Adhesive on lockweights missing	Visual	01001
102.	Detonator not fastened	Visual	01002
Minor:	None defined		

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:40Z
Check the source to verify that this is the current version before use.

4.2.2.2 Housing Assembly, One tipped lockweight (9258706)

Categories	Defects	Method of Inspection	Code No.
Critical: None defined			
Major:	AQL 0.65 Percent		
101.	Adhesive on lockweight missing	Visual	02001
102.	Detonator not fastened	Visual	02002
103.	Min. tip of lockweight	Gage	02003
Minor: None defined			

4.2.2.3 Housing Assembly, Two Adjacent Lockweights tipped (9258707)

Categories	Defects	Method of Inspection	Code No.
Critical: None defined			
Major:	AQL 0.65 Percent		
101.	Adhesive on lockweight missing	Visual	03001
102.	Detonator not fastened	Visual	03002
103.	Min tip of lockweight (2 places)	Gage	03003
Minor: None defined			

4.2.2.4 Housing Assembly, Two Opposite lockweights tipped (9258708)

Categories	Defects	Method of Inspection	Code No.
Critical: None defined			
Major:	AQL 0.65 Percent		
101.	Adhesive on lockweights missing	Visual	04001
102.	Detonator not fastened	Visual	04002
103.	Min. tip of lockweight (2 places)	Gage	04003
Minor: None defined			

4.2.2.5 Housing Assembly, All lockweights Tipped, No Rotor Movement (9258709)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:40Z
Check the source to verify that this is the current version before use.

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 0.65 Percent		
101.	Adhesive on lockweights missing	Visual	05001
102.	Detonator not fastened	Visual	05002
103.	Min tip of lockweights (four places	Gage	05003
Minor:	None defined		

4.2.2.6 Housing Assembly, All lockweights tipped, 22° Rotor Movement (9258710)

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:			
101.	Adhesive on lockweights missing (four places)	Visual	06001
102.	Detonator not fastened	Visual	06002
103.	Min tip of lockweights (four places)	Gage	06003
104.	Min rotation of detonator rotor	Gage	06004
Minor:	None defined		

4.2.2.7 Fuze, Grenade: M219E1 (Simulated Defective) (Inert) (Dwg. 9258715)

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:			
101.	Outside diameter, max. at lead cup end	Gage	07001
102.	Outside diameter, max on largest diameter	Gage	07002
103.	Outside diameter, max. of end opposite to lead cup.	Gage	07003
104.	Length of shoulder, max	Gage	07004
105.	Length max.	Gage	07005
106.	Height of dimple	Gage	07006
Minor:	None defined		

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:40Z
Check the source to verify that this is the current version before use.

4.2.3 Testing

4.2.3.1 Radiographic Inspection of Fuze, Grenade: M219E1 (Simulated Defective) Major Defect, Defect Code 08001.-Each fuze, Grenade: M219E1 (Simulated Defective) shall be subjected to this test. The test shall be performed as specified in 4.3.1. If any fuze fails to meet the requirements of paragraph 3.3, it shall be rejected and removed from the lot.

4.2.3.2 Transportation Vibration Major Defect, Defect Code 09001.-A sample of twenty-five (25) fuze assemblies shall be selected from each lot and subjected to this test. The test shall be performed as specified in 4.3.2. If one (1) or more assemblies fail to comply with the requirements of paragraph 3.4, the lot will be rejected. Samples subjected to this test shall be returned to the lot.

4.2.4 Inspection equipment.-Equipment Tabulation (ET) number 9258715 and Equipment lists (EL's) referenced theron identify the inspection equipment required to perform the examinations and tests prescribed in this section. The contractor shall design inspection equipment in accordance with the instructions in 6.3. Supply and maintenance of the equipment listed on the EL's shall be in accordance with MIL-I-45607.

4.2.4.1 Government rights to documentation.-Inspection equipment drawings and lists provided and revised in accordance with the requirements of this specification may be used by DOD activities for design, procurement, manufacture, testing, evaluation, production and receiving inspection, overhaul, shipping, storage, identification of stock, ordering and storage of replacement parts, inspection of items at overhaul, general maintenance of equipment, construction, survey, and whenever inspection equipment drawings are needed.

4.3 Test methods and procedures

4.3.1 Radiographic Inspection.-The radiographic inspection shall be conducted in a manner identical in all respects with the method in use for Fuze, Grenade M219E1. Equipment and procedures shall be satisfactory to the Contracting Officer.

4.3.2 Transportation Vibration.-The Fuze, Grenade: M219E1 (Simulated Defective) samples shall be placed in a tray and then packed in a standard, shipping carton. (Dummy fuzes may be used to fill the remainder of the tray containing the simulated defects). The carton

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:40Z
Check the source to verify that this is the current version before use.

shall then be securely fastened to the Vibration machine and tested in accordance with MIL-STD-331. Any damage to the simulated defects will be determined by X-ray examination.

5. PREPARATION FOR DELIVERY

5.1 This section is not applicable to this specification.

6. NOTES

6.1 Ordering data.-Procurement document shall specify the following:

a. Title, number and date of this specification.
b. Data cards shall be prepared for each lot in accordance with the information specified in Standard MIL-STD-1167.

6.2 Inspection code numbers.-The five-digit code numbers assigned to the inspections herein are to facilitate future data collection and analysis by the Government. These code numbers are also used to correlate the characteristics cited on Equipment Lists with the inspections listed in this specification. These code numbers shall be listed on drawings of equipment designs submitted by the contractor (see 6.3.5).

6.3 Inspection equipment.-The contractor shall design inspection equipment as required by the referenced Equipment Lists (EL) in accordance with the instructions of paragraphs 6.3.1 through 6.3.5.

6.3.1 Equipment lists.-Equipment lists indicate the availability of inspection equipment designs by showing in the "Part Number" column of the list of inspection equipment (Form SMUPA 1010) the numbers of drawings or Federal Stock numbers of existing equipment designs, or codes as indicated in paragraph 6.3.2. Design action required of the contractor is described in paragraphs 6.3.3 and 6.3.4. The contractor will be required to prepare detailed

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:40Z
Check the source to verify that this is the current version before use.

drawings in accordance with 6.3.4 for all the equipment coded as "Contractor Design" in the "Part Number" column. These contractor designs must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.5.

6.3.2 Equipment list codes.-The inspection equipment as defined in 6.3.3 and 6.3.4 will be designated in the EL by the following codes:

CD - Contractor design on controlled contractor format and/or commercial equipment.
MU - Army design, mandatory for use.

6.3.3 Army designs.-Army designs are reflected on detailed drawings which completely depict all the information necessary for the fabrication of the item of inspection equipment. The contractor need provide no design when an Army design is cited for an item of inspection equipment. Army designs fall into two basic classifications: Mandatory (designated "MU") and non-mandatory (indicated by drawings or Federal Stock Number). When an equipment list references mandatory Army Designs, the contractor shall comply with, and use these designs accordingly. the contractor may, however, in connection with non-mandatory designs, with the approval of the Government, design alternate inspection equipment to facilitate his operations. Such contractor-prepared designs (see 6.3.4) or commercial equipment selections must be approved by the Government prior to fabrication or procurement of the equipment. Designs shall be submitted for approval as specified in 6.3.5.

6.3.4 Contractor designs.-Contractor designs are designs of inspection equipment for which the Government has assigned design responsibility to the contractor. Contractor designs shall be supported by detailed drawings which depict all information necessary to completely fabricate, calibrate and operate an item of inspection equipment. This requires that the necessary views, dimensions, materials, finishes, notes and operating and calibration instructions be properly depicted in accordance with approved practices to the extent that further calculation or clarification will not be required. Unless otherwise specified, contractor designs may be developed on the format the contractor normally employs in his equipment design

Source: https://assist.dla.mil -- Downloaded: 20261O-22T20:40Z
Check the source to verify that this is the current version before use.

procedure provided such format reflects the detail and information specified above, subject to the following controls: All submitted contractor designs shall conform to Specification MIL-D-1000, Category A, Form 3. Legibility and reproducibility shall permit conventional making of clearly understandable, high-contrast reproductions. Contractors shall submit three copies of final designs as a flat set. Designs shall be submitted for approval as specified in 6.3.5.

6.3.5 Submission of contractor design.-All submitted designs shall contain a reference to the applicable 5-digit code number contained in Section 4 of this specification and the appropriate component or assembly drawing number and revision letter to which the specific design applies. Unless otherwise specified on the EL, all designs of equipment for inspection of defects classified as critical and major shall be submitted for approval to the Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-ND13. All other designs of inspection equipment shall be approved by the inspection element of the agency administering the contract. Submission shall be as directed by the contracting officer. Partial submission of inspection equipment designs is permissible and encouraged. However, the Arsenal completion date for design review will be based on the date of the final submission of designs. Picatinny Arsenal design review will be accomplished, normally, within one month after receipt.

Custodian
Army-MU

Preparing Activity:
Army-MU

Project Number: 1330-A226

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:40Z
Check the source to verify that this is the current version before use.