MILITARY SPECIFICATION

MICRODETONATOR CLIP ASSEMBLY PARTS FOR

This specification is approved for use by the U.S. Army Armament Research and Development Command and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification contains requirements not normally covered by the drawings and provides quality assurance provisions for the fabrication of parts, assembly and packing for Microdetonator Clip Assembly.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. - The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification For

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes

DRAWINGS (See 6.4)

U.S. ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND

9326705 - Microdetonator Clip Assembly

9326743 - Container for Microdetonator Clip Assembly

FSC: 1375

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn: DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:28Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Material. - Materials shall be in accordance with the applicable drawings and specifications.

3.2 Parts. - The parts shall comply with all requirements specified on Drawing (Dwg) 9326705, all associated drawings, and with all requiremnts specified in applicable specifications.

3.3 First article inspection. - This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.4 Workmanship. - All parts and assemblies shall be fabricated and finished in a thorough, workmanlike manner. They shall be free of burrs, chips, sharp edges, cracks, unblended radii, surface defects, dirt, grease, rust, corrosion products, and other foreign matter. Cleaning methods used shall not be injurious to any parts, nor shall the parts be contaminated by the cleaning agents. All marking and stamping shall be neat and sharply defined.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. - Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspections. - The following types of inspection shall be conducted on this item:

a. First Article Inspection
b. Quality Conformance Inspection

4.3 First article inspection. -

4.3.1 Submission. - The contractor shall submit a first article as designated by the Contracting Officer for evaluation in accordance with the provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:28Z
Check the source to verify that this is the current version before use.

Part Description	Drawings	Quantity
Clip, Microdetonator	9326703	25
Shunt, Microdetonator	9326704	25
Microdetonator Clip Assembly	9326705	25

4.3.2 Inspections to be performed. - See MIL-A-48078 and Table I herein.

4.3.3 Rejection. - See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:28Z
Check the source to verify that this is the current version before use.

TABLE I - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS MIL-M-63248(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
	Microdetonator Clip Assembly and components				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Clip, microdetonator (Dwg. 9326703)				
	Examination of defects	25		3.2	4.4.2.1
	Shunt, Microdetonator (Dwg. 9326704)				
	Examination of defects	25		3.2	4.4.2.2
	Microdetonator Clip Assembly (Dwg. 9326705)				
	Examination of defects	25		3.2	4.4.2.3

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T02:28Z
Check the source to verify that this is the current version before use.

4. QUALITY CONFORMANCE INSPECTION

4.4.1 Inspection lot formation. - Inspection lots shall comply with the lot formation provisions of MIL-A-48078.

4.4.2 Examination. - See MIL-A-48078.

a. Sampling Plans. - Unless otherwise specified in the Classification of Defects and Test tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:28Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-63248(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.1	Clip, Microdetonator	1 OF 1	9326703
			NEXT HIGHER ASSEMBLY 9326705

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Distance between holes		0.40%	3.2	Gage
102	Large diameter of holes (10 places)		0.40%	3.2	Gage
103	Distance from end to center of first hole		0.40%	3.2	Gage
104	Diameter of circular web (10 places)		0.40%	3.2	Gage
105	Cavity identification above flush		0.40%	3.2	Visual
Minor					
201	Width		0.65%	3.2	Gage
202	Height		0.65%	3.2	Gage
203	Total Length		0.65%	3.2	Gage
204	Diameter of hole on closed surface (10 places)		0.65%	3.2	Gage
205	Flatness of open surface		0.65%	3.2	Gage
206	Taper missing (10 places)		0.65%	3.2	Visual
207	Cavity identification missing or not in proper position		0.65%	3.2	Visual
208	Incorrect number of holes		0.65%	3.2	Visual
209	Evidence of poor workmanship		1.0%	3.4	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T02:28Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-63248(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.2	Shunt, Microdetonator	1 OF 1	9326704
			NEXT HIGHER ASSEMBLY 9326705

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined	See 4.5.1			
Major					
101	Distance between cutouts		0.40%	3.2	Gage
102	Incorrect number of holders		0.40%	3.2	Viusal
Minor					
201	Total length		0.65%	3.2	Gage
202	Evidence of poor workmanship		1.0%	3.4	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:22Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-63248(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.3	Microdetonator Clip Assembly		9326705
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Shunt above flush with clip		0.40%	3.2	Gage
102	Shunt below maximum with clip		0.40%	3.2	Gage
103	Shunt not secure in clip		0.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		1.0%	3.4	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23 02:28Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. - Testing is described in the First Article and Quality Conformance Inspection Tables.

4.4.4 Inspection equipment. - The inspection equipment required to perform the examinations and tests prescribed herein is described in the Paragraph Reference/Inspection Method column in the tables starting with Paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 5 of MIL-A-48078 and 6.3 herein.

4.5 Test methods and procedures. -

4.5.1 Dimensional control of stamped parts. - In place of the normal sampling associated with the Classification of Defects, and with the approval of the Contracting Officer, a sample of at least ten (10) parts shall be dimensionally inspected to qualify the tool used in the stamping process for use in production. In addition, a random sample of five (5) parts shall be selected from the last portion of each hour's production for dimensional inspection as a control of the tool during production.

If any defective parts are found during qualification of the tool, the tool producing the defective part shall not be used in production.

If any defective parts are found when inspection is performed for control of the tool, the tool producing the defective part shall be removed from production. Further, that portion of production since the last tool control check shall be returned to the contractor for corrective action.

All tools removed from production because of some fault, may, after reworking, be returned to production providing they pass the qualification test above. The contractor may request a change of inspection frequency providing he presents objective evidence to the Contracting Officer to substantiate the request.

5. PACKAGING

5.1 Preservation and packaging. -

5.1.1 Level B. - The microdetonator clip assembly shall be preserved and packaged in accordance with Dwg. 9326743.

5.2 Packing

5.2.1 Level B. - The microdetonator clip assembly, preserved and packaged as specified in 5.1.1, shall be packed for shipment in accordance with Dwg. 9326743.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:28Z
Check the source to verify that this is the current version before use.

5.3 Marking. - Marking of the carton shall comply with Dwg. 9326743.

5.4 Shipping. - When components from more than one lot are shipped at one time, as a carload, each lot shall be kept separate and, the division between lots clearly indicated to prevent mixing of the lots in transit.

6. NOTES

6.1 Intended use. - Not applicable.

6.2 Ordering data. - See MIL-A-48078.

6.3 Submission of inspection equipment designs for approval. - Submit equipment designs as required to Commander, ATTN: DRDAR-QAA-I, ARRADCOM, Dover, New Jersey 07801. Request letter of submittal state contractor, contract number, specification number, item nomenclature and classification of defects or test paragraph.

6.4 Drawings. - Drawings listed in Section 2 of this specification under the heading U.S. Army Armament Research and Development Command (ARRADCOM) may also include drawings prepared by, and identified as, Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal or Picatinny ARsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARRADCOM.

Custodian:
Army-AR

Preparing Activity:
Army-AR

Project Number: 1375-A-208

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:28Z
Check the source to verify that this is the current version before use.