MILITARY SPECIFICATION

SELECTOR, FUZE OPTION ASSEMBLY, TRAINING

1. SCOPE

1.1 This specification covers requirements, quality assurance provisions, and the preparation for delivery criteria for one type of selector, entitled Selector, Fuze Option Assembly Training, which is used for training personnel on the Honest John warhead.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-1168	- Lot Numbering of Ammunition.
MIL-STD-1169	- Packaging, Packing and Marking for Shipment of Inert Ammunition Components.
MIL-STD-1460	- Soldering of Electrical Connections and Printed Wiring Assemblies, Procedure For.

DRAWINGS

ORDNANCE CORPS

8813510	- Switch, Option Selector.
8822392	- Selector, Fuze Option Assembly, Training.
EL-8842318	- Equipment List.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:37Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Materials. The contractor shall furnish objective evidence (see 6.2) that the material complies with the specifications listed on the applicable drawing.

3.2 Assembly. The selector shall comply with all requirements specified on the drawing (dwg) 8822392, with all requirements specified herein, and with the requirements of all applicable specifications to the extent specified on the drawing and herein.

3.3 First article testing. Requirements for the submission of first article samples by the contractor shall be as specified in the contract (see 4.2).

3.4 Serialization. The contractor shall assign serial numbers as required by drawings. The contractor may select any number which complies with the drawing requirement. These numbers shall not be duplicated.

3.5 Setting. The switch shall operate with a torque not exceeding 20 inch-pounds. The action of the switch shall not permit stopping between detent position, it shall either return to the starting position or carry through to the opposite position. These conditions shall be met when the switch is tested as specified in 4.4.1.

3.6 Vibration. The selector shall be capable of withstanding any vibration without evidence of damage such as loose parts and shall comply with the requirements of 3.5 after being tested as specified in 4.4.2.

3.7 Soldering. All soldering shall comply with the requirements specified in MIL-STD-1460.

3.8 Workmanship.

3.8.1 Plastic and metal characteristics. All components shall be free from cracks, splits, cold flow, shrinkage, cold shuts, inclusions, porosity, or any similar characteristic.

3.8.2 Threads. Threads shall be full and undamaged for the entire minimum length or depth as required on the applicable drawing.

3.8.3 Burrs. Parts shall be free from burrs.

3.8.4 Foreign matter. Parts shall be free from chips, dirt, grease, rust, corrosion, or any embedded foreign material.

3.8.5 Cleaning. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agent.

3.8.6 Electrical. Cable assemblies and wires shall be dressed in such a manner as to prevent pinching or chafing of the wire insulation. Ends of wires shall be free from burrs, sharp edges, or points. All parts shall be free from flux, chips, dirt, grease, rust or foreign material.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:37Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 First article inspection.

4.2.1 Quantity to be submitted. When the contract requires first article inspection, the contractor shall submit 3 complete assemblies (see dwg 8822392) for first article testing to the testing facility designated in the invitation for bids or request for proposal.

4.2.2 Inspection and testing to be performed. The first article inspection sample shall be subjected to the inspections and tests specified in Table I. Tests shall be conducted in order specified in Table I.

Table I

First article inspection and tests

Inspection or Test	Dest	Non-Dest
1. Classification of characteristics (see 4.3.2.1)		X
2. Setting (see 3.5)		X
3. Vibration (see 3.6)		X

4.2.3 Inspection equipment. The inspection and testing specified in 4.2.2 shall be accomplished by using the gages and test equipment specified in 4.3.4.1.

4.2.4 Rejection. If any item fails to comply with any of the applicable requirements, the first article sample shall be rejected.

4.3 Quality conformance inspection.

4.3.1 Lot formation.

4.3.1.1 Production lot. A lot shall consist of parts and assemblies produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision. Drawing, specification and process changes not affecting

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:37Z
Check the source to verify that this is the current version before use.

safety, performance, storage, or interchangeability, as determined by the Government, shall not necessitate changing the lot interfix number. The criteria and procedures for the assignment of lot numbers shall be in accordance with MIL-STD-1168.

4.3.1.2 Inspection lot. A lot or batch and its formation, size, and presentation is described in MIL-STD-105, Section 5. Accordingly, a lot shall mean an inspection lot and a batch shall mean an inspection batch for the purpose of this specification. The manner in which each inspection lot or batch is to be presented and identified by the contractor, shall be designated or approved by the Government representative.

4.3.2 Product inspection examination. A sample shall be selected at random from each inspection lot in accordance with the applicable major or minor characteristic table (see Table II and Table III), and inspected for all characteristics in the applicable classification. Any characteristics in the sample found to be defective shall reject the inspection lot. Sequence for the inspection of characteristics in each classification need not be followed as long as all characteristic inspections are performed.

Table II
Major Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-16	all	28-29	23	52-56	31	132-156	39
17	16	30-31	24	57-62	32	157-191	40
18	17	32-34	25	63-69	33	192-244	41
19-20	18	35-36	26	70-76	34	245-334	42
21	19	37-40	27	77-86	35	335-519	43
22-23	20	41-43	28	87-97	36	520-1120	44
24-25	21	44-47	29	98-112	37	over 1120	45
26-27	22	48-51	30	113-131	38		

Table III
Minor Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-9	all	14-16	12	28-33	16	77-121	20
10	9	17-18	13	34-41	17	122-273	21
11	10	19-22	14	42-54	18	over 273	22
12-13	11	23-27	15	55-76	19		

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:37Z
Check the source to verify that this is the current version before use.

4.3.2.1 Classification of characteristics (see 3.2). Critical, major and minor characteristics are defined in MIL-STD-105. Inspection shall be conducted as follows:

4.3.2.1.1 Switch, option selector with cover plate removed (see dwg 8813510 covering a detail of dwg 8822392).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Cracked, chipped, broken or cut insulation	Visual
102.	Wire broken or damaged	Visual/Manual
103.	Soldering improper (see 3.7)	Visual/Manual
104.	Objective evidence relating to material missing or improper (see 3.1)	Visual
Minor:		
201.	Evidence of poor workmanship (see 3.8)	Visual

4.3.2.1.2 Switch, option selector (see dwg 8813510 covering a detail of dwg 8822392).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Improper positioning of switch shaft	Visual
102.	Cover plate improperly assembled	Visual
103.	Hardware loose or missing	Visual/Manual
104.	Component parts missing, loose, damaged or improperly aligned	Visual/Manual
Minor:		
201.	Improper serial number, illegible or missing	Visual
202.	Evidence of poor workmanship (see 3.8)	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:37Z
Check the source to verify that this is the current version before use.

4.3.2.1.3 Selector, fuze option assembly, training (see dwg 8822392).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Holes improperly placed	Gage
	102. Hardware loose or missing	Visual/Manual
	103. Parts loose, missing, damaged or improperly placed	Visual/Manual
Minor:		
	201. Marking misleading or unidentifiable	Visual
	202. Evidence of poor workmanship (see 3.8)	Visual

4.3.2.1.4 Preparation for delivery (see 5).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Preservation, packing, and packaging not in accordance with MIL-STD-1169	Visual
	102. Marking not in accordance with MIL-STD-1169	Visual
Minor:		
	201. Evidence of poor workmanship (see 3.8)	Visual

4.3.3 Testing. All tests shall be performed. Tests shall be performed in the order specified below:

Test	Test Classification
a. Setting	Critical
b. Vibration	Major

None of these tests are considered destructive and samples so tested may be returned to the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:37Z
Check the source to verify that this is the current version before use.

4.3.3.1 Setting. Each selector shall be tested in accordance with 4.4.1. If any item fails to comply with 3.5, the item shall be rejected and removed from the lot.

4.3.3.2 Vibration. Three samples selectors shall be selected at random from each lot and tested in accordance with 4.4.2. If any selector fails to comply with 3.6, the lot shall be rejected and removed from the lot.

4.3.4 Acceptance inspection equipment.

4.3.4.1 Major characteristics and tests. Inspection and testing shall be performed with the acceptance inspection equipment, operating instructions, and calibration instructions specified on the Equipment Lists (EL) (see EL-8842318). When either of the conditions listed below exist, the contractor shall design required equipment or specify suitable commercial equipment and obtain approval prior to use on the contract.

a. Any deviation from equipment or procedures specified on the EL is desired (see 6.3).
b. The code "CD" is listed in the "Part or Identifying Number" column on the EL (see 6.1.2).

4.3.4.2 Minor characteristics and tests. Acceptance inspection equipment for minor characteristics is not specified on ELs. The acceptance inspection equipment, operating instructions and calibration instructions used by the contractor for minor classification inspection shall be approved by the Government representative authorized by the procuring agency.

4.4 Test methods. The tolerances specified herein are absolute with no allowance for test equipment inaccuracy. The tolerances used by the manufacturer shall be equal to the absolute tolerances less the accuracy tolerances of the test equipment used.

4.4.1 Setting. Mount the switch on a rigid fixture. Measure the torque required to change positions of the switch in both clockwise and counterclockwise directions (should not exceed 20 inch-pounds). Operate the switch slowly several times, observe the action for possible "dead positions", i.e., positions on which the switch might stop other than its two normal positions.

4.4.2 Vibration. The selector shall be rigidly mounted on the vibration platform. A simple harmonic motion having an amplitude of 0.03 inch (0.06 inch max. total excursion) shall be applied, the frequency being varied uniformly between the approximate limits of 10 and 55 hertz (Hz). The entire frequency range from 10 to 55 and 10 Hz shall be transversed in approximately one minute. The motion shall be continuously applied for 15 minutes in each of the three mutually perpendicular directions. After completion of this test the selector shall be tested as specified in 4.4.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:37Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).

5.1.1 Level A. The selector shall be preserved and packaged in accordance with instructions contained in MIL-STD-1169(MU).

5.1.2 Level C. The selector shall be preserved and packaged in accordance with instructions contained in MIL-STD-1169(MU).

5.2 Packing.

5.2.1 Levels A and C. The selector shall be packed in accordance with the applicable instructions contained in MIL-STD-1169(MU).

5.3 Marking. Marking shall be in accordance with MIL-STD-1169(MU).

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

6.1.1 Procurement requirements.

a. Title, number, and date of this specification.
b. Selection of applicable level of packaging and packing required (see 5.1 and 5.2).

6.1.2 Contract data requirements (see 4.3.4.1). Data specified in 4.3.4.1 will be delivered as identified on a numbered DD Form 1664 when required on a DD Form 1423 incorporated in the contract.

6.2 Objective evidence. Records of contractor quality control and inspections which can be verified.

6.3 Acceptance inspection equipment (see 4.3.4.1). The contractor shall obtain approval from the Commander, Picatinny Arsenal, Dover, New Jersey 07801, ATTN: SARPA-QA-T.

6.4 Supersession data. This specification supersedes the requirements of Purchase Description PA-PD-1814 dated 29 July 1960 and Amendment No. 1 dated 29 July 1964.

Custodian:
Army - PA

Preparing activity:
Army - PA

Project No. 1135-A162

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:37Z
Check the source to verify that this is the current version before use.