
INCH POUND
MIL-PRF-14409/14K
11 June 2010
SUPERSEDING
MIL-PRF-14409/14J
25 July 2001

PERFORMANCE SPECIFICATION SHEET

CAPACITORS, VARIABLE (PISTON TYPE, TUBULAR TRIMMER), STYLES PC27, PC28, PC29

This specification sheet is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the capacitors described herein shall consist of this specification sheet and MIL-PRF-14409.







FIGURE 1. Dimensions and configuration.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:15Z
Check the source to verify that this is the current version before use.



STYLE PC29

Inches	mm	Inches	mm
.002	0.05	.093	2.36
.005	0.13	.120	3.05
.010	0.25	.125	3.18
.015	0.38	.145	3.68
.020	0.51	.219	5.56
.030	0.76	.245	6.22
.062	1.57	.260	6.63
.070	1.78	.281	7.14
.073	1.85	.681	17.30
.078	1.98		

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerance is ± .016 inch (0.41 mm).

FIGURE 1. Dimensions and configurations - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:15Z
Check the source to verify that this is the current version before use.

TABLE I. Capacitor characteristics.

Part or Indentifying Number (PIN)	Capacitance range		Q Min	Dimensions 1/					
	Min	Max		A	B ± .020 (0.51)	C	D	E	F
	pF	pF							
PC27J3R5	0.35	3.5	10,000						
PC28J3R5	0.35	3.5	10,000		.245 (6.22)				
PC28J050	0.5	5.0	7,500		.281 (7.14)				
PC29J3R5	0.35	3.5	10,000	.266 (6.76)	.250 (6.35)	.145 (3.68)	.047 (1.19)	.120-80 UNS-2A	.070 x .015 (1.78) (0.38)
PC29J050	0.5	5.0	7,500	.266 (6.76)	.281 (7.14)	.145 (3.68)	.047 (1.19)	.120-80 UNS-2A	.070 x .015 (1.78) (0.38)
PC29J100	0.8	10.0	7,500	.281 (7.14)	.249 (6.32)	.220 (5.59)	.062 (1.57)	.190-64 UNS-2A	.093 Min x .020 (2.36) (0.51)

1/ Metric equivalents are shown in parentheses for general information only.

REQUIREMENTS:

Dimensions and configuration: See figure 1 and table I.

DC voltage rating: 250 volts.

Construction: Alumina ceramic.

Dielectric: Air.

Capacitance range: See table I.

Insulation resistance: Not less than 10^6 megohms at room ambient temperature and not less than 10^5 megohms at +125°C.

Test condition - 250 volts ±10 percent.

Quality factor (Q): See table I (measured at frequency of 100 MHz).

Driving torque: Greater than or equal to 0.3 ounce-inches and less than or equal to 4.0 ounce-inches from -55°C through +125°C.

Thermal shock: Method 107 of MIL-STD-202, test condition A, except step 3 temperature shall be +125° ±5°C.

Immersion: Method 104 of MIL-STD-202, test condition A.

Resistance to soldering heat: Applicable to style PC28 and PC29 only.

Seal: Applicable, with seal cap on.

Qualification inspection: Qualification inspection is not required. A manufacturer that is currently listed on the QPL for at least one other MIL-PRF-14409 style may supply PC27, PC28, and PC29 parts by performing the group A and group B testing. A manufacturer that is not qualified to any MIL-PRF-14409 styles may produce these parts by performing the group A, group B, and group C testing on the product before delivery.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:15Z
Check the source to verify that this is the current version before use.

Changes from previous issue: The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Referenced documents. In addition to MIL-PRF-14409, this document references MIL-STD-202.

Custodians:
Army – CR
Navy - EC
Air Force - 85

Review activities:
Navy - AS, MC, OS
Air Force - 99

Preparing activity:
DLA - CC

(Project 5910-2010-020)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.daps.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:15Z
Check the source to verify that this is the current version before use.