NOTE: The document identifier and heading have been changed on this page to reflect that this is a performance specification. There are not other changes to this document. The document identifier on subsequent pages has not been changed, but will be changed the next time this document is revised.


MIL-PRF-14409/7B
5 October 1970
SUPERSEDING
MIL-C-14409/7A
9 June 1969


PERFORMANCE SPECIFICATION SHEET

CAPACITORS, VARIABLE (PISTON TYPE, TUBULAR TRIMMER), STYLES PC41 AND PC51


The complete requirements for procuring the capacitors described herein shall consist of this document and the latest issue of Specification MIL-PRF-14409.

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.





INCHES	MM
.005	.13
.016	.41
.020	.51
.030	.76
.032	.81
.080	2.03
.234	5.94
.250	6.35
.281	7.14
.312	7.92
.500	12.70



NOTES:
1. Dimensions are in inches.
2. Metric equivalents (to the nearest .01 mm) are given for general information only and are based upon 1 inch = 25.4 mm.
3. Unless otherwise specified, tolerance is ±.016.
4. There shall be a minimum of one and one-half turns of wire around the body. These turns shall be completely soldered to the body.
5. This style capacitor is designed for printed-circuit mounting.
6. For dimensions A, B, and T see table I.

(B) denotes changes

FSC 5910

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:13Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions: See figure and table I.

DC voltage rating: 750 volts.

Construction: Glass or quartz, see figure and table I.

Insulation resistance (IR): Method 302 of MIL-STD-202, test condition B (500 volts ± 10 percent); not less than 1, 000, 000 megohms, except characteristics J and H shall be not less than 100, 000 megohms at 125° C.

Capacitance range: See table I.

Quality factor (Q): See table I.

Temperature cycling: Method 102 of MIL-STD-202, test condition D, except the step 3 temperature shall be 125° C ± 5° C for characteristics J and H, and 150° C ± 5° C for characteristic Q.

TABLE I. Type designation and characteristics.

Type designation	Capacitance range		Dimensions 1/			Q	Dielectric material	Wire size AWG
	Min	Max	B ± .031(.79)	A (max)	T (max)			
	pf	pf						
PC41Q1R8	0.6	1.8	.250(6.35)	.312(7.92)	.181(4.60)	1,500	Quartz	24
PC41Q5R5	0.6	5.5	.438(11.13)	.562(14.27)	.186(4.72)	1,500	Quartz	22
PC41Q9R5	0.6	9.5	.875(22.23)	1.00 (25.40)	.211(5.36)	1,500	Quartz	22
PC41Q160	0.8	16.0	1.375(34.93)	1.609(40.87)	.196(4.98)	1,500	Quartz	22
PC51J5R5	0.8	5.5	.250(6.35)	.312(7.92)	.181(4.60)	1,000	Glass	24
PC51J110	0.8	11.0	.438(11.13)	.562(14.27)	.186(4.72)	900	Glass	22
PC51H160	0.8	16.0	.625(15.88)	.766(19.46)	.231(5.87)	800	Glass	22
PC51H230	0.8	23.0	.875(22.23)	1.00 (25.40)	.211(5.36)	700	Glass	22
PC51H380	0.8	38.0	1.375(34.93)	1.609(40.87)	.196(4.98)	500	Glass	22

1/ Metric equivalents (to the nearest .01 mm) are given for general information only and are based upon 1 inch = 25.4 mm. Millimeters are in parentheses.

TABLE II. Substitutability data.

Superseded type designation in MIL-C-14409/7	Substitutable type designation in MIL-C-14409/7A
PC41J4R5 and PC47J050	PC51J5R5
PC41J8R5 and PC47J100	PC51J110
PC41H120 and PC47H140	PC51H160
PC41H180 and PC47H190	PC51H230
PC41H300	PC51H380

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:13Z
Check the source to verify that this is the current version before use.

Custodians:
Army - EL
Navy - EC
Air Force - 11

Review activities:
Army -
Navy - AS, OS
Air Force -
DSA - ES

User activities:
Army -
Navy - CG, MC
Air Force -

Preparing activity:
Army - EL

(Project 5910-1011)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:13Z
Check the source to verify that this is the current version before use.