
INCH-POUND
MIL-PRF-14409/9J
6 December 2018
SUPERSEDING
MIL-PRF-14409/9H
4 December 2013


PERFORMANCE SPECIFICATION SHEET

CAPACITOR, VARIABLE (PISTON TYPE, TUBULAR TRIMMER), STYLE PC43

This specification sheet is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the products described herein shall consist of this specification sheet and MIL-PRF-14409.





SUGGESTED MOUNTING HOLES

Inches	mm
.005	0.13
.016	0.41
.020	0.51
.029	0.74
.080	2.03
.125	3.18
.234	5.94
.312	7.92
.500	12.70

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerance is ±.016 inch.
4. This style capacitor is designed for printed-circuit mounting.

FIGURE 1. Dimensions and configurations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:13Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions: See figure 1 and table I.

DC voltage rating: 1,000 volts.

Construction: Sealed glass, see figure 1 and table I.

Capacitance range: See table I.

Insulation resistance (IR): MIL-STD-202-302, test condition B (500 volts ±10 percent); not less than 1,000,000 megohms at room ambient temperature and not less than 100,000 megohms at +125°C.

Quality factor (Q): See table I.

Thermal shock: MIL-STD-202-107, test condition A, except the step 3 temperature shall be +125°C ±5°C.

Immersion: MIL-STD-202-104, test condition A.

Seal test: Applicable.

Rotational life: Capacitance change versus rotation - no reversal greater than 2 percent.

TABLE I. Capacitor characteristics.

Part or identifying number (PIN)	Capacitance range		Dimensions 1/		Q	Temperature coefficient parts/million/°C	Dielectric material
	Min	Max	B±.062 (1.157)	A±.062 (1.157)			
	pF	pF					
PC43G160	1.0	16.0	.688 (17.48)	.734 (18.64)	750	±150	Glass
PC43G360	1.0	36.0	.922 (23.42)	.969 (24.61)	550	±150	Glass
PC43G520	1.0	52.0	1.141 (28.98)	1.188 (30.18)	350	±150	Glass
PC43G750	1.0	75.0	1.375 (34.93)	1.422 (36.12)	250	±150	Glass
PC43G121	1.0	120.0	1.984 (50.39)	2.031 (51.59)	250	±150	Glass
PC43J121	1.0	120.0	1.984 (50.39)	2.031 (51.59)	250	±50	Glass

1/ Metric equivalents are given for general information only. Millimeters are in parentheses.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:13Z
Check the source to verify that this is the current version before use.

Changes from previous issue: The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Referenced documents: In addition to MIL-PRF-14409, this document also references:

MIL-STD-202-104
MIL-STD-202-107
MIL-STD-202-302

Custodians:
Army - CR
Navy - EC
Air Force – 85
DLA - CC

Preparing activity:
DLA - CC

(Project 5910-2019-006)

Review activities:
Navy - AS, MC, OS

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:13Z
Check the source to verify that this is the current version before use.