MIL-F-19579B(MC)
24 October 1972
SUPERSEDING
MIL-F-19579A(MC)
12 September 1966

MILITARY SPECIFICATION

FLAGS, ORGANIZATIONAL: STANDARDS, USMC

This specification is approved for use by all Department and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers requirements for embroidered Marine Corps standard flags.

*1.2 Classification. The Marine Corps standard flags shall be of the following types as specified (see 6.2):

Type I - Battle standard
Type II - Standard
Type III - Reserve standard
Type IV - Command standard

2. APPLICABLE DOCUMENTS

*2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of the specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

V-T-276	- Thread, Cotton.
KK-L-168	- Leather, Deerskin, Chrome-Tanned.
UU-P-268	- Paper, Kraft, Untreated, Wrapping.
UU-P-553	- Paper, Wrapping, Tissue.
CCC-C-430	- Cloth, Sheeting, Cotton, And Polyester And Cotton.
CCC-C-458	- Cloth, Flannel, Cotton.
DDD-L-20	- Label, For Clothing, Equipage And Tentage (General Use).
PPP-B-656	- Box, Fiberboard.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:15Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-C-606	- Cloth, Banner, Rayon.
MIL-F-2310	- Fringe, Ornamental, Rayon.
MIL-C-3636	- Cords and Tassel, Flag.
MIL-L-40051	- Leather, Cattlehide, For Glove Leather.

STANDARDS

FEDERAL

FED-STD-191	- Textile Test Methods.
FED-STD-751	- Stitch, Seam, And Stitching.

MILITARY

MIL-STD-105	- Sampling Procedures And Tables For Inspection By Attributes.
MIL-STD-129	- Marking For Shipment And Storage.

DRAWINGS

MARINE CORPS

71C5042A0000	- Flag Organizational Standard USMC, Location Of Colors.
71C5043A0000	- Flag Organizational Standard USMC
71C5044A0000	- Flag Organizational Standard USMCR

(Copies of specifications, standards and drawings required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

*2.2 Other publications. The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids, or request for proposal, shall apply.

UNIFORM CLASSIFICATION COMMITTEE

Uniform Freight Classification Rules

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, Illinois 60606.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:15Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

*3.1 Samples. Samples are furnished solely for guidance and information to the supplier (see 6.3). Variation from this specification may appear in the sample, in which case the specification shall govern. Unless otherwise specified (see 6.2), the contracting officer shall furnish standard samples of cloth for shade and matching colorfastness requirements.

*3.2 First article. Unless otherwise specified (see 6.2), before production is commenced, the first article consisting of the number of finished flags specified by the procuring activity (see 6.2) shall be submitted, or made available, to the contracting officer or his authorized representative for approval. The approval of the first article authorizes the commencement of production, but does not relieve the supplier of responsibility for compliance with all provisions of this specification. The first article shall be manufactured by the supplier in the same facilities to be used for the manufacture of the production items.

3.3 Materials.

*3.3.1 Basic material. The basic material for the flag shall be cloth, banner, rayon, conforming to MIL-C-606. The background cloth shall be scarlet, Cable No. 65006; the cloth for the globe of the emblem shall be silver gray, Cable No. 70151; and the cloth for the motto and bottom scroll shall be white, Cable No. 70001. The scarlet background cloth shall be 52 inches wide and the selvages shall form the top and bottom edges of the finished flag.

3.3.2 Thread

*3.3.2.1 Cotton thread. The thread for sewing the heading, the hem at the fly end, and attaching the fringe shall be cotton, mercerized, conforming to type IC2, ticket No. 8, of V-T-276. All cotton thread shall be vat dyed and the colors shall match the shade of the material being sewn, except the cotton thread used in the horizontal lines on the globe shall match the Cable No. 67197, Putty HCW, which is identified as No. 16 (see Drawing No. 71C5042A0000 for the location of colors).

*3.3.2.2 Embroidery thread. Machine embroidery thread shall be continuous filament rayon, 600 denier, 460 yards minimum average length per ounce, 2.3 pounds minimum breaking strength. The embroidery thread, when tested as specified in Section 4, Table II, shall comply with the requirements specified herein. All embroidery threads shall be vat dyed, and the colors, of which there are 15, shall match the approved standard shades (see 6.3). The following cable numbers are assigned to the various colors (see Drawing No. 71C5042A0000 for the location of colors):

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:15Z
Check the source to verify that this is the current version before use.

No. 1	Yellow HH	Cable No. 67108
No. 2	Golden Light HG	Cable No. 67107
No. 3.	Yellow HC	Cable No. 67103
No. 4	Gold HF	Cable No. 67106
No. 5	Antique White HAD	Cable No. 67139
No. 6	Steel HCY	Cable No. 67199
No. 7	Old Blue HBR	Cable No. 67167
No. 8	Silver Gray HAM	Cable No. 67137
No. 9	Toast HCU	Cable No. 67195
No. 10	Scarlet HL	Cable No. 67111
No. 11	White HA	Cable No. 67101
No. 12	Gold Brown HCT	Cable No. 67194
No. 13	Black HAN	Cable No. 67138
No. 14	Golden Yellow HD	Cable No. 67104
No. 15	Brown HAL	Cable No. 67136

*3.3.3 Lining for heading. The lining for the heading shall be cloth, flannel, cotton, conforming to type III, class 2, of CCC-C-458, bleached white; or cloth, sheeting, cotton, conforming to type I, class 1, style A of CCC-C-430.

*3.3.4 Leather. The leather tabs shall be natural colored, 5/64-to 6/64-inch-thick leather conforming to type I, class 1, of KK-L-168, except the crocking requirement shall not apply, or type II, class 2, of MIL-L-40051.

*3.3.5 Fringe. The fringe shall be 2-1/2-inch length conforming to class 2 of MIL-F-2310. The color shall be golden yellow matching Cable No. 65001.

3.3.6 Cord and tassel. Each flag shall be furnished with a cord and tassel conforming to class 8 of MIL-C-3636, except that colorfastness to wet (dry) cleaning shall not apply.

*3.3.7 Label. Each flag shall have an identification label conforming to type I, class 5, of DDD-L-20.

*3.4 Design. The general design of the flag shall be the Marine Corps emblem with motto ribbon and scroll appliqued and machine embroidered to both sides of a 66-inch fly by 52-inch hoist scarlet background cloth. The motto ribbon shall have embroidered thereon the words SEMPER FIDELIS. Type I flags shall have embroidered on the scroll the name of the organization specified (see 6.2). Type II flags shall have embroidered on the scroll UNITED STATES MARINE CORPS. Type III flags shall have embroidered on the scroll UNITED STATES MARINE CORPS RESERVE. Type IV flags shall have embroidered on the scroll the major command

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:15Z
Check the source to verify that this is the current version before use.

specified (see 6.2). The flag shall have a tube or tunnel type heading lined with cotton flannel or cotton sheeting, fitted with a slotted leather strap at each end to attach the flag to a flagstaff. The flag shall have a continuous length of 2-1/2-inch-wide gold color rayon fringe stitched to top and bottom edges, fly end, and around ends of heading.

*3.4.1 Design application. The appliqued and embroidered emblem, motto ribbon and scroll shall be identical on both sides of the flag, except the position of the anchor in relation to the globe shall be reversed. The position of the emblem shall be such that a vertical line through the center of the globe coincides with the vertical center of the finished flag, exclusive of the heading and fringe, and a horizontal line which equally divides the distance between top embroidered edge of motto ribbon and bottom embroidered edge of scroll coincides with the horizontal center of the finished flag, exclusive of fringe. The embroidered banner cloth for the globe, motto ribbon and scroll for both sides of the flag shall be appliqued back to back, the words reading from left to right on both sides of the flag and centered on the motto ribbon and scroll from top to bottom. The land areas on the globe shall be in their positions on both sides of the flag. On both sides of the flag, the eagle shall face the hoist end. In relation to the globe, the anchor shall point downward from the northeast quarter to the southwest quarter on the front of the flag, and from the northwest quarter to the southeast quarter on the back of the flag, the ring and stock in the north, and the crown and flukes in the south. The front of the flag shall be that side which when viewed will have the hoist end on the left and the fly end on the right.

3.5 Construction.

3.5.1 Manufacturing requirements. The flags shall be manufactured in accordance with the operations and the stitch, seam and stitching types specified in Table I.

3.5.1.1 Operations. The supplier is not required to follow the exact sequence of operations as listed in Table I but all operations specified shall be used to manufacture the flags.

3.5.1.2 Stitches, seams and stitchings. The stitch, seam and stitching types specified in Table I shall conform to FED-STD-751. The number of stitches per inch as specified in Table I indicates the minimum and maximum number permitted.

*3.5.1.2.1 Ends of seams and stitching. Ends of seams and stitching, when not caught in other seams or stitchings, shall be backtacked not less than 1/4 inch; thread breaks shall be secured by stitching back of break not less than 1/2 inch.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:15Z
Check the source to verify that this is the current version before use.

*3.5.1.3 Embroidery stitching. All embroidery stitching, except the outline stitching of motto ribbon, bottom scroll, globe, and horizontal lines on the globe, shall be a chain and texture type of Bonnaz stitching. The outline stitching of the globe, motto ribbon and scroll, and the horizontal lines on the globe shall be an imitation hand embroidery type of stitching. The stitch type, texture, density and colors for the various parts of the embroidery work shall conform to the standard sample. The chain type of Bonnaz stitching shall be that type shown in the standard sample at the edging of the land areas on the globe, edging of the anchor, or in the wing feathers of the eagle; the textured type of Bonnaz stitching shall be that type shown in the standard sample in the large gold color areas of the continents and anchor. The imitation hand embroidery type of stitching outlining the globe and bottom scroll shall be made with 1/4-inch-long stitches, the lines on the globe shall be 3/16-inch-long stitches, and the outline around the motto ribbon shall be 1/8-inch-long stitches. Each horizontal line on the globe shall have a single row of No. 16 - Cable No. 67197 Putty HCW cotton thread sewn along the center of the line.

*3.5.1.3.1 Letter stitching. All letters shall be embroidered with No. 10-Cable No. 67111, Scarlet HL, embroidery thread. The style of the letters and the stitch type, texture and density of the embroidery work shall conform to the standard sample. Letters for the bottom scroll shall be 2 inches in height, and the letters for the motto ribbon shall be 1/2 inch in height.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:15Z
Check the source to verify that this is the current version before use.

TABLE I MANUFACTURING REQUIREMENTS

OPN NO.	OPERATION	Stitch Type	Seam or Stitch'g Type	Stitches Per Inch	THREAD	
					Needle	Bobbin or Looper
1.	Cutting. a. Cut the scarlet background cloth in a single piece sufficiently long to provide the required hems at the hoist and fly ends, and to provide a sufficient allowance for take-up of the cloth, due to the embroidery and applique work, permitting the flag to finish to the required length. The hoist of the flag shall be full width of the cloth, the selvages forming the top and bottom edges. Cut the cloth for the globe, scroll and motto ribbon for both sides of the flag. b. Cut the cotton flannel or cotton sheeting 6 inches wide and 53 inches long. c. Cut the leather tabs not less than 2 inches long and 3/4 ±1/16 inch wide with outer end rounded. Make a slit in each tab at the vertical center and 5/8 inch from rounded end with a 1/8 inch diameter hole punched in the tabs at the end of the slit nearest the rounded end of the tabs. The combined slit and hole shall measure 3/4 ±1/16 inch long.					
2.	Replacement of damaged parts a. Replace at time of cutting any part containing damages such as holes or serious weakening defects such as smashes, multiple floats and slubs likely to develop into holes.					

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:15Z
Check the source to verify that this is the current version before use.

TABLE I MANUFACTURING REQUIREMENTS

OPN NO.	OPERATION	Stitch Type	Seam or Stitch'g Type	Stitches Per Inch	THREAD	
					Needle	Bobbin or Looper
2.	Replacement of damaged parts (cont'd)					
	b. Replace any part damaged during the manufacturing process by needle chews which may be expected to develop into a hole, scissors or knife cuts, tears, holes, mends or burns.					
3.	Labeling.					
	Finished appearance. The label shall be correctly positioned and securely attached,					
	a. Position the identification label on the inside of the header lining to finish with the upper edge approximately 1/4 inch below finished upper edge of the header and seam on all sides 1/8 inch from each edge.	301	SSa-1	10-14	B	B
4.	Hem fly end of flag.					
	Finished appearance. The hem shall be made on the back of the flag and shall finish straight and parallel with the heading.					
	a. Hem the fly end of the flag 3/8 inch.	301	EFb-1	12-16	B	B
5.	Join fringe.					
	Finished appearance. A continuous length of fringe shall be stitched to the top and bottom edges and fly end of the flag, starting at the raw edge on the back of the flag at one end of the heading, continuing around the selvage edges and fly end on the front of the flag, and finishing at the raw edge on the back of the flag at the other end of the heading.					

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:15Z
Check the source to verify that this is the current version before use.

TABLE I MANUFACTURING REQUIREMENTS

OPN NO.	OPERATION	Stitch Type	Seam or Stitch'g Type	Stitches Per Inch	THREAD	
					Needle	Bobbin or Looper
5.	Join fringe (cont'd)					
	a. Stitch the fringe to the flag with gold and scarlet cotton thread, gold on the front of the flag to match the fringe and scarlet on the back of the flag. The fringe shall be evenly attached around the flag with a single row of stitching 1/8 inch from top edge of fringe heading and shall be neatly turned at the corners of the flag.	301	SSaa-1	12-16	B	B
6.	Make heading					
	Finished appearance. The heading shall be of the tube or tunnel type for the insertion of a flagstaff. The flat width of the finished heading shall be 2-3/4 ±1/8 inches wide.					
	a. Fold the header lining 1/2 inch at each end. Place this strip on the back of the flag at the hoist end with the folded ends of the strip flush with the selvage edges of the flag at the top and bottom, and attached thereto by a single row of stitching across each folded end of the strip.	301	SSb-1	12-16	B	B
	b. Position the leather tabs within the heading and center opposite the stitching of the hem with the rounded ends of the tabs flush with the ends of the heading. Stitch the tabs to the flag across their full width at the square end by cross box stitching.	301		12-16	B	B

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:15Z
Check the source to verify that this is the current version before use.

TABLE I MANUFACTURING REQUIREMENTS

OPN NO.	OPERATION	Stitch Type	Seam or Stitch'g Type	Stitches Per Inch	THREAD	
					Needle	Bobbin or Looper
6.	Make heading. (cont'd)					
	c. Hem the hoist end of the flag with the lining strip inside and 1/4 inch turned under. Stitch with a double row of stitching, 1/8 inch gage, with outer seam 1/16 inch from edge. Stitching shall pass through the turned edge of the flag, both turned edges of the lining strip, and both raw ends of the fringe.	301	LScd-2 (a)	12-16	B	B
7.	Clean flag.					
	a. Trim all ends of stitchings and remove all loose threads from the flag. Remove all spots and stains from the flag without injury to the material.					

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:15Z
Check the source to verify that this is the current version before use.

*3.6 Finished dimensions. The finished flags shall conform to the measurements shown in Drawing No. 71C5043A0000. All dimensions are exclusive of heading and fringe. Dimensional examination for the design and scroll shall be checked by comparing the balance and symmetrical alignment of standard sample. A tolerance of ±2 inches shall be allowed on dimensions over 2 feet. A tolerance of ±1/4 inches shall be allowed for dimensions of less than 2 feet.

* 3.7 Workmanship. The finished flags shall conform to the quality and grade of product established by this specification. The occurrence of defects shall not exceed the applicable quality levels (AQL's).

4. QUALITY ASSURANCE PROVISIONS

*4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

*4.1.1 Certificate of compliance. Where certificates of compliance are submitted, the Government reserves the right to check such items to determine the validity of the certification.

*4.2 Inspection. Inspection shall be in accordance with the provisions set forth in MIL-STD-105, except where otherwise indicated herein.

*4.2.1 First article. When a first article is required, inspection and testing shall be performed on a completely fabricated flag for conformance to all provisions of this specification.

*4.2.2 Component and material inspection. In accordance with 4.1 above, components and materials shall be tested in accordance with all requirements of referenced specifications, drawings, and standards, unless otherwise excluded, amended, modified or qualified in this specification or applicable purchase document. In addition, testing shall be performed on components listed in Table II for characteristics noted. Wherever applicable, tests shall be conducted in accordance with FED-STD-191. All requirements are applicable to the sample unit. All test reports shall contain the individual values utilized in expressing the final results.

*4.2.2.1 Sampling for testing. Unless otherwise specified in subsidiary specifications, sampling shall be in accordance with the following:

Lot size (lot unit)	Sample size (sample unit)
800 or less	2
801 to 22,000 inclusive	3
22,001 and over	5

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:15Z
Check the source to verify that this is the current version before use.

The lot shall be unacceptable if one or more sample units fail to meet any test requirement specified herein. The unit for expressing lot size and sample unit for testing component shall be in accordance with the applicable subsidiary specification as follows:

Component	Lot size expressed as	Sample unit for testing
Embroidery thread	1 spool, cone or tube	1 lb.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:15Z
Check the source to verify that this is the current version before use.

Table II - Test methods

Component	Characteristic	Rqmt. para.	Test method	No. Determinations per sample unit	Results reported as
Embroidery thread	Denier	3.3.2.2	Std. comm'l	5	Nearest Denier
	Breaking strength	3.3.2.2	4102	10	Nearest 0.5 lb.
	Dye Identification	3.3.2.2	Std. comm'l	1	Pass or fail
	Material Identification	3.3.2.2	1/		
	Length per oz.	3.3.2.2	Scale	5	Pass or fail

1/ Certificate of compliance will be acceptable for this requirement.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:15Z
Check the source to verify that this is the current version before use.

*4.2.2.2 In-process inspection. Inspection shall be performed during the manufacturing of the end item to ascertain that the operations are performed as specified herein. The Government reserves the right to determine the acceptability of construction methods not performed in accordance with specified requirements for operations or subassemblies.

*4.2.3 Examination of end item. The end item shall be examined for defects listed in 4.2.3.1 and 4.2.3.2. The sample unit shall be one flag.

*4.2.3.1 General defects. General defects shall be classified as follows:

Examine	Defect	Classification Major	Classification Minor
Material	Not fabricated of specified material, seriously affecting serviceability or appearance.	X	
	Not fabricated of specified material, affecting appearance or limiting serviceability slightly.		X
Color	Basic color other than specified or off shade.	X	
Material defects in fabric	Holes, or any weakening defects, such as smashes, multiple floats, or loose and weakening slubs, etc., expected to develop into a hole.	X	
	Any needle chews which may develop into a hole.	X	
	Any scissors or knife cuts, tears, mend or burn.	X	
	Shade bars, affecting appearance.	X	
Leather	Holes, brands, open cut or scratches, damage to grain or other flesh imperfections, impairing serviceability.	X	
	Leather tabs not positioned and attached as specified.		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:15Z
Check the source to verify that this is the current version before use.

Examine	Defect	Classification Major	Classification Minor
Leather	Not of specified thickness.		X
	Spots or stains clearly noticeable, affecting appearance.		X
	More than four thread ends not trimmed.		X
Seams and stitching	Seams twisted, puckered or pleated, affecting appearance.		X
	Ends of all stitchings (when not caught in other seams or stitches) not securely backstitched.	X	
	Thread break not securely back-stitched.		X
	Part of flag caught in any unrelated operation or stitching:		
	- seriously affecting appearance or serviceability.	X	
	- affecting appearance, but not seriously limiting serviceability.		X
	Gage of stitching not uniform, affecting appearance.		X
	Open seams:		
	-1/4 inch or less at one place.		X
	-1/4 inch or less at two or more places.	X	
	-more than 1/4 inch.	X	

NOTE: One or more broken or two or more continuous skipped or run-off stitches constitute an open seam. Double stitched seams are considered open when the opening occurs on either one or both sides of the seam.

	Open hems:		
	-1/2 inch or more.		X
	-less than 1/2 inch at 2 or more places.		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:15Z
Check the source to verify that this is the current version before use.

Examine	Defect	Classification Major	Minor
	Wrong seam or stitch type.		X
	Loose tension,resulting in loose seam.	X	
	Tight tension (stitches break when normal strain is applied to the seam or stitching).	X	

NOTE: Puckering is evidence of tight tension. When puckering is evident, the inspector shall test seam by exerting normal pull in the lengthwise direction of the seam.

	Less than 12 stitches per inch.		X
Heading	Not extending full length of the hoist of the flag.	X	
	Each end not folded at least 1/4 inch.		X
	Folded ends of heading strip not flush with the selvage edge of the flag at top and bottom.		X
	Less or more than double row of stitching.		X
	Heading seam not formed on back of flag.	X	
	Turned edge of flag not caught in double row of stitching.	X	
	Flat width of finished heading less than 2-5/8 inches or more than 2-7/8 inches.		X
Leather tabs	One or both missing.	X	
	Less than 2 inches long.		X
	Less than 11/16 inch wide.		X
	Strap not slit 1/2 ±1/16 inch at the vertical center and not less than 5/8 inch from the rounded end.	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:15Z
Check the source to verify that this is the current version before use.

Examine	Defect	Classification Major	Minor
	One-eighth inch diameter hole missing at the end of slit nearest the rounded end of strap.	X	
	Straps not centered within heading opposite the stitching of the hem.	X	
Fringe	Not specified type and color.	X	
	Not securely stitched to flag.	X	
	Omitted.	X	
	Not a continuous length.		X
	Not stitched to flag with gold and scarlet thread (gold on one side to match fringe; scarlet on other side to match base cloth).		X
	Fringe not neatly turned at corner.		X
	Raw edge of fringe not caught in heading stitching.	X	
	Fringe not evenly attached to flag.		X
Design	Emblem not clearly distinguishable.	X	
	The design and position of the appliqued and embroidered emblem, motto ribbon and scroll not identical on both sides of the flag (except that only the position of the anchor in relation to the globe will be reversed).	X	
	Lettering not legible from left to right.	X	
	Eagle does not face hoist end on both faces of flag.	X	
	Execution of applique not same as that on standard sample.		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:15Z
Check the source to verify that this is the current version before use.

Examine	Defect	Classification Major	Minor
	Lettering not same as that on standard sample.		X
	Design not equal to that of standard sample.	X	
	Colors not equal to those of standard sample.	X	
	Shades do not approximate those of standard sample.		X
Embroidery	Embroidery work stiff.		X
	Excessive puckering of cloth due to embroidery.		X
	Embroidery stitching (including lettering) not equal to that on standard sample as to type, texture, density, color and size.	X	
Label	Missing.		X
	Not legible.		X
	Not specified legend.		X

*4.2.3.2 Finished measurements. Overall length and width of flag and the placement of design and decorations deviating from dimensions shown in 3.6 shall be classified as a measurement defect.

*4.2.3.3 Inspection levels and AQL's. Inspection levels and AQL's expressed in defects per 100 units (DHU) shall be as follows:

4.2.3.1

Inspection level II of MIL-STD-105	
Major	2.5 DHU
Total Major and Minor	6.5 DHU

4.2.3.2

Inspection level S-3 of MIL-STD-105	
One class	4.0 DHU

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:15Z
Check the source to verify that this is the current version before use.

*4.2.4 Examination of preparation for delivery requirements. An examination shall be made to determine compliance with packaging, packing and marking requirements of Section 5 of this specification. Defects shall be scored in accordance with the list below. The sample unit shall be one shipping container fully prepared for delivery with the exception that it need not be sealed. Defects of closure listed below shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 and the AQL shall be 4.0 DHU.

Examine	Defect
Marking (exterior and interior)	Omitted, incorrect, illegible, of improper size, location, sequence or method of application.
Materials	Any component missing or damaged.
Workmanship	Inadequate application of components, such as incomplete closure of case liners, container flaps, loose strapping, inadequate stapling. Bulging or distortion of containers.
Weight or content (exterior and interior)	Number of intermediate packages is more or less than required. Gross/net weight exceeds requirements.

5 PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A or C, as specified (see 6.2).

5.1.1 Level A.

*5.1.1.1 Unit packaging. Each flag shall be laid out flat on two thicknesses of tissue paper conforming to type I, grade A, class 1 of UU-P-552. The tissue paper shall overlap all edges of the flag a minimum of 2 inches. Each flag and tissue paper shall be rolled open width on a chipboard tube. The tissue paper overlapping the tube ends shall be tucked inside the tube ends. The rolled flag shall then be inserted into a polyethylene bag or tube having a minimum thickness of 0.002 inch. Alternately, each flag shall be tightly wrapped with 50-pound minimum basis weight kraft paper conforming to grade B of UU-P-268. Each flag packaged as specified herein shall be placed in a snug-fitting fiberboard container conforming to class domestic, type CF or SF, grade 200 of PPP-B-636.

5.1.2 Level C. Flags shall be packaged in accordance with manufacturer's commercial practice.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:15Z
Check the source to verify that this is the current version before use.

5.2 Packing. Packing shall be level A, B or C as specified (see 6.2).

*5.2.1 Level A. Flags of one type only, packaged as specified in 5.1 shall be packed within snug-fitting shipping container conforming to class-weather resistant, type CF or SF, grade V3c or V3s of PPP-B-636 and assembled, closed and reinforced as specified in the appendix thereto. Net weight of the contents of each shipping container shall not exceed 65 pounds.

*5.2.2 Level B. Flags, packaged as specified in 5.1, shall be packed within a snug-fitting shipping container conforming to class-domestic type CF and SF, grade 200 of PPP-B-636. Net weight of the contents of each shipping container shall not exceed 65 pounds.

5.2.3 Level C. Flags shall be packed in a manner to insure carrier acceptance and safe delivery at destination. Containers shall be in accordance with Uniform Freight Classification Rules or regulations of other carriers applicable to the mode of transportation.

*5.3 Marking. In addition to any special marking required by the contract or order, unit packages and shipping containers shall be marked in accordance with the requirements of MIL-STD-129.

5.3.1 Labels. Each shipping container packed with mixed types shall have securely attached to the end and side, directly under the printing or stenciling, a white paper label with the words "MIXED TYPES" plainly stamped or printed thereon, and under these words shall be legibly printed the correct quantity contained therein.

5.3.2 Nomenclatures. The following item identification nomenclatures shall be used on all packages and shipping containers:

Type I: "FLAG, ORGANIZATIONAL: battle standard, USMC, w/scroll designating (name of organization embroidered on scroll)."

Type II: "FLAG ORGANIZATIONAL: standard, USMC, w/scroll."

Type III: "FLAG ORGANIZATIONAL: reserve standard, USMC, w/scroll."

Type IV: "FLAG ORGANIZATIONAL: command standard, USMC, w/scroll designating (name of command embroidered on scroll)."

6. NOTES

*6.1 Intended use. The flags covered by this specification are intended to be carried on the same occasions as the national colors.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:15Z
Check the source to verify that this is the current version before use.

*6.2 Ordering data. Purchasers should exercise any desired options offered herein, and procurement documents should specify the following:

*6.2.1 Procurement requirements.

(a) Title, number and date of this specification.
(b) Type required (see 1.2).
(c) When contracting officer shall not furnish standard samples of cloth (see 3.1).
(d) Whether first article is required (see 3.2).
(e) Number of flags in first article (see 3.2).
(f) Name of organization for scroll of type I flags (see 3.4).
(g) Name of command for scroll of type IV flags (see 3.4).
(h) Level of packaging and packing required (see 5.1 and 5.2).

*6.2.2 Contract data requirements. Data conforming to Data Item Description DI-R-4803, DI-R-4805, DI-T-4901, DI-T-4902, DI-T-4903 and DI-T-4904 will usually be required for delivery in connection with this specification. When so required, such data will be specified for delivery on a DD Form 1423 included in the contract.

*6.3 Samples and shade samples. For information regarding the availability of sample flags, and of standard shade specified, address inquiry to the procuring activity issuing the invitation for bids.

*6.4 First article. First article examination, test and approval shall be as specified by the contracting officer (see 3.2).

*6.5 Marginal notations. The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Preparing activity:
Navy - MC
Project Number 8345-N112

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:15Z
Check the source to verify that this is the current version before use.