MIL-R-19533A(AS)
AMENDMENT-3
15 SEPT 1968
SUPERSEDING
AMENDMENT-2
1 OCTOBER 1963

MILITARY SPECIFICATION

RECORDER SET, SOUND AN/UNH-6

This amendment forms a part of Military Specification MIL-R-19533A(Aer) dated 1 October 1957 and has been approved by the Naval Air Systems Command, Department of the Navy.

By this amdnement basic MIL-R-19533A(Aer) is changed to MIL-R-19533A(AS) and throughout the specification Bureau of Aeronautics shall be changed to Naval Air Systems Command.

*Page 6, paragraph 3.2.10(2): Delete "2.5 Amps." and substitute "5.0 Amps."

Page 8, paragraph 3.3.9: Delete and substitute

"3.3.9 Microphone Current - The equipment shall be capable of supplying 25 ma. of microphone current individually or simultaneously to external microphone circuits connected to either or both input circuits of the recorder during the record mode."

Page 8, paragraph 3.3.10.1: Delete "20 and 10,000 cps" and substitute

"50 and 10,000 cps"

Page 8, paragraph 3.3.10.2, first sentence: Delete and substitute

"The total harmonic distortion of recorded signals shall not exceed 2% at input signal frequencies between 70 and 10,000 cps nor 3% between 50 and 70 cps."

Page 8, paragraph 3.3.10.6: Number the existing paragraph (1) and add

"(2) The flutter requirements, under (1), above, shall not apply during vibration from 5 to 10 cps and the amount of flutter shall not exceed 1% on the vertical axis nor 1.5% on the lateral axis for vibration frequencies between 55 and 500 cps. The flutter requirements shall be as specified in (1), above, for all other vibration frequencies."

FSC-5895

Source: https://assist.dla.mil -- Downloaded: 202610-19T06:07Z
Check the source to verify that this is the current version before use.

Page 8, paragraph 3.3.10.9: Delete and substitute

"3.3.10.9 Time Standard - The Recorder Control (3.4.2) shall be capable of generating a 1000 cps time standard with an accuracy within ±.01%. The capability of recording this signal on at least one recorder track is required."

Page 9, paragraph 3.4.1.4: Delete "A shatter-proof glass window" and

substitute

"A 1/16 inch plastic window"

Page 10, paragraph 3.4.1.5.1(5): Delete and substitute

"(5) A blower motor shall not be required provided the equipment meets all the environmental requirements without a blower."

Page 14, paragraph 4.3.1.3: Delete "20 to 30 cps" and substitute

"20 to 60 cps"

An asterisk preceding a page number denotes a change to be made to the specification which did not appear in Amendment-2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:07Z
Check the source to verify that this is the current version before use.