NOT MEASUREMENT SENSITIVE

MIL-L-11484/102B
14 January 1994
SUPERSEDING
MIL-L-11484/102A
27 June 1988

MILITARY SPECIFICATION SHEET

LAPEL BUTTON, REGIONAL AND STATE SCIENCE AND ENGINEERING FAIR AWARDS, ARMY

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-L-11484.



DASH NO.
-1: Gold
-2: Silver
-3: Bronze

MATERIAL: Red Brass

DIMENSIONS:
DIAMETER: 9/16 inch (1.43 cm) (REF)
THICKNESS (At Edge): 0.065 inch ± 0.005 inch (0.165 cm ± 0.012 cm)

FINISH:
-1: Gold Plated, Rose Gold Plated, Relieved, Matte Finish

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil - Downloaded: 2026-10-17T16:41Z
Check the source to verify that this is the current version before use.

-2: Nickel Plated, Silver Plated, Oxidized, Relieved, Matte Finish and shall match TIOH Metal Finish Chip Number 14.

-3: Oxidized, Relieved, Matte Finish and shall match TIOH Metal Finish Chip Number 4.

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. All lapel buttons shall be lacquered.

3. Attaching device shall be prong with pick and flat ball type clutch. The prong shall be centered on the reverse side and fused or soldered to the lapel button.

Custodians:
Army - IH

Review activities:
DLA - CT

Preparing activity:
Army - IH

(Project No. 8455-0745)

Source: https://assist.dla.mil -- Downloaded: 202610-17T16:41Z
Check the source to verify that this is the current version before use.