INCH - POUND

MIL-DTL-11484/102D
12 November 2015
SUPERSEDING
MIL-DTL-11484/102C
27 September 1996

DETAIL SPECIFICATION SHEET

LAPEL BUTTON, REGIONAL AND STATE SCIENCE AND ENGINEERING FAIR AWARDS, U.S. ARMY

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-11484.

DASH NO.
-1: Gold
-2: Silver
-3: Bronze

MATERIAL: Red Brass 85/15 (UNS Alloy No. C-230)

FINISH:
-1: 24K Gold Plated, Matte Finish, and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 7.
-2: Nickel Plated, Silver Plated, Oxidized, Relieved, Matte Finish and shall match TIOH Metal Finish Chip Number 14.
-3: Oxidized, Relieved, Matte Finish and shall match Metal Finish Chip Number 4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:41Z
Check the source to verify that this is the current version before use.

DIMENSION:
DIAMETER: 9/16 inch (REF)
THICKNESS (At edge): 0.080 inch ± 0.005 inch

ATTACHING DEVICE:
1. The attaching device shall be a prong with pick and flat ball type clutch.

2. The prong shall be centered on the reverse side and fused or soldered to the lapel button.

NOTES:
1. The term (REF) refers to the measurements taken from the obverse Government furnished hub or die.

2. Lapel button shall be lacquered.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2015-526)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:41Z
Check the source to verify that this is the current version before use.