NOT MEASUREMENT SENSITIVE

MIL-L-11484/172
9 July 1990

MILITARY SPECIFICATION SHEET

LAPEL BUTTON, EXCEPTIONAL AND MERITORIOUS CIVILIAN SERVICE AWARD
ON-SITE INSPECTION AGENCY

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-L-11484.

MATERIAL: Red brass

DASH NO:
-1: Exceptional Civilian Service
-2: Meritorious Civilian Service

DIMENSIONS:
WIDTH (Overall): 5/8 inch (1.59 cm) (REF)
THICKNESS (At thickest point): .080 inch ± .005 inch (0.203 cm ± 0.012 cm)

FINISH:
-1: Gold plated, rose gold plated, lightly relieved, matte finish.
-2: Nickel plated, silver plated, oxidized, lightly relieved, matte finish.

NOTE: Attaching device shall be prong with pick and wing type clutch. The prong shall be centered on the reverse side and fused or soldered to the lapel button.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activity:
Army - IH

(Project No. 8455-0534)

AMSC N/A

FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T17:09Z
Check the source to verify that this is the current version before use.