NOT MEASUREMENT SENSITIVE

MIL-L-11484/172A
14 January 1994
SUPERSEDING
MIL-L-11484/172 (IN PART)
9 July 1990

MILITARY SPECIFICATION SHEET

LAPEL BUTTON, EXCEPTIONAL CIVILIAN SERVICE AWARD, ON-SITE INSPECTION AGENCY

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-L-11484.

MATERIAL: Red Brass

FINISH: Gold Plated, Rose Gold Plated, Matte Finish, Lightly Relieved

DIMENSIONS:
DIAMETER: 5/8 inch (1.59 cm) (REF)
THICKNESS (At Thickest Point): 0.080 inch ± 0.005 inch (0.203 cm ± 0.012 cm)

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T17:09Z
Check the source to verify that this is the current version before use.

2. Lapel button shall be lacquered.

3. The attaching device shall be prong with pick and wing type clutch. The prong shall be centered on the reverse side and fused or soldered to the label button.

Custodian:
Army - IH

Review activities:
DLA - CT

User activities:
Other - OSIA

Preparing activity:
Army - IH

(Project No. 8455-0745)

Source: https://assist.dla.mil - Downloaded: 2026-10-17T17:09Z
Check the source to verify that this is the current version before use.