NOT MEASUREMENT SENSITIVE

MIL-DTL-11484/178B
27 September 1996
SUPERSEDING
MIL-L-11484/178A
14 January 1994

DETAIL SPECIFICATION SHEET

LAPEL BUTTON, POINT OF LIGHT, FEDERAL EMPLOYEE SERVICE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-11484 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.



MATERIAL: Gilding Metal

FINISH: Hard Enameled, Gold Plated, Mirror-like Polished and shall match TIOH Metal Finish Chip Number 6.

DIMENSIONS:
HEIGHT (Overall): 7/8 inch (2.22 cm) (REF)
WIDTH (Overall): 5/8 inch (1.59 cm) (REF)
THICKNESS (At Thickest Point): 0.090 inch ± 0.005 inch (0.229 cm ± 0.012 cm)

AMSC N/A FSC 8455
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T17:11Z
Check the source to verify that this is the current version before use.

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Enameled areas shall be as indicated. The colors shall conform to the TIOH color chip numbers listed below or the standard sample.

COLOR	CHIP NO.
Black	26
White	28

3. Epoxy resin (stoning epoxy) may be used in lieu of hard enamel at the option of the manufacturer.

4. Attaching device shall be prong with pick and flat ball type clutch. The prong shall be centered on the reverse side and fused or soldered to the lapel button.

5. Each lapel button shall be mounted and centered on a sulfite board 0.030 inch (0.076 cm in thickness (minimum) and approximately 3-3/4 inches (9.53 cm) in length by 2-1/4 inches (5.72 cm) wide. The face of the sulfite board shall be covered with cobalt blue flock. The mounted sulfite board shall be placed in a rigid hinged plastic box having a transparent lid and opaque white bottom section. The box shall have two plastic hinges and catches and shall be approximately 3 inches (7.62 cm) in length, 1-1/4 inches (3.18 cm) wide and 3/4 inch (1.91 cm) in overall depth.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activities:
DLA - CT

(Project No. 8455-0858)

Civil Agency Coordinating Activity:
GSA- 7FXE

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T17:11Z
Check the source to verify that this is the current version before use.