NOT MEASUREMENT SENSITIVE

MIL-DTL-11484/181C
27 May 1997
SUPERSEDING
MIL-DTL-11484/181B
27 September 1996

DETAIL SPECIFICATION SHEET

LAPEL BUTTON, EXEMPLARY CIVILIAN SERVICE AWARD, AIR FORCE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-11484 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.

MATERIAL: Gilding Metal

FINISH: Oxidized, Relieved, Polished Highlights

DIMENSIONS:
DIAMETER: 17/32 inch (1.35 cm) (REF)
THICKNESS (At Thickest Point): 0.050 inch ± 0.010 inch (0.127 cm ± 0.025 cm)

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T17:13Z
Check the source to verify that this is the current version before use.

2. Attaching device shall be prong with pick and flat ball type clutch. The prong shall be centered on the reverse side and fused or soldered to the lapel button.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH
Air Force - 45

Preparing activity:
Army - IH

Review activities:
Air Force - 32, 82, 99
DLA - CT

(Project No. 8455-0896)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T17:13Z
Check the source to verify that this is the current version before use.