NOT MEASUREMENT SENSITIVE

MIL-DTL-11484/181E
4 March 2020
SUPERSEDING
MIL-DTL-11484/181D
27 April 2015

DETAIL SPECIFICATION SHEET

LAPEL BUTTON, EXEMPLARY CIVILIAN SERVICE AWARD, U.S. AIR FORCE

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet, the latest issue of MIL-DTL-11484.



MATERIAL: Gilding Metal 95/5 (UNS Alloy C-210)

FINISH Gilding Metal, Oxidized, Relieved, Polished Highlights and shall match The Institute of Heraldry Metal Finish Chip Number 23.

DIMENSIONS:
DIAMETER: 17/32 inch (REF)
THICKNESS (At thickest point): 0.050 ± 0.010 inch.

ATTACHING DEVICE:
1. Attaching device shall be prong with pick and flat ball type clutch.

2. The prong shall be centered on the reverse side and fused or soldered to the lapel button.

NOTE:
The term (REF) refers to the measurements taken from the Government furnished hub or die.

AMSC N/A FSC 8455

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T17:12Z
Check the source to verify that this is the current version before use.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - IH
Air Force - 11

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2020-182)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T17:12Z
Check the source to verify that this is the current version before use.