INCH-POUND
MIL-B-48447A (AR)
AMENDMENT 3
21 July 1999
SUPERSEDING
AMENDMENT 2
17 June 1991

MILITARY SPECIFICATION

BODY ASSEMBLY: 11744900
(PERISCOPE: M35E1)

MIL-B-48447A was inactivated after 28 November 1995 for new design

This amendment forms a part of MIL-B-48447A (AR) dated 15 October 1979, and is approved for use by the U.S. Army Armament, Research, Development, and Engineering Center, and is available for use by all Departments and Agencies of the Department of Defense

PAGE 2

* Under drawings list delete:

"F11732110 Gage Interchangeability, Minimum"

3.4.3, Delete and Substitute:

"3.4.3 Vibration "A". Vibration shall be applied along each of the three mutually perpendicular axes of the body assembly. The vibration shall be sinusoidal as follows:

a. At a frequency of 5 Hertz (Hz), the acceleration shall be 0.5 G +/- 10%.

b. During a frequency sweep of 5 to 9 Hz, increase acceleration linearly from 0,5 G to 1.5 G's +/- 10%.

c. During a frequency sweep of 9 to 500 Hz, maintain constant acceleration of 1.5 G's +/- 10%.

d. During a frequency sweep of 500 to 9 Hz, maintain constant acceleration of 1.5 G's +/- 10%.

e. During a frequency sweep of 9 to 5 Hz, decrease acceleration linearly from 1.5 G's to 0.5 G +/- 10%

f. At 5 Hz, the acceleration shall be 0.5 G +/- 10%.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:27Z
Check the source to verify that this is the current version before use.

The frequency of applied vibration shall be swept logarithmically in 15 minutes +/- 1 minute sweep cycles for a total of two hours per axis. The body assembly shall show no evidence of physical failure subsequent to vibration. Following the vibration test the body assembly shall meet the requirements of 3.2 and 3.5 through 3.17.4 inclusive."

PAGE 3

3.4.4, Delete and substitute:

"3.4.4 Vibration "B". Vibration shall be applied along each of the three mutually perpendicular axes of the body assembly. The vibration shall be sinusoidal as follows:

a. At a frequency of 5 Hertz (Hz), the acceleration shall be 1.0 G +/- 10%.

b. During a frequency sweep of 5 to 500 Hz, maintain constant acceleration of 1.0 G +/- 10%.

c. During a frequency sweep of 500 to 5 Hz, maintain constant acceleration of 1.0 G +/- 10%.

d. At 5 Hz, acceleration shall be 1.0 G +/- 10%.

The frequency of applied vibration shall be swept logarithmically in 15 minutes +/- 1 minute sweep cycles for a total of two hours per axis. The body assembly shall show no evidence of physical failure subsequent to vibration. Following the vibration test the body assembly shall meet the requirements of 3.2 and 3.5 through 3.17.4 inclusive."

3.4.5, Delete and substitute:

"3.4.5, Shock. The body assembly shall be subjected to 24 cumulative shocks consisting of three each at 35 G's +/- 10% applied in each direction along each of the two mutually perpendicular horizontal axes (all four sides). The shock pulse shall have a half sine wave with a time duration of 3 +/- 0.2 milliseconds. The body assembly shall also be subjected to six cumulative shocks consisting of three each at 35 G's +/- 10%, then 20 G's +/- 10% applied in one direction along the vertical axis (normal operating position of the body assembly only). The shock pulse shall have a half sine wave with a time duration of 18 +/- 3 milliseconds. The body assembly shall show no evidence of physical failure subsequent to shock. Following the shock test, the body assembly shall meet the requirements of 3.2 and 3.5 through 3.17.4 inclusive.

PAGE 4

3.6, Delete and substitute:

"3.6 Sealing. The body assembly shall show no evidence of leakage in excess of 0.1 pound per square inch (psi) when subjected to an internal pressure of 5 +/- 0.10 psi for a minimum of 1 hour. The

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:27Z
Check the source to verify that this is the current version before use.

interior atmosphere of the accepted body assembly shall contain nitrogen having a dew point at least as low as minus 25 degrees F at atmospheric pressure. The body assembly shall then be sealed with the dry nitrogen specified to an internal pressure of between 0.25 and 0.50 psi."

PAGE 10

* 4.5.2.3.2.1 Delete in its entirety and substitute:

"4.5.2.3.2.1 Interchangeability. – Maximum interchangeability gage shall conform to drawing F11732109."

PAGE 14

4.6.6, line 2, Delete "0.25 to 0.50" and substitute with "0.0 to 0.50"

PAGE 18

* 4.6.7.10 Delete in its entirety and substitute:

"4.6.7.10 Interchangeability. – This test shall be performed utilizing the maximum interchangeability gage in drawing F11732109 to determine compliance with 3.2."

NOTE: The margins of the amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only, and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian
Army – AR

Preparing activity
Army – AR

(Project: 1240-0053)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:27Z
Check the source to verify that this is the current version before use.