INCH-POUND

MIL-C-48436A (AR)
AMENDMENT 1
27 August 1992 .

MILITARY SPECIFICATION

TEST SET SUBASSEMBLY: 11726378
(7.5 MHz Clock)

This amendment forms a part of MIL-C-48436A (AR), dated 29 March 1991, and is approved for use by the US Army Armament, Munitions, anti Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1.1: **Add the following military specification:**

"MIL-T-28800 - Test Equipment for use with Electrical and Electronic Equipment, General Specification for"

PAGE 2

2.1.1: **Delete the following military standard:**

'MIL-STD-2000 - Standard Requirements for Soldering Electrical and Electronic Assemblies"

2.1.2: Add the following drawing:

"12950877 - Requirements for Soldering Electrical and Electronic Assemblies"

PAGE 3

3.3.1: Delete in its entirety and substitute the following:

'3.3.1 Vibration. The 7.5 MHz clock shall not suffer damage and shall meet the requirements of 3.4 and 3.5 after exposure to sinusoidal vibrations, in each of three mutually perpendicular axes, as specified in MIL-T-28800 for Type I, Class 3, Style F test equipment."

DISTRIBUTION STAT'EMENT A. Approved for publlc release; distribution is unlimlted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:26Z
Check the source to verify that this is the current version before use.

3.3.3, 3.3.3.1 and 3.3.3.2: Delete in their entirety and substitute the following:

"3.3.2 Altitude operating. The 7.5 MHz clock shall meet the requirements of 3.4 and 3.5 during and after exposure to barometric pressure encountered at 10,000 feet above sea level (20.6 inches of Hg)."

PAGE 6

3.8: Delete in its entirety and substitute the following:

"3.8 Soldering All soldering shall be in accordance with the requirements of Note 2 of Drawing 12950877."

PAGE 12

4.7.1.1: Delete in its entirety and substitute the following:

"4.7.1.1 Vibration. This test shall be performed as specified in MIL-T-28800 for Type I, Class 3, Style F test equipment with the exception that Step 4.c Resonance Dwell does not apply. The 7.5 MHz-clock shall be attached to the vibration generator directly or with a fixture, and securely held by its normal means of attachment. After vibration, the 7.5 MHZ clock shall be tested as specified in 4.7.2 and 4.7.3 herein to determine compliance with 3.3.1."

4.7.1.3: Delete in its entirety and substitute the following:

'4.7.1.3 Altitude operating This test shall be performed as specified in Procedure II, Method 500, of MIL-STD-810. The operational checkout shall be as specified in 4.7.2 and 4.7.3 for compliance with 3.3.3."

PAGE 13

Add new paragraph 4.8 as follows:

"4.8 Soldering Soldering processes shall be inspected by certified inspectors to the requirements and acceptance criteria of Note 2 of Drawing 12950877 as specified in paragraph 3.8."

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1285-A807)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:26Z
Check the source to verify that this is the current version before use.