NOT MEASUREMENT SENSITIVE

MIL-DTL-3943/74E
11 May 1999
SUPERSEDING
MIL-DTL-3943/74D
1 May 1997

DETAIL SPECIFICATION SHEET

DECORATION, MERITORIOUS CIVILIAN SERVICE AWARD, DEFENSE INTELLIGENCE AGENCY

Inactive for new design after 14 January 1999.

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-3943 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.



MATERIAL:
BASE: Gilding Metal
DEVICE: Red Brass

FINISH:

BASE:
OBVERSE: Hard Enameled, Gold Plated, Mirror-like Polished and shall match TIOH Metal Finish Chip Number 6.
REVERSE: Gold Plated, Matte Finish and shall match TIOH Metal Finish Chip Number 7.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T23:19Z
Check the source to verify that this is the current version before use.

DEVICE: Gold Plated, Matte Finish, Polished Highlights and shall match TIOH Metal Finish Chip Number 8.

DIMENSIONS:

BASE:
HEIGHT (including lug): 1-15/16 inches (REF)
WIDTH (overall): 1-1/2 inches (REF)
THICKNESS (thickest point): 0.070 inch ± 0.005 inch

DEVICE:
HEIGHT (overall): 1-1/4 inches (REF)
WIDTH (overall): 3/4 inch (REF)
THICKNESS (center of globe): 0.210 inch ± 0.010 inch

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub and die.

2. Enameled area shall be white as indicated. The color shall conform to TIOH Hard Enamel Color Chip Number 28.

3. Epoxy resin (stoning epoxy) may be used in lieu of hard enamel at the option of the manufacturer. When epoxy resin is used in lieu of hard enamel, the material requirement shall be gilding metal or red brass.

4. The device shall be soft soldered to base as shown.

5. The reverse of the base shall be flat.

6. Pierced areas shall be as indicated.

7. Decoration set shall consist of a regular size medal, a service ribbon, and a lapel button all packaged in a presentation case conforming to MIL-DTL-14633, Type VIII, Style 6 with a Class 1, 1A or 3 pad.

8. The ribbon for the pendant drape and service ribbon shall conform to MIL-DTL-11589/184.

9. The lapel button shall conform to MIL-DTL-11484/93.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T23:19Z
Check the source to verify that this is the current version before use.

Custodian:
Army - IH
DIA - DI

Preparing activity:
Army - IH

Review activities:
DLA - CT

(Project No. 8455-0978)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T23:19Z
Check the source to verify that this is the current version before use.