NOT MEASUREMENT SENSITIVE


MIL-D-3943/75C
12 June 1992
SUPERSEDING
MIL-D-3943/75B
31 March 1987

MILITARY SPECIFICATION SHEET


DECORATION, PRESIDENTIAL CITIZENS MEDAL

This specification is approved for use by all Departments and Agencies of the Department of Defense


The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-D-3943.



OBVERSE



REVERSE



MATERIAL: Gilding Metal

FINISH: Hard Enameled, Gold Plated, Matte Finish

DASH NO.
-1: Regular Size
-2: Miniature Size

AMSC N/A

FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil - Downloaded: 2026-10-16T23:20Z
Check the source to verify that this is the current version before use.

DIMENSIONS:

DIAMETER:

- 1: 1-5/8 inches (4.13 cm) (REF)
-2: 13/16 inch (2.06 cm) (REF)

THICKNESS:

DEVICE (At Eagle's Breast):

-1: 0.150 inch (0.381 cm) (REF)
-2: 0.100 inch (0.254 cm) (REF)

BASE (On Shield Stripes):

-1: 0.110 inch (0.279 cm) (REF)
-2: 0.070 inch (0.178 cm) (REF)

ASSEMBLED (At Eagle's Breast)

-1: 0.240 inch + 0.010 inch (0.610 cm + 0.025 cm)
-2: 0.170 inch + 0.010 inch (0.432 cm + 0.025 cm)

NOTES:

1. Enameled areas shall be as indicated. The color shall conform to TIOH Color Chip Numbers listed below or the standard sample.

COLOR	CHIP NO.
Green	11
Blue	20
White	28

2. Pierced areas shall be as indicated.

3. The pendant shall be fabricated in two pieces and soft soldered together after enameling. The parting line between the base and device shall not be visible after finishing.

4. The lug shall be formed from a half circle of brass wire and shall be soldered in the location shown. The lug for Dash No. 1 shall be formed from 0.050 inch ± 0.003 inch (0.127 cm ± 0.008 cm) diameter wire and shall have an outside diameter of 1/4 inch ± 1/64 inch (0.64 cm ± 0.04 cm). The lug for Dash No. 2 shall be formed from 0.025 inch ± 0.002 inch (0.064 cm ± 0.005 cm) diameter wire and shall have an outside diameter of 1/8 inch ± 1/64 inch (0.32 cm ± 0.04 cm).

5. A forcer may be used to bring up the details of the eagle and the device.

6. Type I Decoration set shall consist of a regular size medal, a service ribbon and a lapel button all packaged in a presentation case conforming to MIL-C-14633, Style 6, Type VIII with a Class 1 or 1A pad.

7. The ribbon for the pendant drape and service ribbon shall conform to MIL-R-11589/179.

8. The lapel button shall conform to MIL-L-11484/94.

9. The term (REF) refers to the measurements taken from the Government furnished hub and die.

Source: https://assist.dla.mil - Downloaded: 2026-10-16T23:20Z
Check the source to verify that this is the current version before use.

Custodians:
Army - IH

Review activities:
DLA - CT

User activity:
Other - DIA

Preparing activity:
Army - IH

(Project No. 8455-0669)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T23:20Z
Check the source to verify that this is the current version before use.