MILITARY SPECIFICATION

THERMOMETER, SELF-INDICATING, 5-INCH SCALE SIZE, LIQUID-IN-GLASS, MERCURY

This supplement lists the Military sheet form Standards associated with Specification MIL-T-24103(SHIPS), 30 October 1964.

MS Standards

MS18139 - Three-eighths Inch Thermometer Well, 2-Inch Insertion Length, 3/4 Inch NPT Thread Connection.
MS18140 - Three-eighths Inch Thermometer Well, 4-Inch Insertion Length, Thread Connection.
MS18141 - Three-eighths Inch Thermometer Well, 4-Inch Insertion Length, 1/2 Inch NPT Thread Connection.
MS18142 - Three-eighths Inch Thermometer Well, 2-Inch Insertion Length, Combination 1/2 Inch and 3/4 Inch NPT Thread Connection.
MS18143 - Three-eighths Inch Thermometer Well, 4-Inch Insertion Length, Combination 1/2 Inch and 3/4 Inch NPT Thread Connection.
MS18144 - Three-eighths Inch Thermometer Well, 2-Inch Insertion Length, 1/2 Inch NPT Thread Connection.
MS18145 - Three-eighths Inch Thermometer Well, 4-Inch Insertion Length, Socket Weld or Brazed Connection (Below 5000 PSI WP).
MS18147 - Three-eighths Inch Thermometer Well, 2-Inch Insertion Length, Socket or Brazed.

Preparing activity:
Navy - SH

FSC 6685

Source: https://assist.dla.mil -- Downloaded: 20261O-19T19:06Z
Check the source to verify that this is the current version before use.