MILITARY SPECIFICATION SHEET

CONNECTOR, FIBER OPTIC, ADAPTER 2.5 MM BAYONET, BULKHEAD PANEL MOUNT, COUPLING RECEPTACLE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the connector described herein shall consist of this specification and the latest issue of MIL-C-83522.




FIGURE 1. Dimensions and configuration.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:36Z
Check the source to verify that this is the current version before use.

Inches	mm	Inches	mm	Inches	mm
.010	0.25	.104	2.64	.375	9.53
.01	0.3	.170	4.32	.386	9.80
.025	0.64	.180	4.57	.570	14.48
.043	1.09	.190	4.83	.580	14.73
.045	1.14	.200	5.08	.590	14.99
.046	1.17	.220	5.59	.610	15.49
.050	1.28	.273	6.92	.620	15.75
.058	1.47	.276	7.01	.635	16.13
.061	1.55	.288	7.32	.795	20.19.
.062	1.57	.30	7.6	.820	20.83
.063	1.60	.320	8.13	1.160	29.46
.09846	2.5009	.335	8.50		

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.

FIGURE 1. Dimensions and configuration - Continued.




FIGURE 2. Recommended panel cutout.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:36Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Metals: The coupling receptacle housing shall be of corrosion-resistant steel in accordance with QQ-S-763, class 303, /316; nickel-plated brass in accordance with QQ-B-626; nickel-plated zinc die cast alloy; or 6061 nickel-plated aluminum. Other metal components shall be of corrosion-resistant steel in accordance with QQ-S-763, class 303, /316; nickel-plated beryllium copper in accordance with QQ-B-530; nickel-plated brass in accordance with QQ-B-626, or 6061 nickel-plated aluminum.

Dust covers: Dust covers shall be thermoplastic.

Hex nut: Hex nut shall be nickel-plated brass or stainless steel.

Dimensions and configurations: See figures 1 and 2.

Optical requirements:

Optical loss (attenuation): Not applicable.

Weight: 6 grams maximum.

Safety wire holes: Not applicable.

Force to engage and disengage:

Longitudinal force: Not applicable.

Torque: Not applicable.

Coupling proof torque: Not applicable.

Coupling mechanism retention force: The force shall be 20 pounds minimum and shall not result in any physical damage.

Mating durability: In accordance with MIL-C-83522, mating durability paragraphs, except 500 cycles instead of 200 cycles.

Ozone exposure: Not applicable.

Fiber optic cable:

Cable diameter: In accordance with DOD-C-85045/2.

Cable configuration: In accordance with DOD-C-85045/2.

Fiber diameter: In accordance with DOD-F-49291/1 through DOD-F-49291/4.

Fiber numerical aperture: Not applicable.

Fiber type: Not applicable.

Fiber class: Not applicable.

Military part number: M83522/13-01.

Coupling receptacle accessories: Coupling receptacle shall be supplied with two dust covers, one lock washer, and one hex nut.

Note: This coupling receptacle is used to mate two MIL-C-83522/12, 2.5 mm connector plugs together.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:36Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 85

Review activities:
Navy - SH
Air Force - 11, 17, 19, 80, 90, 99
DLA - ES

User activities:
Navy - AS, MC, OS
Air Force - 13, 14

Preparing activity:
Air Force - 85

Agent:
DLA - ES

(Project 6060-0072-2)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:36Z
Check the source to verify that this is the current version before use.