MILITARY SPECIFICATION SHEET

CONNECTOR, FIBER OPTIC, PLUG-RECEPTACLE-ADAPTER STYLE, FIXED SINGLE TERMINUS, THREADED, PLUG (STEP-DOWN NOSE INTERFACE), LENSLESS, EPOXY, FOR 50/125 µm AND 100/140 µm FIBER

This amendment forms a part of MIL-C-83522/1C, dated 17 February 1987, and is approved for use by all Departments and Agencies of the Department of Defense

PAGE 4

Torque, delete and substitute:

"Torque: 4 inch-pounds maximum."

Coupling proof torque, delete and substitute:

"Coupling proof torque: 5 inch-pounds minimum."

Custodians:
Army - CR
Navy - EC
Air Force - 85

Review activities:
Navy - SH
Air Force - 11, 17, 19, 80, 90, 99
DLA - ES

User activities:
Navy - AS, MC, OS
Air Force - 13, 14

Preparing activity:
Air Force - 85

Agent:
DLA - ES

(Project 6060-0063-1)

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:35Z
Check the source to verify that this is the current version before use.