NOT MEASUREMENT SENSITIVE


MIL-I-15665/21F
30 July 1992
SUPERSEDING
MIL-I-15665/21E
15 March 1988

MILITARY SPECIFICATION SHEET

INSIGNIA, SERVICE CAP, EP; AIR FORCE

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-I-15665.



MATERIAL: Nickel Silver, Red Brass or Zinc Aluminum

FINISH: Nickel Plated (Red Brass & Zinc Aluminum Only), Silver Plated, Oxidized, Relieved, Matte Finish. The reverse and inner and outer surfaces of the ring shall be dark grey or black.

DIMENSIONS:
DIAMETER: 1-3/4 inches (4.45 cm) (REF)
THICKNESS (Outside Edge): 0.070 inch ± 0.005 inch (0.178 cm ± 0.012 cm)

FSC 8455

AMSC N/A
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T06:34Z
Check the source to verify that this is the current version before use.

NOTE:

1. The term (REF) refers to measurements taken from the Government furnished hub or die.

2. In addition to the finish specified, the zinc aluminum shall be copper plated to begin the finishing process.

3. A full forcer may be used except on the outer ring.

4. Pierced areas shall be as indicated. Only the left hand piercing is shown.

5. The insignia shall be spherically dapped to a depth of 1/8 inch + 1/32 inch - 0 (0.32 cm + 0.08 cm - 0) when measured from the back of the rim to the high point of the obverse.

6. The attaching device shall be a screw post and registering prong soldered or fused to the reverse of the insignia. The screw post shall be located on the vertical center line at the top edge of the shield and the registering prong located on the vertical center line and the center of the glory.

7. The screw post shall be 9/16 inch ± 1/32 inch (1.43 cm ± 0.08 cm) in diameter and shall have a No. 5-40UNC-2A thread.

8. The thumb nut shall be 0.625 inch ± 0.010 inch (1.578 cm ± 0.025 cm) in diameter and shall have a No. 5-40UNC-2B thread.

9. The registering prong shall be prong and clutch type. The prong shall be 1/4 ± 1/64 inch (0.64 cm ± 0.04 cm) length and 0.045 inch ± 0.010 inch (0.114 cm ± 0.005 cm) in diameter.

Custodian:
Army - IH
Air Force - 11

Review activities:
Air Force - 82, 99
DLA - CT

User Activity:
Air Force - 45

Preparing activities:
Army - IH

(Project No. 8455-0680)

Source: https://assist.dla.mil -- Downloaded: 202640-18T06:34Z
Check the source to verify that this is the current version before use.