NOT MEASUREMENT SENSITIVE


MIL-I-15665/22C
30 July 1992
SUPERSEDING
MIL-I-15665/22B
15 March 1988


MILITARY SPECIFICATION SHEET

INSIGNIA, SERVICE CAP, EP; ARMY


This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-I-15665.





CROSS SECTION OF ASSEMBLED INSIGNIA



MATERIAL:
DISC, AND COAT OF ARMS: Red Brass

FINISH:
DISC: Mirror-like Polished
COAT OF ARMS: Matte Finish with Polished Highlights

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T06:35Z
Check the source to verify that this is the current version before use.

DIMENSIONS:

DISC:

DIAMETER: 1-1/2 inches ± 1/32 inch (3.81 cm ± 0.08)

THICKNESS (At Center): 0.020 inch ± 0.002 inch (0.051 cm ± 0.005 cm)

COAT OF ARMS:

HEIGHT (Overall): 1-1/4 inches (3.18 cm) (REF)

THICKNESS (Center of Shield): 0.050 inch ± 0.005 inch (0.127 cm ± 0.012 cm)

NOTE:

1. The term (REF) refers to measurements taken from the Government furnished hub or die.
2. A full forcer shall be used to bring up the design on the coat of arms.
3. Pierced area shall be as indicated.
4. Pierced holes on the disc may be circular as shown or any polygon shape provided distance between opposite sides of the polygon are equal to diameter shown.
5. The disc shall be spherically dapped to a radius of 2-3/8 inches ± 1/8 inch (6.03 cm ± 0.32 cm).
6. The coat of arms shall be spherically dapped to a radius of 1-7/16 inches ± 1/16 inch (3.65 cm ± 0.16 cm).
7. The screw post shall be centered on the coat of arms and shall be 9/16 inch ± 1/32 inch (1.43 cm ± 0.08 cm) long with a No. 5-40UNC-2A thread. The post shall be soldered or electronically fused to the coat of arms.
8. The thumb nut shall be 0.625 inch ± 1/64 inch (1.65 cm ± 0.04 cm) in diameter and shall have a No. 5-40UNC-2A thread.
9. The prong, 0.032 inch ± 0.002 inch (0.812 cm ± 0.005 cm) in diameter and 1/4 inch ± 1/64 inch (0.64 cm ± 0.04 cm) in length, shall be soldered or electronically fused to the vertical center line of the coat of arms so that it will fit into the hole in the disc and not interfere with the thumb nut when it is screwed down on the post.
10. Support bars between laurel leaves and wings and arrow heads and wings shall be 1/32 inch + 1/64 inch - 0 (0.08 cm + 0.04 cm - 0) wide and 1/16 inch (0.16 cm) long (REF).
11. Insignia may be manufactured using 22 karat gold plate with nickel underplating for commercial sale only.

Custodian:
Army - IH

Review activities:
DLA - CT

Preparing activities:
Army - IH

(Project No. 8455-0680)

Source: https://assist.dla.mil - Downloaded: 2026-10-18T06:35Z
Check the source to verify that this is the current version before use.