MIL-I-15665 / 23B
15 March 1988
SUPERSEDING
MIL-I-15665 / 23A
30 September 1975

MILITARY SPECIFICATION SHEET

INSIGNIA, SERVICE CAP, EP; MARINE CORPS

This specification is approved for use by all Departments and Agencies of the Department of Defense. The complete requirements for procuring the item(s) described herein shall consist of this document and the issue in effect of Specification MIL-I-15665.



MATERIAL:
INSIGNIA (EXCEPT SCREW POST, NUT & WASHER): RED BRASS
SCREW POST, NUT & WASHER: ANY TYPE BRASS
DIMENSIONS (INCHES):
HEIGHT (OVERALL): 1-21/32 (REF)
WIDTH (OVERALL): 1-9/16 (REF)
THICKNESS (MIN): .055

FINISH:
-1: BRIGHT DIPPED, MIRROR-LIKE POLISH
-2: FLAT BLACK ENAMEL

NOTES:
1. A FORCER SHALL BE USED TO BRING UP THE DESIGN.
2. THE SCREW POST SHALL BE SOLDERED OR ELECTRONICALLY FUSED TO THE INSIGNIA IN THE POSITION SHOWN.
3. THE ATTACHING DEVICE SHALL BE A SCREW POST AND THUMB NUT. THE SCREW POST SHALL BE 9/16 ± 1/32 INCH LONG, 1/8 INCH IN DIAMETER AND SHALL HAVE A NO. 5-40UNC-2A THREAD.
4. THE WASHER SHALL BE MADE FROM ANY TYPE OF BRASS. THE WASHER SHALL HAVE A 7/8 INCH OUTSIDE DIAMETER AND 1/8 INCH, +1/32, -0 INCH INSIDE DIAMETER. THE WASHER SHALL BE .020 ± .003 INCH THICK.
5. THE THUMB NUT SHALL BE .625 ± .010 INCH IN DIAMETER AND SHALL HAVE A NO. 5-40UNC-2B THREAD.

Custodian:
Army - IH
Navy - MC

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455 - 0269)

FSC 8455

AMSC N/A

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T06:35Z
Check the source to verify that this is the current version before use.