MIL-I-15665 / 27C
15 March 1988
SUPERSEDING
MIL-I-15665 / 27B
5 February 1986

MILITARY SPECIFICATION SHEET

INSIGNIA, HAT; THE SERGEANT MAJOR OF THE ARMY AND THE CHIEF MASTER SERGEANT OF THE AIR FORCE

This specification is approved for use by all Departments and Agencies of the Department of Defense. The complete requirements for procuring the item(s) described herein shall consist of this document and the issue in effect of Specification MIL-I-15665.



DASH NOS.
-1: SERGEANT MAJOR OF THE ARMY
-2: CHIEF MASTER SERGEANT OF THE AIR FORCE

MATERIAL: RED BRASS
DIMENSIONS (INCHES):
BASE (WREATH):
HEIGHT (OVERALL): 1-15/16 (REF)
WIDTH (OVERALL): 2-1/16 (REF)
THICKNESS (EDGE): .080 ± .010
DEVICE (EAGLE):
HEIGHT (OVERALL): 1-5/8 (REF)
WIDTH (OVERALL): 1-9/16 (REF)
THICKNESS (WING & TAIL FEATHER TIPS): .050 ± .010

FINISH:
-1: GOLD ELECTROPLATED, SATIN FINISH WITH HIGHLIGHTS POLISHED.
-2: NICKEL PLATED, SILVER PLATED, OXIDIZED, RELIEVED, SATIN FINISH.

FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T06:37Z
Check the source to verify that this is the current version before use.

NOTES:

1. THE INSIGNIA SHALL BE FABRICATED IN TWO PIECES WITH THE DEVICE SOLDERED TO THE BASE IN THE LOCATION SHOWN. THE DEVICE SHALL BE SOLDERED TO THE BASE IN THREE PLACES, AT THE TIP OF EACH WING AND AT THE TAIL FEATHERS.
2. A FULL FORCER IS ALLOWED TO BRING UP THE DESIGN OF THE DEVICE (EAGLE).
3. PIERCED AREAS SHALL BE AS INDICATED.
4. THE ATTACHING DEVICE SHALL BE A SCREW POST WITH NUT AND TWO REGISTERING PRONGS. THE SCREW POST SHALL BE LOCATED ON THE VERTICAL CENTERLINE OF THE DEVICE 1/8 ± 1/32 INCH ABOVE THE TOP OF THE SHIELD. THE REGISTRATION PRONGS SHALL BE LOCATED ON A HORIZONTAL LINE 5/16 ± 1/32 INCH BELOW THE TOP OF THE WREATH AND SHALL BE CENTERED ACROSS THE WIDTH OF THE WREATH.
5. THE SCREW POST SHALL BE 9/16 ± 1/32 INCH LONG, 1/8 INCH IN DIAMETER AND SHALL HAVE A NO. 5-40UNC-2A THREAD.
6. THE THUMB NUT SHALL BE .625 ± .010 INCH IN DIAMETER AND SHALL HAVE A NO. 5-40UNC-2B THREAD.
7. THE REGISTERING PRONG SHALL BE 1/4 ± 1/64 INCH IN LENGTH AND .032 ± .002 INCH IN DIAMETER.

Custodian:
Army - IH
Air Force - 11

Review activity:
Air Force - 82,99
DLA - CT

User activity:
Air Force - 45

Preparing activity:
Army - IH

(Project No. 8455 - 0269)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T06:37Z
Check the source to verify that this is the current version before use.