NOT MEASUREMENT SENSITIVE

MIL-DTL-15665/27F
27 June 1996
SUPERSEDING
MIL-I-15665/27E
29 October 1993

DETAIL SPECIFICATION SHEET

INSIGNIA, SERVICE CAP, ENLISTED, THE SEARGEANT MAJOR OF THE U.S. ARMY AND THE CHIEF MASTER SERGEANT OF THE U.S. AIR FORCE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-15665 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.



DASH NO.
-1: Sergeant Major of the U.S. Army
-2: Chief Master Sergeant of the U.S. Air Force

MATERIAL: Red Brass

FINISH:
-1: Gold Plated, Matte Finish, Polished Highlights and shall match TIOH Metal Finish Chip Number 8.
-2: Nickel Plated, Antiqued with Glossy Black Lacquer and Brightly polished Highlights.

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-18T06:37Z
Check the source to verify that this is the currentversion before use.

DIMENSIONS:

BASE (Wreath):

HEIGHT (Overall): 1-15/16 inch (7.46 cm) (REF)

WIDTH (Overall): 2-1/16 inch (5.24 cm) (REF)

THICKNESS (Edge): 0.080 inch ± 0.010 inch (0.203 cm ± 0.025 cm)

DEVICE (Eagle):

HEIGHT (Overall): 1-5/8 inch (4.13 cm) (REF)

WIDTH (Overall): 1-9/16 inch (3.97 cm) (REF)

THICKNESS (Wing & Tail Feather Tips): 0.050 inch ± 0.010 inch (0.127 cm ± 0.025 cm)

NOTES:

1. The term (REF) refers to measurements taken from the Government furnished hub or die.

2. The insignia shall be fabricated in two pieces. The device shall be soldered to the base at the tip of each wing and at the tail feathers for a total of three places.

3. A full forcer is allowed to bring us the design of the device (Eagle).

4. Pierced areas shall be as indicated.

5. The attaching device shall be a screw post with thumb nut and two registering prongs. The screw post shall be located on the vertical center line of the device 1/8 inch ± 1/32 inch (0.32 cm ± 0.08 cm) above the top of the shield. The registration prongs shall be located on a horizontal line 5/16 inch ± 1/32 inch (0.79 cm ± 0.08 cm) below the top of the wreath and shall be centered across the width of the wreath.

6. The screw post shall be 9/16 inch ± 1/32 inch (1.43 cm ± 0.08 cm) in length, 1/8 inch 0.32 cm in diameter and shall have a No. 5-40 UNC-2A thread.

7. The thumb nut shall be 0.625 inch ± 0.010 inch (1.695 cm ± 0.025 cm) in diameter and shall have a No. 5-40 UNC-2B thread.

8. The registering prong shall be 1/4 inch ± 1/64 inch (0.64 cm ± 0.04 cm) in length and 0.032 inch ± 0.002 inch (0.081 ± 0.005 cm) in diameter.

9. At the option of the manufacturer for commercial sale only, Dash No. -1 insignia may be manufactured using 22 karat gold plate with a mirror-like polished finish and nickel underplating which shall match TIOH Metal Finish Chip Number 11.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH
Air Force - 45

Preparing activity:
Army - IH

Review activities:
Air Force - 32, 89, 99
DLA - CT

(Project No. 8455-0843)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T06:37Z
Check the source to verify that this is the current version before use.