NOT MEASUREMENT SENSITIVE

MIL-DTL-15665/27J
3 June 2024
SUPERSEDING
MIL-DTL-15665/27H
29 July 2019

DETAIL SPECIFICATION SHEET

INSIGNIA, SERVICE CAP, ENLISTED, THE SERGEANT MAJOR OF THE U.S. ARMY AND THE CHIEF MASTER SERGEANT OF THE U.S.AIR FORCE

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-15665.



DASH NO.
-1: Sergeant Major of the U.S. Army, Gold
-2: Sergeant Major of the U.S. Army, Brass
-3: Chief Master Sergeant of the Air Force

MATERIAL (-1,-2 and -3): Red Brass 85/15 (UNS Alloy No. C-230)

FINISH:
-1: 24K Gold Plated, Matte Finish, Polished Highlights and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 8.
-2: Brass, Oxidized, Buffed Relieved and shall match Metal Finish Chip Number 4.
-3: Nickel Plated, Antigued with Glossy Black Lacquer and Brightly Polished Highlights.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T06:37Z
Check the source to verify that this is the current version before use.

DIMENSIONS:
BASE (Wreath):
HEIGHT (Overall): 1-15/16 inches (REF)
WIDTH (Overall): 2-1/16 inches (REF)
THICKNESS (Edge): 0.080 inch ± 0.010 inch
DEVICE (Eagle):
HEIGHT (Overall): 1-15/16 inches (REF)
WIDTH (Overall): 2-1/16 inches (REF)
THICKNESS (Wing & tail feather tips): 0.080 inch ± 0.010 inch

ATTACHING DEVICE:
1. The attaching device shall be a screw post with thumb nut and two registering prongs. The screw post shall be located on the vertical center line of the device 1/8 inch ± 1/32 inch above the top of the shield. The registration prongs shall be located on a horizontal line 5/16 inch ± 1/32 inch below the top of the wreath and shall be centered across the width of the wreath.

2. The screw post shall be 9/16 inch ± 1/32 inch in length, 1/8 inch 0.32 cm in diameter and shall have a No. 5-40 UNC-2A thread.

3. The thumb nut shall be 0.625 inch ± 0.010 inch in diameter and shall have a No. 5-40 UNC-2B thread.

4. The registering prong shall be 1/4 inch ± 1/64 inch in length and 0.032 inch ± 0.002 inch in diameter.

NOTES:
1. The term (REF) refers to measurements taken from the Government furnished hub or die.

2. The insignia shall be fabricated in two pieces. The device shall be soldered to the base at the tip of each wing and at the tail feathers for a total of three places.

3. A full forcer is allowed to bring up the design of the device (Eagle).

4. At the option of the manufacturer for commercial sale only, for -1 insignia may be manufactured using 22 karat Gold Plated with a Mirror-like Polished and nickel underplating which shall match TIOH Metal Finish Chip Number 9.

CHANGES FROM PREVIOUS ISSUE: The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T06:37Z
Check the source to verify that this is the current version before use.

Custodians:
Army - IH
Air Force - 11

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2024-166)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T06:37Z
Check the source to verify that this is the current version before use.