UU-P-546C
January 11, 1974
SUPERSEDING
Int. Fed. Spec. UU-P-00546B
September 22, 1966

FEDERAL SPECIFICATION

PAPER, TABULATING MACHINE CONTINUOUS FLAT FOLD

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers tabulating forms for use on automatic data processing equipment equipped with a sprocket feed mechanism.

1.2 Classification.

1.2.1 Types and styles. Tabulating forms covered by this specification shall be of the following types and styles, as specified (see 6.2).

Type I - Single copy.
Type II - Multi-copy.
Style A - Carbon interleaved.
Style B - Chemical Transfer Carbonless.
Style C - Chemical Self-imaging Carbonless.
Style D - Physical Transfer Carbonless Paper.
Style E - Physical Self-imaging Carbonless.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specifications:

PPP-B-636 - Boxes, Shipping, Fiberboard.
PPP-F-320 - Fiberboard; Corrugated and Solid, Sheet Stock (Container Grade), and Cut Shapes.

Federal Standard:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civil Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which included cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification and Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Services Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

Technical Association of the Pulp and Paper Industry (TAPPI) Standards:

T 402 - Standard Conditioning and Testing Atmospheres for Paper, Board, Pulp Handsheets and Related Products.
T 410 - Weight per Unit Area (Basis Weight or Substance) of Paper and Paperboard.
T 411 - Thickness (Caliper) of Paper and Paperboard.

(Application for copies may be obtained from the Technical Association of the Pulp and Paper Industry, One Dunwoody Park, Atlanta, GA 30341.)

National Motor Freight Traffic Association, Inc., Agent:

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Associations, Inc., Tariff Order Section, 1616 P Street, N.W., Washington, DC 20036.)

Uniform Classification Committee, Agent:

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 Performance. Unless otherwise specified (see 6.2), tabulating paper in accordance with this specification shall be constructed to provide satisfactory processing on a high speed printer (IBM 1403 NI, Univac, RCA 301 or similar machines), decollator, or other forms handling equipment. All parts of multipart forms shall produce legible copy when tested as specified in 4.4.1.

3.2 Materials.

3.2.1 Paper. The paper shall be made from fibrous cellulosic material and by such processes as to insure compliance with this specification.

3.2.1.1 Basis weight. When the basis weight of the paper is specified (see 6.2), this is expressed as the weight of 1000 sheets of paper of a basic ream size of 17 by 22 inches. A weight tolerance of plus or minus 5 percent shall be permitted.

3.2.1.2 Thickness. When the thickness of the paper is specified (see 6.2), it shall be expressed in inches, and allowable tolerances shall be stated.

3.2.1.3 Sizing. The paper shall be suitably sized for writing on with ink without spreading or feathering, when tested as specified in 4.4.2.

3.2.1.4 Color. Unless otherwise specified (see 6.2), the color of the paper shall be white.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

3.2.2 Carbon leaves. The carbon leaves used with type II, style A, tabulating paper sets shall be in a continuous strip, black, of good quality, and with the necessary graded sensitivity to insure clear, legible copies on all parts of the set, when processed on a high speed printer (see 3.1). The carbon coating may cover only the area between marginal aligning strips or extend to the edge of the carbon tissue at the contractor's option.

3.3 Punching and perforations.

3.3.1 Marginal aligning strips. Forms shall include marginal aligning strips of not less than 3/8 inch nor more than 5/8 inch on the left and right sides, with or without vertical tearline perforations as specified (see 6.2). Width of the aligning strips within these limitations shall be at the supplier's option, unless otherwise specified (see 6.2).

3.3.1.1 Vertical tearline perforations. The location of the vertical tearline(s) and whether parts and carbons or parts only are to be perforated shall be as specified (see 6.2). When vertical tearline perforations are specified, the cut and uncut portions shall be such as to insure straight and proper tears. Perforation cuts shall not intersect cuts in horizontal perforations.

3.3.1.2 Horizontal tearline perforations. Horizontal tearline perforations shall be positioned 1/4 inch above the center of the top marginal aligning holes within the form (applicable when form length is evenly divisible by 1/2 inch) and shall be accurately positioned at a 90° angle to a vertical line through the center of all marginal aligning holes in either margin. The perforations shall be cut through both forms and carbons. The cut and uncut portions shall be such as to insure straight and proper tears.

3.3.1.3 All perforations shall be clean cut and sufficiently deep to permit easy separation but not to tear in ordinary handling or in feeding through the machine.

3.3.2 Marginal punching. Tabulating paper in accordance with this specification shall be punched in the right and left aligning margins with round holes 5/32 inch + 1/64 inch in diameter, except that the holes adjacent to the top and bottom horizontal tearline perforations in both margins shall be 3/16 inch ± 1/64 inch. The bottom marginal holes of a form shall be located 1/4 inch ± 1/32 inch above the horizontal tearline perforation and all holes shall be set 1/4 inch + 1/64 inch or -1/32 inch from the edge of the form, measured to the center of the hole. Holes shall be spaced vertically 1/2 inch, center to center, for full length of the forms and identically located on all copies of all sets throughout each pack of forms. The marginal holes shall extend in a straight line parallel to the sides of the continuous strip, perpendicular to the horizontal perforations. Holes punched in carbons shall be not less than the actual size of the holes punched in the form and not greater than 7/32 inch in diameter. Carbons shall be punched in the margin(s) which is flush with the edge of the form. Carbons positioned between and extending from the inner edge of the marginal holes on one side of the form to the inner edge of the form holes on the opposite margin are not punched. Holes in carbons shall be centered with the corresponding holes in the form. All holes must be clean cut and the forms, as delivered, completely free of waste.

3.3.3 File punching. When specified (see 6.2), prepunched holes 1/4 inch ± 1/16 inch in diameter shall be located at the top, bottom, or top and bottom of each set, 5/8 inch ± 1/8 inch from the horizontal perforation measured to the center of the hole. The number of holes and distance between holes shall be as specified, with a tolerance of ± 1/16 inch. Unless otherwise specified, the holes shall be equidistant from the vertical edges of the form when the perforated margin portion is removed.

3.4 Joining. Type II forms shall be joined in the marginal aligning strip by one of the following methods as specified (see 6.2). Temporary joining (a fastening which permits gravity or mechanical separation of parts and carbon leaves, as applicable, without the necessity of first stripping off the fastened marginal aligning strip), permanent joining (a fastening which requires stripping off the fastened marginal aligning strip before separating parts and, as applicable, carbon leaves), or combination joining (a fastening which combines temporary and permanent fastening and requires stripping off the fastened marginal aligning strip before separating parts and carbon leaves).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

3.4.1 Temporary joining. Temporary joining shall include one of the following:

3.4.1.1 Crimping. Crimping is a method of joining in which the forms are die embossed or cut in one or both marginal aligning strips thereby interlocking the parts and, as applicable, carbons. Narrow unpunched carbon leaves shall be engaged by two prongs of a four prong crimp in one margin and by at least one prong of the crimp in the opposite margin. Crimps shall be spaced at not more than 3 inch intervals and shall fall not closer than 1/2 inch to the horizontal tearlines.

3.4.1.2 Fugitive gluing. Fugitive gluing is a method of pasting a carbon to the back of the preceding part with a special glue that will hold sufficiently so to keep carbon in place on the printer and release when forms pass over a carbon decollator. Forms shall also be crimped in both margins with not less than two prongs. Crimps shall be spaced at not more than 3 inch intervals and shall not fall closer than 1/2 inch to the horizontal tearline.

3.4.2 Permanent joining. Permanent joining shall include firm gluing, or flexible stub.

3.4.2.1 Firm gluing is a method in which adhesive is applied within the marginal aligning strip(s) in such a manner that the forms are tightly held. A combination of fanfolding and firm gluing, open on one side, may be furnished.

3.4.2.2 Flexible stub is a method of construction in which adhesive is applied within the marginal aligning strip(s) and the strip(s) is constructed in such a manner as to allow parts and carbons to move and adjust to each other as the sets pass through the machine.

3.4.3 Combination joining. Combination joining shall include any combination of temporary and permanent fastening suitable for the use specified.

3.5 Assembly of forms. All forms shall be marginally punched (see 3.3.2) and flat-folded. When specified, forms shall be furnished with vertical perforations (see 3.3.1.1) and punch holes for filing (see 3.3.3). Multi-part sets shall be joined by one of the methods in 3.4 (see 6.2). A form set shall be that material between two consecutive horizontal perforations.

3.5.1 Type I. Type I sets shall consist of a continuous strip of paper, conforming to 3.2.1, flat-folded at the horizontal tearline perforations to produce the number of single part sets specified in section 5 for each unit container (see 6.2). Unless otherwise specified (see 6.2), the basis weight of the paper shall be 40 pounds.

3.5.2 Type II, style A. Type II, style A, sets shall consist of one or more continuous strips of paper conforming to 3.2.1, interleaved with a continuous strip(s) of carbon paper conforming to 3.2.2. The number of strips (parts) comprising a multi-part set shall be as specified (see 6.2). The sets shall be flat-folded at the horizontal tearline to produce the number of multi-part sets specified in section 5 for each container. Unless otherwise specified (see 6.2), the basis weight of paper and carbon interleaves shall be as selected by the contractor to insure compliance with 3.1. The width of the carbon strip with respect to the paper strip shall be full width, full width on one edge and short on the other, or short both edges, as specified (see 6.2). The method of joining shall be in accordance with 3.4 and as specified (see 6.2).

3.5.3 Type II, style B. Type II, style B, sets shall consist of 2 to 6 strips of surface coated papers. The coatings shall be chemically reactive materials so that the impact of the printer type face on the top part of a multi-part set shall develop images of the imprinted characters on subsequent underlying parts. The top strip shall be coated on the back (CB) and the bottom sheet shall be coated on the front (CF). Middle parts shall be coated front and back (CFB). The front and back surface coatings shall be the same color. The number of strips (parts) comprising a multi-part set shall be as specified (see 6.2). The sets shall be flat-folded at the horizontal tearline to produce the number of multi-part set specified in section 5 for each unit container. The basis weight of the paper shall be selected by the contractor to insure compliance with 3.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

3.5.4 Type II, style C. Type II, style C, sets shall consist of two to six strips of pressure activated self-imaging paper. The self-imaging paper shall be so fabricated that impact of the printer type face on the top part of multi-part sets shall develop images of the imprinted characters on subsequent underlying parts. The number of strips (parts) comprising a multi-part set shall be as specified (see 6.2). The sets shall be flat-folded at the horizontal tearline to produce the number of multi-part sets specified in section 5 for each unit container. The basis weight of the paper shall be selected by the contractor to insure compliance with 3.1.

3.5.5 Type II, style D. Type II, style D, sets shall consist of two to eight strips of paper coated face and back. The sequence of coatings (CB-CFB-CF) and principle of operation are similar to the construction specified in 3.5.3 except that the back coating (CB) shall be gray or gray-black. The color and number of strips (parts) comprising the set shall be as specified (see 6.2). The strips shall be flat-folded at the horizontal tearline to produce the number of multi-part sets specified in section 5 for each unit container. The basis weight of the paper shall be selected by the contractor to insure compliance with 3.1.

3.5.6 Type II, style E. Type II, style E, sets shall consist of two to eight strips of paper, coated on the back with a gray or gray-black coating, except that the last strip in the sequence shall be uncoated. The color and number of strips (parts) comprising the set shall be as specified (see 6.2). The strips shall be flat-folded at the horizontal tearline to produce the number of multi-part sets specified in section 5 for each unit container. The basis weight of the paper shall be selected by the contractor to insure compliance with 3.1.

3.6 Dimensions. The tabulating forms shall be furnished in the size(s) specified (see 6.2). The width shall be the overall form width in inches including the marginal aligning strips. The length shall be the distance in inches between the horizontally perforated tear lines.

3.6.1 Form tolerances. A tolerance of ± 1/16 inch shall be allowed on the width of the forms. The length shall not vary by more than ± 1/32 inch from the specified length. The length of a strip of forms whose total length comes the closest to 120 inches shall not vary by more than ± 3/32 inch from the specified length of a single form times the number of forms in the strip.

3.6.2 Carbon paper tolerances. The carbon paper used to interleave type II, style A, forms shall be furnished in the width specified (see 6.2). When full width carbons are specified they shall extend the full width of the form. The carbon paper shall extend not more than 1/32 inch beyond either vertical edge nor be less than 1/16 inch narrower than the form. When carbons are specified to be short on one or both margins, the location of the carbon paper edge and the tolerances permitted shall be as specified (see 6.2). The length of the carbons shall not vary from the actual form length by more than ± 1/64 inch and the length of the carbons for a continuous length of sets closest to 120 inches shall not vary from the length of the forms by more than ± 1/16 inch.

3.7 Printing. Tabulating paper forms shall be printed as specified (see 6.2). Printing may consist of horizontal lines or alternate shaded areas as follows:

3.7.1 Line printing. When specified, horizontal lines shall be printed on the face of the forms with black, gray, or green ink. There shall be 1, 2, 3, 4, or 6 lines per inch as specified (see 6.3). All horizontal lines shall be positioned at a 90° angle to a vertical line through the center of all marginal aligning holes in either margin. Discontinuities in broken lines shall not exceed 1/8 inch. The last line of a set need not be printed if it falls on a horizontal perforation.

3.7.1.1 One line per inch. When one line per inch is specified, all lines shall be heavy with the first line one inch below the top horizontal perforation. All subsequent lines shall be one inch apart.

3.7.1.2 Two lines per inch. When two lines per inch are specified, the lines shall be alternatively heavy and light or broken. The first line shall be heavy and 1/2 inch below the top horizontal perforation. All lines shall be 1/2 inch apart.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

3.7.1.3 Three lines per inch. When three lines per inch are specified, the first and second lines shall be light or broken and the third line shall be heavy. Every third line thereafter shall be heavy. The first line shall be 1/3 inch below the top horizontal perforation. All lines shall be 1/3 inch apart.

3.7.1.4 Four lines per inch. When four lines per inch are specified, the first three lines shall be light or broken and the fourth line shall be heavy. Every fourth line thereafter shall be heavy. The first line shall be 1/4 inch below the top horizontal perforation. All lines shall be 1/4 inch apart.

3.7.1.5 Six lines per inch. When six lines per inch are specified, the first and fourth lines shall be heavy and the second, third, fifth, and sixth lines shall be light or broken. Every first and fourth line thereafter shall be heavy. The first line shall be 1/6 inch below the top horizontal perforation. All lines shall be 1/6 inch apart.

3.7.2 Shaded space printing. When specified (see 6.2), forms may be printed with alternate tinted light green and white spaces, in lieu of line printing. As specified, there may be 2, 3, 4, or 6 spaces per inch, beginning with a white space, then alternating green and white spaces. The width of the spaces shall be 1/2, 1/3, 1/4, or 1/6 inch ± 1/32 inch as applicable. The color depth of the tinted portion shall be such as to permit numerals or characters printed thereon to be readily distinguishable on all parts of a multi-part form.

3.8 Forms continuity. As specified (see 6.2), strips of forms within a shipping container shall have one break per container, splices not permitted; unbroken strip, one splice permitted; or unbroken strip, no splices permitted. Splices, as applicable shall be made at the horizontal tearline. The method of splicing and materials used by the contractor shall be such as to insure compliance with 3.1. There shall be not less than 100 continuous forms in any broken or spliced strip. Not more than 10 percent of the containers shall contain broken or spliced strips.

3.9 Workmanship. The forms shall be clean and free from dirt, foreign matter, tears, wrinkles, creases, folds (other than at the horizontal tearline), paper dust, lint, or grit.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Inspection. Sampling for inspection shall be performed in accordance with MIL-STD-105, except where otherwise indicated.

4.2 Inspection of components and materials. In accordance with 4.1 above, the supplier is responsible for insuring that components and materials used were manufactured, examined and tested in accordance with this specification or referenced subsidiary specifications and standards.

4.3 Inspection of the end item.

4.3.1 Examination of the end item. Examination of the end item shall be made for the defects set forth in the applicable subparagraphs at the inspection levels and acceptable quality levels (AQL's) set forth therein.

4.3.1.1 Examination of preparation for delivery. An examination shall be made to determine that markings, materials, workmanship, and contents comply with requirements of section 5. The lot size shall be expressed in units of shipping containers. The inspection level shall be S-2 and the AQL shall be 2.5 expressed as percent defective. The sample unit shall be one shipping container, fully prepared for delivery.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

Examine	Defects
Marking (exterior and interior)	Incorrect; incomplete; illegible; omitted; of improper size, location, sequence, or method of application.
Material	Any nonconforming component; components missing, damaged, or otherwise defective.
Workmanship	Inadequate application of components such as, incomplete closure of container flaps, loose or inadequate sealing, strapping, or stapling. Bulged or distorted container.
Contents	Number of form sets per shipping container less than specified.
Weight	Net weight exceeds requirement.

4.3.1.1.1 Forms continuity. Examine the contents of the shipping containers selected under 4.3.1.1 for the defects listed below. The acceptable quality level (AQL) shall be 2.5 percent defective.

Examine	Defects
Forms continuity	Not as specified; less than 100 sets between breaks or splices.
Splices, as applicable	Not at horizontal tearline; not neatly made.

4.3.1.2 Examination for defects in appearance, workmanship, and construction. The sample unit for this examination shall be one continuous strip of 50 sets. The lot size for the purpose of determining the sample size shall be expressed in units of sets in the lot. The sample size shall be S-1 and the acceptable quality level (AQL) shall be 2.5 percent defective. The sets comprising the sample unit shall be randomly selected from the sets in the shipping containers sampled under 4.3.1.1.

Examine	Defects
Appearance	
Printing, as applicable	Not as specified; lines missing; not black, gray or green; printed both sides; not horizontal; heavy lines not as specified. Shaded spaces, as applicable, not as specified.
Paper	Dirt specks larger than 0.5 mm in area; oil, size, glue, or slime spots; foreign matter; fuzz or loose particles.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

(Cont.)

Examine	Defects
Appearance	
Carbon paper, as applicable	Not black; coating not uniform, coated two sides.
Workmanship	Wrinkles, creases, or folds (fold at horizontal tearline is not a defect). Tears, cuts, or holes (marginal aligning holes, file holes, and perforations are not defects). Ragged, uneven, or crushed edges.
Construction	
General	Not as specified for the type.
Marginal punching	Hole missing, not punched clean or misaligned. Holes in carbons, as applicable, smaller than in the paper, not centered with holes in form. Holes of multi-part forms not aligned.
Perforations	Not as specified; missing. Vertical perforations not parallel to line through center of marginal aligning holes, incomplete. Horizontal perforations not perpendicular to line through center of marginal aligning holes, incomplete. Can not be separated without tearing form; separated along perforation. Horizontal and vertical cuts intersect.
File holes, as applicable	Not as specified.
Joining	Not as specified.
Crimping	Not as specified; crimps fall on tearline perforations.
Fugitive glue	Not as specified; crimps missing, forms tear when decollated.
Firm gluing	Glueline not positioned as specified. Glue extends beyond vertical perforations onto form body.
Flexible stub	Not as specified.

4.3.1.3 Examination for dimensional defects. The sample unit for this examination shall be a continuous strip of forms whose length comes closest to 120 inches. The lot size for the purpose of determining the sample size shall be expressed in units of sets in the lot. The sample size shall be S-1 and the acceptable quality level shall be 2.5 percent defective. The sets comprising the sample unit shall be randomly selected from the sets in the shipping containers sampled under 4.3.1.1. The examination for length of a continuous strip shall be made on the entire sample unit. All other dimensional examinations shall be made on one set.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

Examine	Defects
Carbon paper, as applicable	
Length	Carbon paper in a continuous length of sets closest to 120 inches varies from length of forms by more than ± 1/16 inch.
Width	Not as specified.
Vertical tearline perforations	Not located as specified.
Marginal punching	Holes not 5/32 ± 1/64 inch in diameter except holes adjacent to top and bottom horizontal perforations, not 3/16 ± 1/64 inch. Center of holes not located 1/4 + 1/64 or - 1/32 inch from the edge of the form. Center of bottom hole not located 1/4 ± 1/64 inch above horizontal perforation. Holes not properly spaced.
Carbon paper, as applicable	Holes greater than 7/32 inch or less than 5/32 inch.
Filing holes	Holes not equidistant from vertical edges when margin is removed. Holes more than 5/8 ± 1/8 inch from the horizontal perforation. Holes diameter more or less than 1/4 ± 1/16 inch.

4.3.2 Testing of the end item. The end item shall be tested for performance and writing quality. The sample unit for performance shall be 100 complete sets (see 4.4.1) and for writing quality and basis weight, as applicable, (see 4.4.2 and 4.4.3) shall be five complete sets. The lot size shall be expressed in units of 100 sets of tabulating forms. The sample size shall be S-1 and there shall be no failure to pass the performance, writing quality, or, as applicable, basis weight tests.

4.4 Test procedures.

4.4.1 Performance. Feed 100 complete sets of the tabulating paper, single or multi-part forms, as applicable through a high speed printer (IBM 1403, Model N-1 or equal) at approximately 1200 lines per minute. The printer shall be properly adjusted for the number of parts in the set and with the printer activated to print randomly selected information utilizing the working area of each of the 100 sheets in the set. Note continuity of operation and legibility of copy on all parts of the set. To be considered satisfactory the operation shall be free from jams or interruptions caused by the paper construction and the information shall be readily distinguishable on all parts of the form set.

4.4.2 Writing quality. Characters shall be written on each part of a set with a one (1) percent aqueous solution of Acid Red 1 Color Index Number 18050 or Acid Green 3 Color Index Number 42085 (see 6.3). To be considered satisfactory, the characters shall be clear cut and shall not feather.

4.4.3 Basis weight. The basis weight, as applicable, shall be determined in accordance with TAPPI method T 410 after samples are conditioned in accordance with TAPPI method T 402. To be considered satisfactory, the lot average shall meet the specified weight, with a tolerance of plus or minus 5 percent.

4.4.4 Thickness. The thickness, as applicable, shall be determined in accordance with TAPPI method T 411 after samples are conditioned in accordance with TAPPI method T 402. To be considered satisfactory, the lot average shall meet the specified thickness with allowable tolerances.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Packing. Tabulating paper, in the quantities shown in table I shall be packed in accordance with level A, B, or C, as specified (see 6.2).

TABLE I. Number of sets per shipping container

Part(s) per set	Basis weight (17 X 22 - 1000)	Sets per shipping container
1 - part	30 - 32	3,200
1 - part	40	2,500
2 - parts	18 - 32	1,500
3 - parts	18 - 32	950
4 - parts	18 - 32	700
5 - parts	18 - 32	550
6 - parts	18 - 32	500
7 - parts	18 - 32	400
8 - parts	18 - 32	350

5.1.1 Level A. Tabulating machine paper sets of one type, style, part(s) and size, in the quantities specified in table I shall be packed in a close-fitting fiberboard box conforming to PPP-B-636, style RSC, grade V3c or V3s. The sets shall be compressed after being placed in the box. Top and bottom fiberboard pads shall be provided in each box. The fiberboard pads shall be grade 200 or better. Closure shall be in accordance with the appendix to PPP-B-636. When specified (see 6.2), the fiberboard box shall conform to style RSC, grade V2s of PPP-B-636.

5.1.2 Level B. Tabulating machine paper sets of one type, style, part(s) and size, in the quantity specified in table I, shall be packed in a box conforming to PPP-B-636, class domestic, grade 275. The sets shall be compressed after being placed in the box. Top and bottom fiberboard pads shall be provided in each box. The pads shall be fiberboard conforming to PPP-F-320, grade not less than 125. The box shall be closed by method II closure of the appendix to PPP-B-636.

5.1.2.1 When specified (see 6.2), the fiberboard shipping container shall be a grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method III as specified in the appendix of the container specification.

5.1.3 Level C. Tabulating machine paper sets, in the quantities specified in table I, shall be packed in containers to assure carrier acceptance and safe arrival at destination in compliance with Uniform Freight Classification or National Motor Freight Classification, as applicable.

5.2 Marking. In addition to any special markings required in the procurement documents, marking of the exterior shipping containers shall be in accordance with Fed. Std. No. 123 for civil agencies or MIL-STD-129 for military agencies, as applicable (see 6.2).

6. NOTES

6.1 Intended use. Tabulating paper forms covered by this specification are used on electro-mechanical line printers, tabulating machines, mechanical bursters, and decollators.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

6.2 Ordering data. Purchasers shall select the preferred options permitted herein and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Type, style, and size required (see 1.2.1 and 3.6).
(c) Whether vertical tearline perforations and location thereof are required (see 3.3.1).
(d) Number of parts for type II sets (see 3.5.2, 3.5.3, 3.5.4, 3.5.5, and 3.5.6).
(e) Basis weight of paper, as applicable (see 3.2.1.1).
(f) Method of joining (see 3.4).
(g) Width and tolerance of carbon leaves, as applicable (see 3.6.2).
(h) Location, center to center distance of filing holes, as applicable (see 3.3.3).
(i) Forms continuity (see 3.8).
(j) Printing required (see 3.7).
(k) Type of equipment on which forms are to be used (see 3.1).
(l) Selection of applicable levels of packing (see 5.1).
(m) When weather resistant grade fiberboard shipping containers are required for level B packing (see 5.1.2.1).
(n) When V2s box is required (see 5.1.1).
(o) Color, as applicable (see 3.2.1.4).
(p) Thickness, as applicable (see 3.2.1.2).

6.3 Color index. Acid Red 1 Color Index Number 18050 may be obtained from Textile Aniline and Chemical Company. Acid Green 3 Color Index Number 42085 may be obtained from the following: Sandoz, Incorporated; National Aniline Division of Allied Chemical Corporation, Geigy Chemical Corporation; and American Cyanamid Company.

Military Coordinating Activity:

Army - GL

Military Custodians:

Army - GL
Air Force - 84

User Activities:

Navy - SA

Review Activity:

Army - MD

Preparing Activity:

GSA - FSS

CIVIL AGENCY COORDINATING ACTIVITIES:

COM - NBS
GSA - FSS
HEW - SSA
VA - DMS

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See Section 2 of this specification to obtain extra copies and other documents referenced herein. Price 15 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.