[INCH - POUND]

UU-P-546D
July 11, 1990
SUPERSEDING
UU-P-546C
January 11, 1974

FEDERAL SPECIFICATION

PAPER, TABULATING MACHINE CONTINUOUS FLAT FOLD

This specification is approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers tabulating forms for use on automatic data processing equipment equipped with a sprocket feed mechanism.

1.2 Classification.

1.2.1 Types and styles. Tabulating forms covered by this specification shall be of the following types and styles, as specified (see 6.2).

Type I - Single copy

Type II - Multi-copy
Style A - Carbon interleaved
Style B - Chemical Transfer Carbonless
Style C - Chemical Self-imaging Carbonless

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited

FSC 7530

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specifications:

PPP-B-636 Boxes, Shipping, Fiberboard
PPP-F-320 Fiberboard; Corrugated and Solid, Sheet Stock (Container Grade), and Cut Shapes

Federal Standard:

Fed. Std. No. 123 Marking for Domestic Shipment (Civil Agencies)

Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which included cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

Single copies of this specification and Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Services Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angeles, and Auburn, WA.

Federal Government activities may obtain copies of Federal Specification, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.

Federal Supply Schedule:

Federal Supply Schedule, Copying Equipment Supplies, FSC Group 36 Part IV, FSC Class 3610

Federal agencies may obtain copies of Federal Supply Schedules from: General Services Administration, Centralized Mailing List Service (CAIL), 819 Taylor Street, P.O. Box 17077, Fort Worth, TX 76102-0077.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

Individuals and nongovernment entities may obtain copies of Federal Supply Schedules from: General Services Administration, FSS Information Center (FFNI), Washington DC 20406.

Military Standards:

MIL-STD-105 Sampling Procedures and Tables for Inspection by Attributes

MIL-STD-129 Marking for Shipment and Storage

Copies of Military Specifications and Standards required by suppliers in connection with specific procurement functions may be obtained from the U.S. Navy Publication and Forms Center, Standardization Documents Order Desk, Bldg. 4D, 700 Robins Avenue, Phila., PA 19111-5094.

2.2 Other publications The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

Technical Association of the Pulp and Paper Industry (TAPPI) Standards

T 400 - Sampling and Accepting a single lot of paper, paperboard, fiberboard, or related product
T 401 - Fiber Analysis of Paper and Paperboard
T 402 - Standard Conditioning and Testing Atmospheres for Paper, Board, Pulp Handsheets and Related Products.
T 410 - Weight per Unit Area (Basis Weight or Substance) of Paper and Paperboard.
T 411 - Thickness (Caliper) of Paper and Paperboard.
T 452 - Brightness of Pulp, Paper, and Paperboard (Directional Reflectance at 457 nm)
T 524 - L, a, b, 45° 0° colorimetry of white and near-white paper and paperboard

(Application for copies may by obtained from the Technical Association of the Pulp and Paper Industry, P.O. Box 105113, Atlanta, GA 30348.)

National Motor Freight Traffic Association, Inc., Agent:

National Motor Freight Classification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

(Application for copies should be addressed to the American Trucking Associations, Inc., Tariff Order Section, 1616 P Street, N.W., Washington, DC 20036.)

Uniform Classification Committee, Agent:

Uniform Freight Classification.

Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.

Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.

3. REQUIREMENTS

3.1 Performance and capability of being copied Unless otherwise specified (see 6.2), tabulating paper in accordance with this specification shall be constructed to provide satisfactory processing on high speed printers (IBM 1403 NI, Univac, RCA 301 and similar machines), decollators, and other forms handling equipment. All parts of multipart form shall produce legible copies and shall be capable of being copied (for Type II, only) when tested as specified in 4.4.1.

3.2 Materials

3.2.1 Paper The paper shall be made from not less than 95 percent bleached chemical pulp, with not more than 5 percent unbleached and/or groundwood pulp (see 4.2.3). No polychlorinated biphenyls (PCB's) shall be added or used during the manufacture of the paper or in any coating operation on the base paper. As evidence of compliance, the contractor shall submit a certificate stating that no polychlorinated biphenyls have been added or used during the manufacturing or converting operations.

For designated carbonless forms only and provided that all other requirements are met, the paper may be made from a minimum 40 percent bleached chemical pulp and a maximum 60 percent groundwood, when tested as specified in 4.2.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

3.2.1.1 Regulatory requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practicable.

3.2.1.2 Basis Weight When the basis weight of the paper is specified (see 6.2), this shall be expressed as the weight of 500 sheets of paper of a basic ream size of 17 by 22 inches. The basis weight tolerance shall be plus or minus 5 percent unless otherwise specified. Basis weight shall be tested in accordance with 4.2.1.

3.2.1.3 Thickness When the thickness of the paper is specified (see 6.2), it shall be expressed in inches, and allowable tolerances shall be stated. Thickness shall be tested in accordance with 4.2.2.

3.2.1.4 Sizing The paper shall be suitably sized for writing on with ink without spreading or feathering. Conformance shall be determined by testing in accordance with 4.4.2.

3.2.1.5 Color Unless otherwise specified (see 6.2), the color of the paper shall be white with:

Y greater than 64
L greater than 80 or L^* greater than 84

On the average, neither $(a^2 + b^2)^{1/2}$ nor $(a^{*2} + b^{*2})^{1/2}$ shall exceed 10.

Conformance shall be determined by testing in accordance with 4.4.3. The color shall be maintained for at least one year from date of acceptance.

3.2.1.6 Brightness The brightness shall be 78% minimum, unless otherwise specified (see 6.2). Conformance shall be determined in accordance with 4.4.4.

3.2.2 Carbon leaves The carbon leaves used with type II, style A, tabulating paper sets shall be in a continuous strip, black, of good quality, and with the necessary graded sensitivity to ensure clear, legible copies on all parts of the set, when processed on a high speed printer (see 3.1). The carbon coating may cover only the area between marginal aligning strips or extend to the edge of the carbon tissue, at the contractor's option.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

3.3 Perforations and punching

3.3.1 Perforations All perforations shall be clean cut and sufficiently deep to permit easy separation but not to tear in ordinary handling or in feeding through the machine.

3.3.1.1 Marginal aligning strips Forms shall include marginal aligning strips of not less than 3/8 inch nor more than 5/8 inch on the left and right sides, with or without vertical tearline perforations, as specified (see 6.2). Width of the aligning strips within these limitations shall be at the supplier's option, unless otherwise specified (see 6.2).

3.3.1.2 Vertical tearline perforations The location of the vertical tearline(s) and whether parts and carbons or parts only are to be perforated shall be as specified (see 6.2). When vertical tearline perforations are specified, the cut and uncut portions shall be such as to ensure straight and proper tears.

3.3.1.3 Horizontal tearline perforations Horizontal tearline perforations shall be positioned 1/4 inch above the center of the top marginal aligning holes within the form (applicable when form length is evenly divisible by 1/2 inch) and shall be positioned at a 90° angle to a vertical line through the center of all marginal aligning holes in either margin. The perforations shall be cut through both forms and carbons. The cut and uncut portions shall be such as to ensure straight and proper tears.

3.3.1.4 Microperforations Perforations of all one part and first part of multi-part forms sized 9 1/2" x 11" shall contain a minimum of 50 ties per inch for the vertical and horizontal tearlines, unless specified otherwise (see 6.2). Conformance shall be determined in accordance with 4.3.5.

3.3.2 Punching

3.3.2.1 Marginal punching Tabulating paper in accordance with this specification shall be punched in the right and left aligning margins with round holes 5/32 inch $\pm$ 1/64 inch in diameter, except that the holes adjacent to the top and bottom horizontal tearline perforations in both margins shall be 3/16 inch $\pm$ 1/64 inch. The bottom marginal holes of a form shall be located 1/4 inch $\pm$ 1/32 inch above the horizontal tearline perforation and all holes shall be set 1/4 inch + 1/64 inch or - 1/32 inch from the edge of the form, measured to the center of the hole.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

Holes shall be spaced vertically 1/2 inch ± 1/64 inch, center to center, for full length of the forms and identically located on all copies of all sets throughout each pack of forms. The marginal holes shall extend in a straight line parallel to the sides of the continuous strip, perpendicular to the horizontal perforations. Holes punched in carbons shall not be less than the actual size of the holes punched in the form and not greater than 7/32 inch in diameter. Carbons shall be punched in the margin(s) which is flush with the edge of the form. Carbons positioned between and extending from the inner edge of the marginal holes on one side of the form to the inner edge of the form holes on the opposite margin are unpunched. Holes in carbons shall be centered with the corresponding holes in the form. All holes must be clean cut and the forms, as delivered, completely free of waste.

3.3.2.2 File punching When specified (see 6.2), prepunched holes 1/4 inch ± 1/16 inch in diameter shall be located at the top, bottom, or top and bottom of each set, 5/8 inch ± 1/8 inch from the horizontal perforation measured to the center of the hole. The number of holes and distance between holes shall be as specified, with a tolerance of ± 1/16 inch. Unless otherwise specified, the holes shall be equidistant from the vertical edges of the form when the perforated margin portion is removed.

3.4 Joining Type II forms shall be joined in the marginal aligning strip by one of the following methods (see 3.4.1 through 3.4.3) as specified (see 6.2):

(a) Temporary joining - a fastening which permits gravity or mechanical separation of parts and carbon leaves, as applicable, without the necessity of first stripping off the fastened marginal aligning strip.
(b) Permanent joining - a fastening which requires stripping off the fastened marginal aligning strip before separating parts and, as applicable, carbon leaves
(c) Combination joining - a fastening which combines temporary and permanent fastening and requires stripping off the fastened marginal aligning strip before separating parts and carbon leaves.

3.4.1 Temporary joining Temporary joining shall include one of the following:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

3.4.1.1 Crimping Crimping is a method of joining in which the forms are die embossed or cut in one or both marginal aligning strips thereby interlocking the parts and, as applicable, carbons. Narrow unpunched carbon leaves shall be engaged by at least one prong of a four prong crimp in one margin and by at least one prong of the crimp in the opposite margin. Crimps shall be spaced at not more than 3 inch intervals and shall fall not closer than 3/8 inch to the horizontal tearlines.

3.4.1.2 Fugitive gluing Fugitive gluing is a method of pasting a carbon to the back of the preceding part with a special glue that will hold sufficiently so to keep carbon in place on the printer and release when forms pass over a carbon decollator. Forms shall also be crimped in both margins with not less than two prongs. Crimps shall be spaced at not more than 3 inch intervals and shall not fall closer than 3/8 inch to the horizontal tearline.

3.4.2 Permanent joining Permanent joining shall include firm gluing, or flexible stub.

3.4.2.1 Firm gluing Firm gluing is a method in which adhesive is applied within the marginal aligning strip(s) in such a manner that the forms are tightly held. A combination of fanfolding and firm gluing, open on one side, may be furnished.

3.4.2.2 Flexible stub Flexible stub is a method of construction in which adhesive is applied within the marginal aligning strip(s) and the strip(s) is constructed in such a manner as to allow parts and carbons to move and adjust to each other as the sets pass through the machine.

3.4.3 Combination joining Combination joining shall include any combination of temporary and permanent fastening suitable for the use specified.

3.5 Assembly of forms All forms shall be marginally punched (see 3.3.2) and flat folded. When specified, forms shall be furnished with vertical perforations (see 3.3.1.1) and punched holes for filing (see 3.3.2.2). Multipart sets shall be joined by one of the methods in 3.4 (see 6.2). A form set shall be that material between two consecutive horizontal perforations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

3.5.1 Type I Type I sets shall consist of a continuous strip of paper, conforming to 3.2.1, flat folded at the horizontal tearline perforations to produce the number of single part sets specified in section 5 for each unit container (see 6.2). Unless otherwise specified (see 6.2), the basis weight of the paper shall be 20 pounds.

3.5.2 Type II, Style A Type II, Style A, sets shall consist of two or more continuous strips of paper conforming to 3.2.1, interleaved with a continuous strip(s) of carbon paper conforming to 3.2.2. The number of strips (parts) comprising a multipart set shall be as specified (see 6.2). The sets shall be flat folded at the horizontal tearline to produce the number of multipart sets specified in section 5 for each container. Unless otherwise specified (see 6.2) the basis weight of paper and carbon interleaves shall be as selected by the contractor to insure compliance with 3.1. The width of the carbon strip with respect to the paper strip shall be full width, full width on one edge and short on the other, or short both edges, as specified (see 6.2). The method of joining shall be in accordance with 3.4, as specified (see 6.2).

3.5.3 Type II, Style B Type II, Style B, sets shall consist of 2 to 6 strips of surface coated papers. The coatings shall be chemically reactive materials so that the impact of the printer type face on the top part of a multipart set shall develop images of the imprinted characters on subsequent underlying parts. The top strip shall be coated on the back (CB) and the bottom sheet shall be coated on the front (CF). Middle parts shall be coated front and back (CFB). The front and back surface coatings shall be the same color. The number of strips (parts) comprising a multipart set shall be as specified (see 6.2). The sets shall be flat folded at the horizontal tearline to produce the number of multipart set specified in section 5 for each unit container. Unless otherwise specified (see 6.2) the basis weight of the paper shall be as selected, by the contractor, to insure compliance with 3.1.

3.5.4 Type II, Style C Type II, Style C, sets shall consist of two to six strips of pressure activated self-imaging paper. The self-imaging paper shall be so fabricated that impact of the printer type face on the top part of multipart sets shall develop images of the imprinted characters on subsequent underlying parts. The number of strips (parts) comprising a multipart set shall be as specified (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

The sets shall be flat-folded at the horizontal tearline to produce the number of multipart sets specified in section 5 for each unit container. Unless otherwise specified (see 6.2) the basis weight of the paper shall be as selected from Table I, by the contractor, to insure compliance with 3.1.

3.6 Dimensions The tabulating forms shall be furnished in the size(s) specified (see 6.2). The width shall be the overall form width in inches including the marginal aligning strips. The length shall be the distance in inches between the horizontal perforated tear lines.

3.6.1 Form tolerances A tolerance of ± 1/16 inch shall be allowed on the width of the forms. The length shall not vary by more than ± 1/32 inch from the specified length. The length of a strip of forms whose total length is nearest to 120 inches shall not vary by more than ± 3/32 inch from the specified length of a single form times the number of forms in the strip.

3.6.2 Carbon paper tolerances The carbon paper used to interleave type II, style A, forms shall be furnished in the width specified (see 6.2). When full width carbons are specified they shall extend the full width of the form. The carbon paper shall extend not more than 1/32 inch beyond either vertical edge nor be less than 1/16 inch narrower than the form. When carbons are specified to be short on one or both margins, the location of the carbon paper edge and the tolerances permitted shall be as specified (see 6.2). The length of the carbons shall not vary from the actual form length by more than ± 1/64 inch and the length of the carbons for a continuous length of sets closest to 120 inches shall not vary from the length of the forms by more than ± 1/16 inch.

3.7 Printing Tabulating paper forms shall be printed as specified (see 6.2). Printing may consist of horizontal lines or alternate shaded areas as follows:

3.7.1 Line printing When specified, horizontal lines shall be printed on the face of each part in the form set with black, gray, or green ink. There shall be 1, 2, 3, 4, or 6 lines per inch as specified (see 6.2). All horizontal lines shall be positioned at a 90° angle to a vertical line through the center of all marginal aligning holes in either margin. Discontinuities in broken lines shall not exceed 1/8 inch. The last line of a set need not be printed if it falls on a horizontal perforation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

3.7.1.1 One line per inch When one line per inch is specified, all lines shall be heavy with the first line one inch below the top horizontal perforation. All subsequent lines shall be one inch apart.

3.7.1.2 Two lines per inch When two lines per inch are specified, the lines shall be alternatively heavy and light or broken. The first line shall be heavy and 1/2 inch below the top horizontal perforation. All lines shall be 1/2 inch apart.

3.7.1.3 Three lines per inch When three lines per inch are specified, the first and second lines shall be light or broken and the third line shall be heavy. Every third line thereafter shall be heavy. The first line shall be 1/3 inch below the top horizontal perforation. All lines shall be 1/3 inch apart.

3.7.1.4 Four lines per inch When four lines per inch are specified, the first three lines shall be light or broken and the fourth line shall be heavy. Every fourth line thereafter shall be heavy. The first line shall be 1/4 inch below the top horizontal perforation. All lines shall be 1/4 inch apart.

3.7.1.5 Six lines per inch When six lines per inch are specified, the first and fourth lines shall be heavy and the second, third, fifth, and sixth lines shall be light or broken. Every first and fourth line thereafter shall be heavy. The first line shall be 1/6 inch below the top horizontal perforation. All lines shall be 1/6 inch apart.

3.7.2 Shaded space printing When specified (see 6.2), forms shall be printed with alternate tinted light green and white spaces, in lieu of line printing. As specified, there shall be 2, 3, 4, or 6 spaces per inch, beginning with a white space, then alternating green and white spaces. The width of the spaces shall be 1/2, 1/3, 1/4, or 1/6 inch $\pm$ 1/32, inch as applicable. The color depth of the tinted portion shall be such as to permit numerals or characters printed thereon to be readily distinguishable on all parts of a form.

3.8 Forms continuity Each strip shall have no more than one break per shipping container with not less than 100 continuous forms in any broken strip. Not more than 10 percent of the shipping containers shall contain broken strips. No splices shall be permitted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

3.9 Workmanship The forms shall be clean and free from dirt, foreign matter, tears, wrinkles, creases, folds (other than at the horizontal tearline), paper dust, lint, or grit or other defects which adversely affect appearance or serviceability.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Inspection Sampling for inspection shall be performed in accordance with MIL-STD-105, except where otherwise indicated.

4.2 Component testing Each lot of paper used in the manufacture of the tabulating forms shall be sampled and tested for basis weight (as applicable), thickness (as applicable) and fiber analysis, in accordance with the methods specified in 4.2.1, 4.2.2 and 4.2.3, respectively.

4.2.1 Basis Weight The basis weight, as applicable, shall be determined in accordance with TAPPI method T 410 after samples are conditioned in accordance with TAPPI method T 402. To be considered satisfactory, the lot average shall meet the specified weight, with a tolerance of plus or minus 5 percent, unless otherwise specified.

4.2.2 Thickness The thickness, when applicable, shall be determined in accordance with TAPPI method T 411 after samples are conditioned in accordance with TAPPI method T 402. To be considered satisfactory, the lot average shall meet the specified thickness, within allowable tolerances.

4.2.3 Fiber analysis The paper shall be tested in accordance with TAPPI Method T 401 to determine conformance with the composition requirement specified in 3.2.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

4.3 Visual and Dimensional Examinations

4.3.1 Examination of preparation for delivery An examination shall be made to determine that markings, materials, workmanship, and contents comply with requirements of section 5. The lot size shall be expressed in units of shipping containers. The inspection level shall be S-2 and the AQL shall be 2.5 expressed as percent defective. The sample unit shall be one shipping container, fully prepared for delivery.

4.3.2 Forms continuity When applicable, examine the contents of the shipping containers selected under 4.3.1 for conformance with 3.8, applying the same accept reject numbers as derived in 4.3.1.

4.3.3 Examination for defects in appearance, workmanship, and construction The sample unit for this examination shall be one continuous strip of 50 sets. The lot size for the purpose of determining the sample size shall be expressed in units of sets in the lot. The sample size shall be S-1 and the acceptable quality level (AQL) shall be 2.5 percent defective.

The sets comprising the sample unit shall be randomly selected from the sets in the shipping containers sampled under 4.3.1. Samples shall be examined for conformance to the requirements of section 3 of this specification, not otherwise covered by specific tests or examinations.

4.3.4 Examination for dimensional defects The sample unit for this examination shall be a continuous strip of forms whose length comes closest to 120 inches. The lot size for the purpose of determining the sample size shall be expressed in units of sets in the lot. The sample size shall be S-1 and the acceptable quality level shall be 2.5 percent defective. The sets comprising the sample unit shall be randomly selected from the sets in the shipping containers sampled under 4.3.1. The examination for length of a continuous strip shall be made on the entire sample unit. All other dimensional examinations shall be made on one set. Examination shall be made for conformance with specified dimensions.

4.3.5 Microperforations Microperforations, as applicable, shall be examined as follows:

Randomly, select a sample consisting of two attached sheets.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

Carefully examine the vertical perforations along each side of the sheets and the undetached horizontal perforations between the two sheets. There shall be no more than two ties (the uncuted area between perforated cuts) in succession which exceed 1/32 of an inch each in length for each of the sheets examined.

The number of ties per inch of the vertical perforations on the right side margin is determined by using a magnifier having a minimum magnification of ten and a measuring device capable of measuring to one sixteenth inch, or smaller. Align the center of one of the ties to the center of one of the markings on the device. Mark off an inch length of perforation, and count the number of ties within that length. Repeat the above procedure for the vertical perforations on the left side margin and for one of the horizontal perforations. There shall be not less than the required number of ties per inch for any of the perforations examined.

4.4 End Item Tests The end item shall be tested for performance and capability of being copied, writing quality, color, and brightness in accordance with the methods in 4.4.1, 4.4.2, 4.4.3, and 4.4.4, respectively. The sample unit for performance testing shall be 100 (one-hundred) complete sets, and for writing quality shall be 5 (five) complete sets.

The lot size shall be expressed in terms of 100 (one-hundred) sets of tabulating forms. The inspection level shall be S-1, with an AQL of 2.5 percent defective.

4.4.1 Performance and capability of being copied Feed 100 complete sets of the tabulating paper, single or multi-part forms, as applicable through a high speed printer at 1200 lines per minute. The printer shall be properly adjusted for the number of parts in the set and with the printer activated to print randomly selected information utilizing the working area of each complete set in the sample unit. To be considered satisfactory, the operation shall be free from jams or interruptions caused by the paper construction and the information shall be readily distinguishable on all parts of the form set. Capability of being copied (applies to Type II, only) shall be determined by randomly selecting 2 tested sets from those tested above, and making copies of all parts of each set. Use any one model from those copiers listed under Federal Supply Schedules Group 36 Part IV and copy each part of the set. Examine each of the copies for legibility. To be satisfactory, all copies shall be legible.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

4.4.2 Writing quality Characters shall be written on one part (chosen alternately, from specimen to specimen) of a set with a one (1) percent aqueous solution of Acid Red 1 Color Index Number 18050 or Acid Green 3 Color Index Number 42085 (see 6.3). To meet the requirement of 3.2.1.4, the characters shall be clear cut and shall not feather.

4.4.3 Color The color conformance with 3.2.1.5 shall be determined in accordance with TAPPI T524. To be considered satisfactory, the value of ΔE shall not exceed 1.75.

4.4.4 Brightness The brightness, in accordance with 3.2.1.6, applicable, shall be determined in accordance with TAPPI T452.

5. PREPARATION FOR DELIVERY

5.1 Packing Tabulating paper, in the quantities shown in Table I shall be packed in accordance with level A, B, or C, as specified (see 6.2).

Table I. Number of Sets per Shipping Container

Part(s) per set	Basis weight (17x22-500)	Sets per shipping container tolerance +3/-1 set
1 - part	15	3,200
1 - part	20	2,500
2 - parts	9 - 16	1,500
3 - parts	9 - 16	950
4 - parts	9 - 16	700
5 - parts	9 - 16	550
6 - parts	9 - 16	500

5.1.1 Level A Tabulating machine paper sets of one type, style, part(s) and size, in the quantities specified in Table I shall be packed in a close-fitting fiberboard box conforming to PPP-B-636, style RSC, grade V3c or V3s. The sets shall be compressed after being placed in the box. Top and bottom fiberboard pads shall be provided in each box. The fiberboard pads shall be grade 200 or higher. Closure shall be any acceptable method in accordance with the appendix to PPP-B-636. When specified (see 6.2), the fiberboard box shall conform to style RSC, grade V2s of PPP-B-636.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

5.1.2 Level B Tabulating machine paper sets of one type, style, part(s) and size, in the quantity specified in Table I, shall be packed in a box conforming to PPP-B-636, class domestic, grade 275. The sets shall be compressed after being placed in the box. Top and bottom fiberboard pads shall be provided in each box. The pads shall be fiberboard conforming to PPP-F-320, grade not less than 125. The box shall be closed by method II closure of the appendix to PPP-B-636.

5.1.2.1 When specified (see 6.2), the fiberboard shipping container shall be a grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method III, as specified, in the appendix of the container specification.

5.1.3 Level C Tabulating machine paper sets of one type, style, part(s) and size, in the quantities specified in table I, shall be packed in containers to assure carrier acceptance and safe arrival at destination in compliance with Uniform Freight Classification or National Motor Freight Classification, as applicable.

5.2 Marking In addition to any special markings required in the procurement documents, marking of the exterior shipping containers shall be in accordance with Fed. Std. No. 123 for delivery to civil agencies; or, MIL-STD-129 for delivery to military agencies, as applicable (see 6.2). Unless otherwise specified (see 6.2), bar code marking is required.

6. NOTES

6.1 Intended use Tabulating paper forms covered by this specification are used on electro-mechanical line printers, tabulating machines, mechanical bursters, and decollators.

6.2 Ordering data Purchasers shall select the preferred options permitted herein and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Type, style, and size required (see 1.2.1 and 3.6).
(c) Type of equipment on which forms are to be used (see 3.1).
(d) Basis weight of paper, as applicable (see 3.2.1.2).
(e) Thickness, when applicable (see 3.2.1.3).
(f) Color, as applicable (see 3.2.1.5).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

(g) Brightness, when applicable (see 3.2.1.6).
(h) Whether vertical tearline perforations and location thereof are required (see 3.3.1.1 and 3.3.1.2).
(i) Location, center to center distance of filing holes, as applicable (see 3.3.2.2).
(j) Method of joining (see 3.4).
(k) Number of parts for type II set (see 3.5.2, 3.5.3 and 3.5.4).
(l) Width and tolerance of carbon leaves, as applicable (see 3.6.2).
(m) Line and shade printing required (see 3.7).
(n) Selection of applicable levels of packing (see 5.1).
(o) When weather resistant grade fiberboard shipping containers are required for level B packing (see 5.1.2.1.).
(p) When V2s box is required (see 5.1.1).
(q) If microperforations are not required for 9 1/2" x 11" forms (see 3.3.1.4).
(r) If bar code marking is not required (see 5.2).

6.3 Color index Acid Red 1 Color Index Number 18050 may be obtained from Pylam Products, International Dyestuffs Corp., Sandoz, Incorporated and Ciba-Geigy Chemical Corp. Acid Green 3 Color Index Number 42085 may be obtained from Pylam Products and International Dyestuffs Corp.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

6.4 Item identifiers/reference part number system (for cataloging use only)

UUP546 - 1A1A1A1 This example describes a single copy, 8 1/2" x 11", 1-part, carbon interleaved, no printing, 500 sets per box and vertical marginal perforations on left side tabulating machine continuous flat fold paper.

_VERTICAL MARGINAL PERFORATIONS:
1 - Left Side
2 - Right Side
3 - Both Sides
4 - None
5 - As specified

__SETS PER BOX:
A - 500
B - 550
C - 700
D - 950
E - 1500
F - 2500
G - 3200
H - As specified

___PRINTING:
1 - No Printing
2 - 3 Horizontal lines per inch
3 - 1/2" wide green shaded areas
4 - As specified

____STYLE:
A - Carbon Interleaved
B - Chemical Transfer Carbonless
C - Chemical Self-imaging Carbonless
D - Optional, B or C
E - Not applicable
F - As specified

_____PART:
1 - 1-Part
2 - 2-Part
3 - 3-Part
4 - 4-Part
5 - 5-Part
6 - 6-Part
7 - As specified

______SIZE:
A - 8 1/2" x 11"
B - 9 1/2" x 11"
C - 9 7/8" x 11"
D - 13 5/8" x 3 2/3"
E - 14 7/8" x 11"
F - As specified

_______TYPE:
1 - Type I - Single Copy
2 - Type II - Multi-copy

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

Military Coordinating Activity:
Army - GL

Preparing Activity:
GSA - FSS

Military Custodians:
Army - GL
Air Force - 99

Civil Agency Coordinating Activities:
COM - NIST
VA - OSS
HHS - SSA
VA - OSS

User Activity:
Navy - SA

Review Activity:
Army - MD
Air Force - 84

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.